

Package ‘AnnotationDbi’

April 4, 2014

Title Annotation Database Interface

Description Provides user interface and database connection code for annotation data packages using SQLite data storage.

Version 1.24.0

Author Herve Pages, Marc Carlson, Seth Falcon, Nianhua Li

Maintainer Bioconductor Package Maintainer <maintainer@bioconductor.org>

Depends R (>= 2.7.0), methods, utils, BiocGenerics (>= 0.5.4), Biobase (>= 1.17.0)

Imports methods, utils, DBI, RSQLite, BiocGenerics, Biobase, IRanges

Suggests DBI (>= 0.2-4), RSQLite (>= 0.6-4), hgu95av2.db, GO.db, org.Sc.sgd.db, org.At.tair.db, KEGG.db, RUnit, TxDb.Hsapiens.UCSC.hg19.knownGene, hom.Hs.actome.db, AnnotationForge, graph, org.TguttataTestingSubset.eg.db

Collate 00RTobjs.R unlist2.R AllGenerics.R AllClasses.R FlatBimap.R SQL.R AnnDbObj-lowAPI.R Bimap.R GOTerms.R BimapFormatting.R Bimap-envirAPI.R flatten.R methods-AnnotationDb.R methods-seqnames.R methods-geneCentricDbs.R methods-ReactomeDb.R methods-Inparanoid.R loadDb.R createAnnObjs-utils.R createAnnObjs.NCBIORG_DBs.R createAnnObjs.NCBICHIP_DBs.R createAnnObjs.ORGANISM_DB.R createAnnObjs.YEASTCHIP_DB.R createAnnObjs.COELICOLOR_DB.R createAnnObjs.ARABIDOPSISCHIP_DB.R createAnnObjs.MALARIA_DB.R createAnnObjs.YEAST_DB.R createAnnObjs.YEASTNCBI_DB.R createAnnObjs.ARABIDOPSIS_DB.R createAnnObjs.GO_DB.R createAnnObjs.KEGG_DB.R createAnnObjs.INPARANOID_DB.R createAnnObjs.PFAM_DB.R AnnDbPkg-templates-common.R AnnDbPkg-checker.R print.probetable.R makeMap.R inpIDMapper.R test_AnnotationDbi_package.R

License Artistic-2.0

biocViews Annotation, Infrastructure

R topics documented:

ACCNUM	2
AnnDbObj-objects	4
AnnDbPkg-checker	6
AnnotationDb-objects	7
AnnotationDbi-defunct	9
AnnotationDbi-deprecated	9
Bimap	10
Bimap-direction	13
Bimap-envirAPI	16
Bimap-keys	17
Bimap-toTable	19
BimapFormatting	22
GOFrame	23
GOID	24
GOTerms-class	25
HOMO_SAPIENS	26
inpIDMapper	30
KEGGFrame	33
makeGOGraph	33
make_eg_to_go_map	34
print.probetable	35
supportedSeqnameStyles	36
toggleProbes	38
toSQLStringSet	40
unlist2	41
Index	42

ACCNUM

*Descriptions of available values for columns and keytypes.***Description**

This manual page enumerates the kinds of data represented by the values returned when the user calls columns or keytypes

Details

All the possible values for columns and keytypes are listed below. Users will have to actually use these methods to learn which of the following possible values actually apply in their case.

ACCNUM: GenBank accession numbers

ALIAS: Commonly used gene symbols

ARACYC: KEGG Identifiers for arabidopsis as indicated by aracyc

ARACYCENZYMES: Aracyc enzyme names as indicated by aracyc

CHR: Chromosome
CHRLOC: Chromosome and starting base of associated gene
CHRLOCEND: Chromosome and ending base of associated gene
COMMON: Common name
DESCRIPTION: The description of the associated gene
ENSEMBL: The ensembl ID as indicated by ensembl
ENSEMBLPROT: The ensembl protein ID as indicated by ensembl
ENSEMBLTRANS: The ensembl transcript ID as indicated by ensembl
ENTREZID: Entrez gene Identifiers
ENZYME: Enzyme Commission numbers
EVIDENCE: Evidence codes for GO associations with a gene of interest
EVIDENCEALL: Evidence codes for GO (includes less specific terms)
GENENAME: The full gene name
GO: GO Identifiers associated with a gene of interest
GOALL: GO Identifiers (includes less specific terms)
INTERPRO: InterPro identifiers
IPI: IPI accession numbers
MAP: cytoband locations
OMIM: Online Mendelian Inheritance in Man identifiers
ONTOLOGY: For GO Identifiers, which Gene Ontology (BP, CC, or MF)
ONTOLOGYALL: Which Gene Ontology (BP, CC, or MF), (includes less specific terms)
ORF: Yeast ORF Identifiers
PATH: KEGG Pathway Identifiers
PFAM: PFAM Identifiers
PMID: Pubmed Identifiers
PROBEID: Probe or manufacturer Identifiers for a chip package
PROSITE: Prosite Identifiers
REFSEQ: Refseq Identifiers
SGD: Saccharomyces Genome Database Identifiers
SMART: Smart Identifiers
SYMBOL: The official gene symbol
TAIR: TAIR Identifiers
UNIGENE: Unigene Identifiers
UNIPROT: Uniprot Identifiers

To get the latest information about the date stamps and source URLs for the data used to make an annotation package, please use the metadata method as shown in the example below.

Unless otherwise indicated above, the majority of the data for any one package is taken from the source indicated by either it's name (if it's an org package) OR from the name of it's associated org package. So for example, org.Hs.eg.db is using "eg" in the name to indicate that most of the data in that package comes from NCBI entrez gene based data. And org.At.tair.db uses data that primarily comes from tair. For chip packages, the relevant information is the organism package that they depend on. So for example, hgu95av2.db depends on org.Hs.eg.db, and is thus primarily based on NCBI entrez gene ID information.

Author(s)

Marc Carlson

Examples

```
library(hgu95av2.db)
## List the possible values for columns
columns(hgu95av2.db)
## List the possible values for keytypes
keytypes(hgu95av2.db)
## get some values back
keys <- head(keys(hgu95av2.db))
keys
select(hgu95av2.db, keys=keys, columns=c("SYMBOL", "PFAM"),
keytype="PROBEID")

## More information about the dates and original sources for these data:
metadata(hgu95av2.db)
```

AnnDbObj-objects

AnnDbObj objects

Description

The AnnDbObj class is the most general container for storing any kind of SQLite-based annotation data.

Details

Many classes in AnnotationDbi inherit directly or indirectly from the AnnDbObj class. One important particular case is the [AnnDbBimap](#) class which is the lowest class in the AnnDbObj hierarchy to also inherit the [Bimap](#) interface.

Accessor-like methods

In the code snippets below, x is an AnnDbObj object.

`dbconn(x)`: Return a connection object to the SQLite DB containing x's data.

`dbfile(x)`: Return the path (character string) to the SQLite DB (file) containing x's data.

`dbmeta(x, name)`: Print the value of metadata whose name is 'name'. Also works if x is a DBIConnection object.

`dbschema(x, file="", show.indices=FALSE)`: Print the schema definition of the SQLite DB. Also works if x is a DBIConnection object.

The file argument must be a connection, or a character string naming the file to print to (see the file argument of the `cat` function for the details).

The CREATE INDEX statements are not shown by default. Use `show.indices=TRUE` to get them.

`dbInfo(x)`: Prints other information about the SQLite DB. Also works if x is a DBIConnection object.

See Also

[dbConnect](#), [dbListTables](#), [dbListFields](#), [dbGetQuery](#), [Bimap](#)

Examples

```
library("hgu95av2.db")

dbconn(hgu95av2ENTREZID)      # same as hgu95av2_dbconn()
dbfile(hgu95av2ENTREZID)     # same as hgu95av2_dbfile()

dbmeta(hgu95av2_dbconn(), "ORGANISM")
dbmeta(hgu95av2_dbconn(), "DBSCHEMA")
dbmeta(hgu95av2_dbconn(), "DBSCHEMAVERSION")

library("DBI")
dbListTables(hgu95av2_dbconn()) #lists all tables on connection

## If you use dbSendQuery instead of dbGetQuery
## (NOTE: for ease of use, this is definitely NOT recommended)
## Then you may need to know how to list results objects
dbListResults(hgu95av2_dbconn()) #for listing results objects

## Sometimes you may want to see all the SQLite databases that are
## presently connected in your session. To do that you have to specify
## the driver:
library("RSQLite")
drv <- dbDriver("SQLite")      #gets the driver for SQLite
dbListConnections(drv)        #List all DB Connections using drv

dbListFields(hgu95av2_dbconn(), "probes")
```

```

dbListFields(hgu95av2_dbconn(), "genes")
dbschema(hgu95av2ENTREZID)      # same as hgu95av2_dbschema()
## According to the schema, the probes._id column references the genes._id
## column. Note that in all tables, the "_id" column is an internal id with
## no biological meaning (provided for allowing efficient joins between
## tables).
## The information about the probe to gene mapping is in probes:
dbGetQuery(hgu95av2_dbconn(), "SELECT * FROM probes LIMIT 10")
## This mapping is in fact the ENTREZID map:
toTable(hgu95av2ENTREZID)[1:10, ] # only relevant columns are retrieved

dbInfo(hgu95av2G0)              # same as hgu95av2_dbInfo()

##Advanced example:
##Sometimes you may wish to join data from across multiple databases at
##once:
## In the following example we will attach the GO database to the
## hgu95av2 database, and then grab information from separate tables
## in each database that meet a common criteria.
library(hgu95av2.db)
library("GO.db")
attachSql <- paste(ATTACH ", GO_dbfile(), " as go;, sep = "")
dbGetQuery(hgu95av2_dbconn(), attachSql)
sql <- SELECT DISTINCT a.go_id AS "hgu95av2.go_id",
      a._id AS "hgu95av2._id",
      g.go_id AS "GO.go_id", g._id AS "GO._id",
      g.term, g.ontology, g.definition
      FROM go_bp_all AS a, go.go_term AS g
      WHERE a.go_id = g.go_id LIMIT 10;
data <- dbGetQuery(hgu95av2_dbconn(), sql)
data
## For illustration purposes, the internal id "_id" and the "go_id"
## from both tables is included in the output. This makes it clear
## that the "go_ids" can be used to join these tables but the internal
## ids can NOT. The internal IDs (which are always shown as _id) are
## suitable for joins within a single database, but cannot be used
## across databases.

```

Description

Check the SQL data contained in an SQLite-based annotation package.

Usage

```
checkMAPCOUNTS(pkgname)
```

Arguments

pkgnam The name of the SQLite-based annotation package to check.

Author(s)

H. Pages

See Also

[AnnDbPkg-maker](#)

Examples

```
checkMAPCOUNTS("hgu95av2.db")
checkMAPCOUNTS("GO.db")
```

AnnotationDb-objects *AnnotationDb objects and their progeny, methods etc.*

Description

AnnotationDb is the virtual base class for all annotation packages. It contains a database connection and is meant to be the parent for a set of classes in the Bioconductor annotation packages. These classes will provide a means of dispatch for a widely available set of select methods and thus allow the easy extraction of data from the annotation packages.

select, columns and keys are used together to extract data from an AnnotationDb object (or any object derived from the parent class). Examples of classes derived from the AnnotationDb object include (but are not limited to): ChipDb, OrgDb, GODb, InparanoidDb and ReactomeDb.

columns shows which kinds of data can be returned for the AnnotationDb object.

keytypes allows the user to discover which keytypes can be passed in to select or keys and the keytype argument.

keys returns keys for the database contained in the AnnotationDb object. This method is already documented in the keys manual page but is mentioned again here because its usage with select is so intimate. By default it will return the primary keys for the database, but if used with the keytype argument, it will return the keys from that keytype.

select will retrieve the data as a data.frame based on parameters for selected keys and columns and keytype arguments.

saveDb will take an AnnotationDb object and save the database to the file specified by the path passed in to the file argument.

loadDb takes a .sqlite database file as an argument and uses data in the metadata table of that file to return an AnnotationDb style object of the appropriate type.

species shows the genus and species label currently attached to the AnnotationDb objects database.

Usage

```

columns(x)
keytypes(x)
keys(x, keytype, ...)
select(x, keys, columns, keytype, ...)
saveDb(x, file)
loadDb(file, dbType, dbPackage, ...)

```

Arguments

x	the AnnotationDb object. But in practice this will mean an object derived from an AnnotationDb object such as a OrgDb or ChipDb object.
keys	the keys to select records for from the database. All possible keys are returned by using the keys method.
columns	the columns or kinds of things that can be retrieved from the database. As with keys, all possible columns are returned by using the columns method.
keytype	the keytype that matches the keys used. For the select methods, this is used to indicate the kind of ID being used with the keys argument. For the keys method this is used to indicate which kind of keys are desired from keys
file	an sqlite file path. A string the represents the full name you want for your sqlite database and also where to put it.
dbType	dbType - not required
dbPackage	dbPackage - not required
...	other arguments. These include: pattern: the pattern to match (used by keys) column: the column to search on. This is used by keys and is for when the thing you want to pattern match is different from the keytype, or when you want to simply want to get keys that have a value for the thing specified by the column argument. fuzzy: TRUE or FALSE value. Use fuzzy matching? (this is used with pattern by the keys method)

Value

keys, columns and keytypes each return a character vector or possible values. select returns a data.frame.

Author(s)

Marc Carlson

See Also

keys, [dbConnect](#), [dbListTables](#), [dbListFields](#), [dbGetQuery](#), [Bimap](#)

Examples

```
require(hgu95av2.db)
## display the columns
columns(hgu95av2.db)
## get the 1st 6 possible keys
keys <- head( keys(hgu95av2.db) )
keys
## lookup gene symbol and unigene ID for the 1st 6 keys
select(hgu95av2.db, keys=keys, columns = c("SYMBOL","UNIGENE"))

## get keys based on unigene
keyunis <- head( keys(hgu95av2.db, keytype="UNIGENE") )
keyunis
## list supported key types
keytypes(hgu95av2.db)
## lookup gene symbol and unigene ID based on unigene IDs by setting
## the keytype to "UNIGENE" and passing in unigene keys:
select(hgu95av2.db, keys=keyunis, columns = c("SYMBOL","UNIGENE"),
       keytype="UNIGENE")
```

AnnotationDbi-defunct *Defunct Functions in Package* **AnnotationDbi**

Description

The functions or variables listed here are no longer part of the AnnotationDbi package.

See Also

[Defunct](#)

AnnotationDbi-deprecated

Defunct Functions in Package **AnnotationDbi**

Description

The functions or variables listed here have been deprecated and should no longer be used.

See Also

[Deprecated](#)

Description

What we usually call "annotation maps" are in fact Bimap objects. In the following sections we present the bimap concept and the Bimap interface as it is defined in AnnotationDbi.

Display methods

In the code snippets below, `x` is a Bimap object.

`show(x)`: Display minimal information about Bimap object `x`.

`summary(x)`: Display a little bit more information about Bimap object `x`.

The bimap concept

A bimap is made of:

- 2 sets of objects: the left objects and the right objects. All the objects have a name and this name is unique in each set (i.e. in the left set and in the right set). The names of the left (resp. right) objects are called the left (resp. right) keys or the Lkeys (resp. the Rkeys).
- Any number of links (edges) between the left and right objects. Note that the links can be tagged. In our model, for a given bimap, either none or all the links are tagged.

In other words, a bimap is a bipartite graph.

Here are some examples:

1. bimap B1:

4 left objects (Lkeys): "a", "b", "c", "d"

3 objects on the right (Rkeys): "A", "B", "C"

Links (edges):

"a" <--> "A"

"a" <--> "B"

"b" <--> "A"

"d" <--> "C"

Note that:

- There can be any number of links starting from or ending at a given object.
- The links in this example are untagged.

2. bimap B2:

4 left objects (Lkeys): "a", "b", "c", "d"

3 objects on the right (Rkeys): "A", "B", "C"

Tagged links (edges):

"a" <-"x"-> "A"

"a" <-"y"-> "B"

"b" <-"x"-> "A"

"d" <-"x"-> "C"

"d" <-"y"-> "C"

Note that there are 2 links between objects "d" and "C":
1 with tag "x" and 1 with tag "y".

Flat representation of a bimap

The flat representation of a bimap is a data frame. For example, for B1, it is:

left	right
a	A
a	B
b	A
d	C

If in addition the right objects have 1 multivalued attribute, for example, a numeric vector:

```
A <-- c(1.2, 0.9)
B <-- character(0)
C <-- -1:1
```

then the flat representation of B1 becomes:

left	right	Rattrib1
a	A	1.2
a	A	0.9
a	B	NA
b	A	1.2
b	A	0.9
d	C	-1
d	C	0
d	C	1

Note that now the number of rows is greater than the number of links!

AnnDbBimap and FlatBimap objects

An AnnDbBimap object is a bimap whose data are stored in a data base. A FlatBimap object is a bimap whose data (left keys, right keys and links) are stored in memory (in a data frame for the links). Conceptually, AnnDbBimap and FlatBimap objects are the same (only their internal representation differ) so it's natural to try to define a set of methods that make sense for both (so they can be manipulated in a similar way). This common interface is the Bimap interface.

Note that both AnnDbBimap and FlatBimap objects have a read-only semantic: the user can subset them but cannot change their data.

The "flatten" generic

`flatten(x)` converts AnnDbBimap object `x` into FlatBimap object `y` with no loss of information

Note that a FlatBimap object can't be converted into an AnnDbBimap object (well, in theory maybe it could be, but for now the data bases we use to store the data of the AnnDbBimap objects are treated as read-only). This conversion from AnnDbBimap to FlatBimap is performed by the "flatten" generic function (with methods for AnnDbBimap objects only).

Property0

The "flatten" generic plays a very useful role when we need to understand or explain exactly what a given Bimap method `f` will do when applied to an AnnDbBimap object. It's generally easier to explain what it does on a FlatBimap object and then to just say "and it does the same thing on an AnnDbBimap object". This is exactly what Property0 says:

for any AnnDbBimap object `x`, `f(x)` is expected to be identical to `f(flatten(x))`

Of course, this implies that the `f` method for AnnDbBimap objects return the same type of object than the `f` method for FlatBimap objects. In this sense, the "revmap" and "subset" Bimap methods are particular because they are expected to return an object of the same class as their argument `x`, so `f(x)` can't be identical to `f(flatten(x))`. For these methods, Property0 says:

for any AnnDbBimap object `x`, `flatten(f(x))` is expected to be identical to `f(flatten(x))`

Note to the AnnotationDbi maintainers/developpers: the `checkProperty0` function (AnnDbPkg-checker.R file) checks that Property0 is satisfied on all the AnnDbBimap objects defined in a given package (FIXME: `checkProperty0` is currently broken).

The Bimap interface in AnnotationDbi

The full documentation for the methods of the Bimap interface is splitted into 4 man pages: [Bimap-direction](#), [Bimap-keys](#) and [Bimap-toTable](#).

See Also

[Bimap-direction](#), [Bimap-keys](#), [Bimap-toTable](#), [BimapFormatting](#), [Bimap-envirAPI](#)

Examples

```
library(hgu95av2.db)
ls(2)
hgu95av2G0 # calls the "show" method
summary(hgu95av2G0)
hgu95av2G02PROBE # calls the "show" method
summary(hgu95av2G02PROBE)
```

Bimap-direction	<i>Methods for getting/setting the direction of a Bimap object, and undirected methods for getting/counting/setting its keys</i>
-----------------	--

Description

These methods are part of the [Bimap](#) interface (see [?Bimap](#) for a quick overview of the [Bimap](#) objects and their interface).

They are divided in 2 groups: (1) methods for getting or setting the direction of a [Bimap](#) object and (2) methods for getting, counting or setting the left or right keys (or mapped keys only) of a [Bimap](#) object. Note that all the methods in group (2) are undirected methods i.e. what they return does NOT depend on the direction of the map (more on this below).

Usage

```
## Getting or setting the direction of a Bimap object
direction(x)
direction(x) <- value
revmap(x, ...)

## Getting, counting or setting the left or right keys (or mapped
## keys only) of a Bimap object
Lkeys(x)
Rkeys(x)
Llength(x)
Rlength(x)
mappedLkeys(x)
mappedRkeys(x)
count.mappedLkeys(x)
count.mappedRkeys(x)
Lkeys(x) <- value
Rkeys(x) <- value
subset(x, ...)
```

Arguments

<code>x</code>	A Bimap object.
<code>value</code>	A single integer or character string indicating the new direction in <code>direction(x) <- value</code> . A character vector containing the new keys (must be a subset of the current keys) in <code>Lkeys(x) <- value</code> and <code>Rkeys(x) <- value</code> .
<code>...</code>	Extra argument for <code>revmap</code> can be: <code>objName</code> The name to give to the reversed map (only supported if <code>x</code> is an AnnDbBimap object). Extra arguments for <code>subset</code> can be: <code>Lkeys</code> The new Lkeys. <code>Rkeys</code> The new Rkeys. <code>drop.invalid.keys</code> If <code>drop.invalid.keys=FALSE</code> (the default), an error will be raised if the new Lkeys or Rkeys contain invalid keys i.e. keys that don't belong to the current Lkeys or Rkeys. If <code>drop.invalid.keys=TRUE</code> , invalid keys are silently dropped. <code>objName</code> The name to give to the submap (only supported if <code>x</code> is an AnnDbBimap object).

Details

All [Bimap](#) objects have a direction which can be left-to-right (i.e. the mapping goes from the left keys to the right keys) or right-to-left (i.e. the mapping goes from the right keys to the left keys). A [Bimap](#) object `x` that maps from left to right is considered to be a direct map. Otherwise it is considered to be an indirect map (when it maps from right to left).

`direction` returns 1 on a direct map and -1 otherwise.

The direction of `x` can be changed with `direction(x) <- value` where `value` must be 1 or -1. An easy way to reverse a map (i.e. to change its direction) is to do `direction(x) <- - direction(x)`, or, even better, to use `revmap(x)` which is actually the recommended way for doing it.

The `Lkeys` and `Rkeys` methods return respectively the left and right keys of a [Bimap](#) object. Unlike the `keys` method (see [?keys](#) for more information), these methods are direction-independent i.e. what they return does NOT depend on the direction of the map. Such methods are also said to be "undirected methods" and methods like the `keys` method are said to be "directed methods".

All the methods described below are also "undirected methods".

`Llength(x)` and `Rlength(x)` are equivalent to (but more efficient than) `length(Lkeys(x))` and `length(Rkeys(x))`, respectively.

The `mappedLkeys` (or `mappedRkeys`) method returns the left keys (or right keys) that are mapped to at least one right key (or one left key).

`count.mappedLkeys(x)` and `count.mappedRkeys(x)` are equivalent to (but more efficient than) `length(mappedLkeys(x))` and `length(mappedRkeys(x))`, respectively. These functions give overall summaries, if you want to know how many Rkeys correspond to a given Lkey you can use the `nhit` function.

`Lkeys(x) <- value` and `Rkeys(x) <- value` are the undirected versions of `keys(x) <- value` (see [?keys](#) for more information) and `subset(x, Lkeys=new_Lkeys, Rkeys=new_Rkeys)` is provided as a convenient way to reduce the sets of left and right keys in one single function call.

Value

1L or -1L for direction.

A [Bimap](#) object of the same subtype as x for revmap and subset.

A character vector for Lkeys, Rkeys, mappedLkeys and mappedRkeys.

A single non-negative integer for Llength, Rlength, count .mappedLkeys and count .mappedRkeys.

Author(s)

H. Pages

See Also

[Bimap](#), [Bimap-keys](#), [BimapFormatting](#), [Bimap-envirAPI](#), [nhit](#)

Examples

```
library(hgu95av2.db)
ls(2)
x <- hgu95av2GO
x
summary(x)
direction(x)
```

```
length(x)
Llength(x)
Rlength(x)
```

```
keys(x)[1:4]
Lkeys(x)[1:4]
Rkeys(x)[1:4]
```

```
count.mappedkeys(x)
count.mappedLkeys(x)
count.mappedRkeys(x)
```

```
mappedkeys(x)[1:4]
mappedLkeys(x)[1:4]
mappedRkeys(x)[1:4]
```

```
y <- revmap(x)
y
summary(y)
direction(y)
```

```
length(y)
Llength(y)
Rlength(y)
```

```
keys(y)[1:4]
Lkeys(y)[1:4]
Rkeys(y)[1:4]
```

```
## etc...

## Get rid of all unmapped keys (left and right)
z <- subset(y, Lkeys=mappedLkeys(y), Rkeys=mappedRkeys(y))
```

Bimap-envirAPI

Environment-like API for Bimap objects

Description

These methods allow the user to manipulate any [Bimap](#) object as if it was an environment. This environment-like API is provided for backward compatibility with the traditional environment-based maps.

Usage

```
ls(name, pos, envir, all.names, pattern)
exists(x, where, envir, frame, mode, inherits)
get(x, pos, envir, mode, inherits)
#x[[i]]
#x$name

## Converting to a list
mget(x, envir, mode, ifnotfound, inherits)
eapply(env, FUN, ..., all.names, USE.NAMES)
#contents(object, all.names)

## Additional convenience method
sample(x, size, replace=FALSE, prob=NULL, ...)
```

Arguments

name	A Bimap object for <code>ls</code> . A key as a literal character string or a name (possibly backtick quoted) for <code>x\$name</code> .
pos	Ignored.
envir	Ignored for <code>ls</code> . A Bimap object for <code>mget</code> , <code>get</code> and <code>exists</code> .
all.names	Ignored.
USE.NAMES	Ignored.
pattern	An optional regular expression. Only keys matching 'pattern' are returned.
x	The key(s) to search for for <code>exists</code> , <code>get</code> and <code>mget</code> . A Bimap object for <code>[[</code> and <code>x\$name</code> . A Bimap object or an environment for <code>sample</code> .
where	Ignored.
frame	Ignored.

mode	Ignored.
inherits	Ignored.
i	Single key specifying the map element to extract.
ifnotfound	A value to be used if the key is not found. Only NA is currently supported.
env	A Bimap object.
FUN	The function to be applied (see original eapply for environments for the details).
...	Optional arguments to FUN.
size	Non-negative integer giving the number of map elements to choose.
replace	Should sampling be with replacement?
prob	A vector of probability weights for obtaining the elements of the map being sampled.

See Also

[ls](#), [exists](#), [get](#), [mget](#), [eapply](#), [contents](#), [sample](#), [BimapFormatting](#), [Bimap](#)

Examples

```
library(hgu95av2.db)
x <- hgu95av2CHRLOC

ls(x)[1:3]
exists(ls(x)[1], x)
exists("titi", x)
get(ls(x)[1], x)
x[[ls(x)[1]]]
x$titi # NULL

mget(ls(x)[1:3], x)
eapply(x, length)
contents(x)

sample(x, 3)
```

Description

These methods are part of the [Bimap](#) interface (see [?Bimap](#) for a quick overview of the [Bimap](#) objects and their interface).

Usage

```

#length(x)
isNA(x)
mappedkeys(x)
count.mappedkeys(x)
keys(x) <- value
#x[i]

```

Arguments

x	A Bimap object. If the method being called is <code>keys(x)</code> , then x can also be a <code>AnnotationDb</code> object or one of that objects progeny.
value	A character vector containing the new keys (must be a subset of the current keys).
i	A character vector containing the keys of the map elements to extract.

Details

`keys(x)` returns the set of all valid keys for map x. For example, `keys(hgu95av2GO)` is the set of all probe set IDs for chip hgu95av2 from Affymetrix.

Please Note that in addition to `Bimap` object, `keys(x)` will also work for `AnnotationDb` objects and related objects such as `OrgDb` and `ChipDb` objects.

Note also that the double bracket operator `[[` for `Bimap` objects is guaranteed to work only with a valid key and will raise an error if the key is invalid. (See [?Bimap-envirAPI](#) for more information about this operator.)

`length(x)` is equivalent to (but more efficient than) `length(keys(x))`.

A valid key is not necessarily mapped (`[[` will return an NA on an unmapped key).

`isNA(x)` returns a logical vector of the same length as x where the TRUE value is used to mark keys that are NOT mapped and the FALSE value to mark keys that ARE mapped.

`mappedkeys(x)` returns the subset of `keys(x)` where only mapped keys were kept.

`count.mappedkeys(x)` is equivalent to (but more efficient than) `length(mappedkeys(x))`.

Two (almost) equivalent forms of subsetting a `Bimap` object are provided: (1) by setting the keys explicitly and (2) by using the single bracket operator `[` for `Bimap` objects. Let's say the user wants to restrict the mapping to the subset of valid keys stored in character vector `mykeys`. This can be done either with `keys(x) <- mykeys` (form (1)) or with `y <- x[mykeys]` (form (2)). Please note that form (1) alters object x in an irreversible way (the original keys are lost) so form (2) should be preferred.

All the methods described on this pages are "directed methods" i.e. what they return DOES depend on the direction of the `Bimap` object that they are applied to (see [?direction](#) for more information about this).

Value

A character vector for keys and `mappedkeys`.

A single non-negative integer for `length` and `count.mappedkeys`.

A logical vector for isNA.

A [Bimap](#) object of the same subtype as x for x[i].

Author(s)

H. Pages

See Also

[Bimap](#), [Bimap-envirAPI](#), [Bimap-toTable](#), [BimapFormatting](#), [AnnotationDb](#), [select](#), [columns](#)

Examples

```
library(hgu95av2.db)
x <- hgu95av2GO
x
length(x)
count.mappedkeys(x)
x[1:3]
links(x[1:3])

## Keep only the mapped keys
keys(x) <- mappedkeys(x)
length(x)
count.mappedkeys(x)
x # now it is a submap

## The above subsetting can also be achieved with
x <- hgu95av2GO[mappedkeys(hgu95av2GO)]

## mappedkeys() and count.mappedkeys() also work with an environment
## or a list
z <- list(k1=NA, k2=letters[1:4], k3="x")
mappedkeys(z)
count.mappedkeys(z)

## retrieve the set of primary keys for the ChipDb object named hgu95av2.db
keys <- keys(hgu95av2.db)
head(keys)
```

Description

These methods are part of the [Bimap](#) interface (see [?Bimap](#) for a quick overview of the [Bimap](#) objects and their interface).

Usage

```

## Extract all the columns of the map (links + right attributes)
toTable(x)
nrow(x)
ncol(x)
#dim(x)
head(x, ...)
tail(x, ...)

## Extract only the links of the map
links(x)
count.links(x)
nhit(x)

## Col names and col metanames
colnames(x, do.NULL=TRUE, prefix="col")
colmetanames(x)
Lkeyname(x)
Rkeyname(x)
keyname(x)
tagname(x)
Rattribnames(x)
Rattribnames(x) <- value

```

Arguments

x	A Bimap object (or a list or an environment for nhit).
...	Further arguments to be passed to or from other methods (see head or tail for the details).
do.NULL	Ignored.
prefix	Ignored.
value	A character vector containing the names of the new right attributes (must be a subset of the current right attribute names) or NULL.

Details

toTable(x) turns [Bimap](#) object x into a data frame (see section "Flat representation of a bimap" in [?Bimap](#) for a short introduction to this concept). For simple maps (i.e. no tags and no right attributes), the resulting data frame has only 2 columns, one for the left keys and one for the right keys, and each row in the data frame represents a link (or edge) between a left and a right key. For maps with tagged links (i.e. a tag is associated to each link), toTable(x) has one additional column for the tags and there is still one row per link. For maps with right attributes (i.e. a set of attributes is associated to each right key), toTable(x) has one additional column per attribute. So for example if x has tagged links and 2 right attributes, toTable(x) will have 5 columns: one for the left keys, one for the right keys, one for the tags, and one for each right attribute (always the rightmost columns). Note that if at least one of the right attributes is multivalued then more than 1

row can be needed to represent the same link so the number of rows in `toTable(x)` can be strictly greater than the number of links in the map.

`nrow(x)` is equivalent to (but more efficient than) `nrow(toTable(x))`.

`ncol(x)` is equivalent to (but more efficient than) `ncol(toTable(x))`.

`colnames(x)` is equivalent to (but more efficient than) `colnames(toTable(x))`. Columns are named accordingly to the names of the SQL columns where the data are coming from. An important consequence of this that they are not necessarily unique.

`colmetanames(x)` returns the metanames for the column of `x` that are not right attributes. Valid column metanames are "Lkeyname", "Rkeyname" and "tagname".

`Lkeyname`, `Rkeyname`, `tagname` and `Rattribnames` return the name of the column (or columns) containing the left keys, the right keys, the tags and the right attributes, respectively.

Like `toTable(x)`, `links(x)` turns `x` into a data frame but the right attributes (if any) are dropped. Note that dropping the right attributes produces a data frame that has eventually less columns than `toTable(x)` and also eventually less rows because now exactly 1 row is needed to represent 1 link.

`count.links(x)` is equivalent to (but more efficient than) `nrow(links(x))`.

`nhit(x)` returns a named integer vector indicating the number of "hits" for each key in `x` i.e. the number of links that start from each key.

Value

A data frame for `toTable` and `links`.

A single integer for `nrow`, `ncol` and `count.links`.

A character vector for `colnames`, `colmetanames` and `Rattribnames`.

A character string for `Lkeyname`, `Rkeyname` and `tagname`.

A named integer vector for `nhit`.

Author(s)

H. Pages

See Also

[Bimap](#), [BimapFormatting](#), [Bimap-envirAPI](#)

Examples

```
library(GO.db)
x <- GOSYNONYM
x
toTable(x)[1:4, ]
toTable(x["GO:0007322"])
links(x)[1:4, ]
links(x["GO:0007322"])

nrow(x)
ncol(x)
```

```

dim(x)
colnames(x)
colmetanames(x)
Lkeyname(x)
Rkeyname(x)
tagname(x)
Rattribnames(x)

links(x)[1:4, ]
count.links(x)

y <- GOBPCHILDREN
nhy <- nhit(y) # nhy is a named integer vector
identical(names(nhy), keys(y)) # TRUE
table(nhy)
sum(nhy == 0) # number of GO IDs with no children
names(nhy)[nhy == max(nhy)] # the GO ID(s) with the most direct children

## Some sanity check
sum(nhy) == count.links(y) # TRUE

## Changing the right attributes of the GOSYNONYM map (advanced
## users only)
class(x) # GOTermsAnnDbBimap
as.list(x)[1:3]
colnames(x)
colmetanames(x)
tagname(x) # untagged map
Rattribnames(x)
Rattribnames(x) <- Rattribnames(x)[3:1]
colnames(x)
class(x) # AnnDbBimap
as.list(x)[1:3]

```

BimapFormatting

Formatting a Bimap as a list or character vector

Description

These functions format a Bimap as a list or character vector.

Usage

```

## Formatting as a list
as.list(x, ...)

## Formatting as a character vector
#as.character(x, ...)

```

Arguments

x A [Bimap](#) object.
... Further arguments are ignored.

Author(s)

H. Pages

See Also

[Bimap](#), [Bimap-envirAPI](#)

Examples

```
library(hgu95av2.db)
as.list(hgu95av2CHRLOC)[1:9]
as.list(hgu95av2ENTREZID)[1:9]
as.character(hgu95av2ENTREZID)[1:9]
```

GOFrame

GOFrame and GOAllFrame objects

Description

These objects each contain a data frame which is required to be composed of 3 columns. The 1st column are GO IDs. The second are evidence codes and the 3rd are the gene IDs that match to the GO IDs using those evidence codes. There is also a slot for the organism that these annotations pertain to.

Details

The GOAllFrame object can only be generated from a GOFrame object and its constructor method does this automatically from a GOFrame argument. The purpose of these objects is to create a safe way for annotation data about GO from non-traditional sources to be used for analysis packages like GSEABase and eventually GOstats.

Examples

```
## Make up an example
genes = c(1,10,100)
evi = c("ND", "IEA", "IDA")
GOIds = c("GO:0008150", "GO:0008152", "GO:0001666")
frameData = data.frame(cbind(GOIds, evi, genes))

library(AnnotationDbi)
frame=GOFrame(frameData,organism="Homo sapiens")
allFrame=GOAllFrame(frame)

getGOFrameData(allFrame)
```

GOID	<i>Descriptions of available values for columns and keytypes for GO.db.</i>
------	---

Description

This manual page enumerates the kinds of data represented by the values returned when the user calls columns or keytypes

Details

All the possible values for columns and keytypes are listed below.

GOID: GO Identifiers

DEFINITION: The definition of a GO Term

ONTOLOGY: Which of the three Gene Ontologies (BP, CC, or MF)

TERM: The actual GO term

To get the latest information about the date stamps and source URLs for the data used to make an annotation package, please use the metadata method as shown in the example below.

Author(s)

Marc Carlson

Examples

```
library(GO.db)
## List the possible values for columns
columns(GO.db)
## List the possible values for keytypes
keytypes(GO.db)
## get some values back
keys <- head(keys(GO.db))
keys
select(GO.db, keys=keys, columns=c("TERM", "ONTOLOGY"),
keytype="GOID")

## More information about the dates and original sources for these data:
metadata(GO.db)
```

GOTerms-class	Class "GOTerms"
---------------	-----------------

Description

A class to represent Gene Ontology nodes

Objects from the Class

Objects can be created by calls of the form `GOTerms(GOId, term, ontology, definition, synonym, secondary)`. `GOId`, `term`, and `ontology` are required.

Slots

GOID: Object of class "character" A character string for the GO id of a primary node.

Term: Object of class "character" A character string that defines the role of gene product corresponding to the primary GO id.

Ontology: Object of class "character" Gene Ontology category. Can be MF - molecular function, CC - cellular component, or BP - biological process.

Definition: Object of class "character" Further definition of the ontology of the primary GO id.

Synonym: Object of class "character" other ontology terms that are considered to be synonymous to the primary term attached to the GO id (e.g. "type I programmed cell death" is a synonym of "apoptosis"). Synonymous here can mean that the synonym is an exact synonym of the primary term, is related to the primary term, is broader than the primary term, is more precise than the primary term, or name is related to the term, but is not exact, broader or narrower.

Secondary: Object of class "character" GO ids that are secondary to the primary GO id as results of merging GO terms so that One GO id becomes the primary GO id and the rest become the secondary.

Methods

GOID signature(object = "GOTerms"): The get method for slot GOID.

Term signature(object = "GOTerms"): The get method for slot Term.

Ontology signature(object = "GOTerms"): The get method for slot Ontology.

Definition signature(object = "GOTerms"): The get method for slot Definition.

Synonym signature(object = "GOTerms"): The get method for slot Synonym.

Secondary signature(object = "GOTerms"): The get method for slot Secondary.

show signature(x = "GOTerms"): The method for pretty print.

Note

GOTerms objects are used to represent primary GO nodes in the SQLite-based annotation data package `GO.db`

References

<http://www.geneontology.org/>

See Also

[makeGOGraph](#) shows how to make GO mappings into graphNEL objects.

Examples

```
gonode <- new("GOTerms", GOID="GO:1234567", Term="Test", Ontology="MF",
             Definition="just for testing")

GOID(gonode)
Term(gonode)
Ontology(gonode)

##Or you can just use these methods on a GOTermsAnnDbBimap
## Not run: ##I want to show an ex., but dont want to require GO.db
require(GO.db)
FirstTenGOBimap <- GOTERM[1:10] ##grab the 1st ten
Term(FirstTenGOBimap)

##Or you can just use GO IDs directly
ids = keys(FirstTenGOBimap)
Term(ids)

## End(Not run)
```

HOMO_SAPIENS	<i>Descriptions of available values for columns and keytypes for in- paranoid packages.</i>
--------------	---

Description

When the user calls `columns` or `keytypes` for an `inparanoid` package, the `columns` and `keytypes` methods will give the full genus and species names of all the organisms that are available.

Details

All the possible values for `columns` and `keytypes` are listed below.

ACYRTHOSIPHON_PISUM: the pea aphid

AEDES_AEGYPTI: a mosquito that can spread the dengue fever, Chikungunya and yellow fever viruses, and other diseases

ANOPHELES_GAMBIAE: a mosquito notorious as a vector for malaria

APIS_MELLIFERA: the western honey bee

ARABIDOPSIS_THALIANA: the thale cress

ASPERGILLUS_FUMIGATUS: a fungus that causes disease in immunodeficient individuals

- BATRACHOCHYTRIUM_DENDROBATIDIS:** a chytrid fungus that causes the disease chytridiomycosis
- BOMBYX_MORI:** the silk worm
- BOS_TAURUS:** domestic cattle
- BRANCHIOSTOMA_FLORIDAE:** a lancelet (amphioxus)
- BRUGIA_MALAYI:** a nematode (roundworm), one of the three causative agents of lymphatic filariasis
- CAENORHABDITIS_BRENNERI:** a small nematode, closely related to the model organism *Caenorhabditis elegans*
- CAENORHABDITIS_BRIGGSAE:** a small nematode, closely related to *Caenorhabditis elegans*
- CAENORHABDITIS_ELEGANS:** a small nematode
- CAENORHABDITIS_JAPONICA:** a gonochoristic (male-female) species related to *C. elegans*
- CAENORHABDITIS_REMANEI:** a species of nematode (gonochoristic)
- CANDIDA_ALBICANS:** a diploid fungus that grows both as yeast and filamentous cells and a causal agent of opportunistic oral and genital infections in humans
- CANDIDA_GLABRATA:** a haploid yeast of the genus *Candida*
- CANIS_FAMILIARIS:** domestic dog
- CAPITELLA_SPI:** a polychaete worm
- CAVIA_PORCELLUS:** Guinea pig
- CHLAMYDOMONAS_REINHARDTII:** a single celled green alga
- CIONA_INTESTINALIS:** a urochordata (sea squirt), a tunicate widely distributed in Northern European waters
- CIONA_SAVIGNYI:** a urochordata (sea squirt)
- COCCIDIOIDES_IMMIS:** a pathogenic fungus that resides in the soil
- COPRINOPSIS_CINEREUS:** a species of mushroom
- CRYPTOCOCCUS_NEOFORMANS:** an encapsulated yeast that can live in both plants and animals
- CRYPTOSPORIDIUM_HOMINIS:** an obligate parasite of humans that can colonize the gastrointestinal tract
- CRYPTOSPORIDIUM_PARVUM:** one of several protozoal species that cause cryptosporidiosis, a parasitic disease of the mammalian intestinal tract
- CULEX_PIPPIENS:** the common house mosquito
- CYANIDIOSCHYZON_MEROLAE:** an algae that is the main organism in red tide
- DANIO_RERIO:** the zebrafish
- DAPHNIA_PULEX:** the most common species of water flea
- DEBARYOMYCES_HANSENII:** a yeast that tolerates high concentrations of salt and is related to yeasts that cause disease, including *Candida albicans*
- DICTYOSTELIUM_DISCOIDEUM:** a species of soil-living amoeba, AKA a slime mold
- DROSOPHILA_ANANASSAE:** a fruit fly

DROSOPHILA_GRIMSHAWI: a fruit fly
DROSOPHILA_MELANOGASTER: a fruit fly
DROSOPHILA_MOJAVENSIS: a fruit fly
DROSOPHILA_PSEUDOOBSCURA: a fruit fly
DROSOPHILA_VIRILIS: a fruit fly
DROSOPHILA_WILLISTONI: a fruit fly
ENTAMOEBIA_HISTOLYTICA: an anaerobic parasitic protozoan
EQUUS_CABALLUS: domestic horse
ESCHERICHIA_COLIK12: a laboratory strain of coliform bacteria
FUSARIUM_GRAMINEARUM: a fungus that attacks cereal grains
GALLUS_GALLUS: domesticated chicken
GASTEROSTEUS_ACULEATUS: three spined stickleback fish
GIARDIA_LAMBLIA: a flagellated protozoan parasite
HELOBDELLA_ROBUSTA: a leech
IXODES_SCAPULARIS: the black legged deer tick, a vector for lyme disease
KLUYVEROMYCES_LACTIS: yeast commonly used for genetic studies
LEISHMANIA_MAJOR: a species of Leishmania, associated with zoonotic cutaneous leishmaniasis
LOTTIA_GIGANTEA: a species of sea snail, a true limpet, a marine gastropod mollusc
MACACA_MULATTA: the rhesus Macaque
MAGNAPORTHE_GRISEA: rice blast fungus
MONODELPHIS_DOMESTICA: grey short tailed opossum
MONOSIGA_BREVICOLLIS: a marine choanoflagellate
MUS_MUSCULUS: lab mouse
NASONIA_VITRIPENNIS: a small pteromalid parasitoid wasp
NEMATOSTELLA_VECTENSIS: the starlet sea anemone
NEUROSPORA_CRASSA: a type of red bread mould
ORNITHORHYNCHUS_ANATINUS: the platypus
ORYZA_SATIVA: rice
ORYZIAS_LATIPES: medaka fish
OSTREOCOCCUS_TAURI: a unicellular coccoid or spherically shaped green alga
PAN_TROGLODYTES: chimp
PEDICULUS_HUMANUS: a species of lice that infects humans
PHYSCOMITRELLA_PATENS: a moss (Bryophyta) used as a model organism for studies on plant evolution
PHYTOPHTHORA_RAMORUM: the oomycete plant pathogen (sudden oak death)
PHYTOPHTHORA_SOJAE: an oomycete and a soil-borne plant pathogen that causes stem and root rot of soybean

- PLASMODIUM_FALCIPARUM:** a protozoan parasite that causes malaria
- PLASMODIUM_VIVAX:** a protozoal parasite and a human pathogen that causes a more benign malaria
- PONGO_PYGMAEUS:** the Bornean orangutan
- POPULUS_TRICHOCARPA:** black cottonwood; also known as western balsam poplar or California poplar
- PRISTIONCHUS_PACIFICUS:** a diplogastrid nematode
- PUCCINIA_GRAMINIS:** stem, black or cereal rusts
- RATTUS_NORVEGICUS:** common lab rat
- RHIZOPUS_ORYZAE:** a fungus that lives worldwide in dead organic matter. An opportunistic human pathogen
- SACCHAROMYCES_CEREVISIAE:** brewers yeast
- SCHISTOSOMA_MANSONI:** a significant parasite of humans, a trematode that is one of the major agents of the disease schistosomiasis
- SCHIZOSACCHAROMYCES_POMBE:** fission yeast
- SCLEROTINIA_SCLEROTIORUM:** an omnivorous fungal plant pathogen
- SORGHUM_BICOLOR:** sorghum
- STAGONOSPORA_NODORUM:** a fungal leaf spot disease
- STRONGYLOCENTROTUS_PURPURATUS:** the purple sea urchin
- TAKIFUGU_RUBRIPES:** Japanese pufferfish
- TETRAHYMENA_THERMOPHILA:** a single celled ciliate
- TETRAODON_NIGROVIRIDIS:** green spotted pufferfish (fresh water)
- THALASSIOSIRA_PSEUDONANA:** a species of marine centric diatom
- THEILERIA_ANNULATA:** a tickborne protozoan pathogen which is a major cause of livestock disease in sub-tropical regions
- THEILERIA_PARVA:** a parasitic protozoan, that causes East Coast fever (theileriosis) in cattle
- TRIBOLIUM_CASTANEUM:** the red flour beetle
- TRICHOMONAS_VAGINALIS:** an anaerobic, flagellated protozoan
- TRICHOPLAX_ADHAERENS:** Trichoplax adhaerens represents the simplest known animal, with the smallest known animal genome
- TRYPANOSOMA_CRUZI:** a species of parasitic euglenoid trypanosomes. This species causes the trypanosomiasis diseases in humans and animals in America.
- USTILAGO_MAYDIS:** a pathogenic plant fungus that causes smut disease on maize
- XENOPUS_TROPICALIS:** Western clawed frog
- YARROWIA_LIPOLYTICA:** Yarrowia lipolytica is a "non-conventional" species of yeast, often used in genetic research because it differs from other well-studied species

To get the latest information about the date stamps and source URLs for the data used to make an annotation package, please use the metadata method as shown in the example below.

Author(s)

Marc Carlson

Examples

```
library(hom.Hs.inp.db)
## List the possible values for columns
columns(hom.Hs.inp.db)
## List the possible values for keytypes
keytypes(hom.Hs.inp.db)
## get some values back
keys <- head(keys(hom.Hs.inp.db, keytype="HOMO_SAPIENS"))
keys
select(hom.Hs.inp.db, keys=keys, columns=c("BOS_TAURUS", "EQUUS_CABALLUS"),
keytype="HOMO_SAPIENS")

## More information about the dates and original sources for these data:
metadata(hom.Hs.inp.db)
```

inpIDMapper*Convenience functions for mapping IDs through an appropriate set of annotation packages*

Description

These are a set of convenience functions that attempt to take a list of IDs along with some additional information about what those IDs are, what type of ID you would like them to be, as well as some information about what species they are from and what species you would like them to be from and then attempts to the simplest possible conversion using the organism and possible inparanoid annotation packages. By default, this function will drop ambiguous matches from the results. Please see the details section for more information about the parameters that can affect this. If a more complex treatment of how to handle multiple matches is required, then it is likely that a less convenient approach will be necessary.

Usage

```
inpIDMapper(ids, srcSpecies, destSpecies, srcIDType="UNIPROT",
destIDType="EG", keepMultGeneMatches=FALSE, keepMultProtMatches=FALSE,
keepMultDestIDMatches = TRUE)
```

```
intraIDMapper(ids, species, srcIDType="UNIPROT", destIDType="EG",
keepMultGeneMatches=FALSE)
```

```
idConverter(ids, srcSpecies, destSpecies, srcIDType="UNIPROT",
destIDType="EG", keepMultGeneMatches=FALSE, keepMultProtMatches=FALSE,
keepMultDestIDMatches = TRUE)
```

Arguments

ids	a list or vector of original IDs to match
srcSpecies	The original source species in in paranoid format. In other words, the 3 letters of the genus followed by 2 letters of the species in all caps. Ie. 'HOMSA' is for Homo sapiens etc.
destSpecies	the destination species in inparanoid format
species	the species involved
srcIDType	The source ID type written exactly as it would be used in a mapping name for an eg package. So for example, 'UNIPROT' is how the uniprot mappings are always written, so we keep that convention here.
destIDType	the destination ID, written the same way as you would write the srcIDType. By default this is set to "EG" for entrez gene IDs
keepMultGeneMatches	Do you want to try and keep the 1st ID in those ambiguous cases where more than one protein is suggested? (You probably want to filter them out - hence the default is FALSE)
keepMultProtMatches	Do you want to try and keep the 1st ID in those ambiguous cases where more than one protein is suggested? (default = FALSE)
keepMultDestIDMatches	If you have mapped to a destination ID OTHER than an entrez gene ID, then it is possible that there may be multiple answers. Do you want to keep all of these or only return the 1st one? (default = TRUE)

Details

inpIDMapper - This is a convenience function for getting an ID from one species mapped to an ID type of your choice from another organism of your choice. The only mappings used to do this are the mappings that are scored as 100 according to the inparanoid algorithm. This function automatically tries to join IDs by using FIVE different mappings in the sequence that follows:

1) initial IDs -> src organism Entrez Gene IDs 2) src organism Entrez Gene IDs -> sre organism Inparanoid ID 3) src organism Inparanoid ID -> dest organism Inparanoid ID 4) dest organism Inparanoid ID -> dest organism Entrez Gene ID 5) dest organism Entrez Gene ID -> final destination organism ID

You can simplify this mapping as a series of steps like this:

srcIDs —> srcEGs —> srcInp —> destInp —> destEGs —> destIDs (1) (2) (3) (4) (5)

There are two steps in this process where multiple mappings can really interfere with getting a clear answer. It's no coincidence that these are also adjacent to the two places where we have to tie the identity to a single gene for each organism. When this happens, any ambiguity is confounding. Preceding step \#2, it is critical that we only have ONE entrez gene ID per initial ID, and the parameter keepMultGeneMatches can be used to toggle whether to drop any ambiguous matches (the default) or to keep the 1st one in the hope of getting an additional hit. A similar thing is done preceding step \#4, where we have to be sure that the protein IDs we are getting back have all mapped to only one gene. We allow you to use the keepMultProtMatches parameter to make the same kind of decision as in step \#2, again, the default is to drop anything that is ambiguous.

intraIDMapper - This is a convenience function to map within an organism and so it has a much simpler job to do. It will either map through one mapping or two depending whether the source ID or destination ID is a central ID for the relevant organism package. If the answer is neither, then two mappings will be needed.

idConverter - This is mostly for convenient usage of these functions by developers. It is just a wrapper function that can pass along all the parameters to the appropriate function (intraIDMapper or inpIDMapper). It decides which function to call based on the source and destination organism. The disadvantage to using this function all the time is just that more of the parameters have to be filled out each time.

Value

a list where the names of each element are the elements of the original list you passed in, and the values are the matching results. Elements that do not have a match are not returned. If you want things to align you can do some bookkeeping.

Author(s)

Marc Carlson

Examples

```
## Not run:
## This has to be in a dontrun block because otherwise I would have to
## expand the DEPENDS field for AnnotationDbi
## library("org.Hs.eg.db")
## library("org.Mm.eg.db")
## library("org.Sc.eg.db")
## library("hom.Hs.inp.db")
## library("hom.Mm.inp.db")
## library("hom.Sc.inp.db")

##Some IDs just for the example
library("org.Hs.eg.db")
ids = as.list(org.Hs.egUNIPROT)[10000:10500] ##get some ragged IDs
## Get entrez gene IDs (default) for uniprot IDs mapping from human to mouse.
MouseEGs = inpIDMapper(ids, "HOMSA", "MUSMU")
##Get yeast uniprot IDs in exchange for uniprot IDs from human
YeastUPS = inpIDMapper(ids, "HOMSA", "SACCE", destIDType="UNIPROT")
##Get yeast uniprot IDs but only return one ID per initial ID
YeastUPsingles = inpIDMapper(ids, "HOMSA", "SACCE", destIDType="UNIPROT", keepMultDestIDMatches = FALSE)

##Test out the intraIDMapper function:
HumanEGs = intraIDMapper(ids, species="HOMSA", srcIDType="UNIPROT",
destIDType="EG")
HumanPATHs = intraIDMapper(ids, species="HOMSA", srcIDType="UNIPROT",
destIDType="PATH")

##Test out the wrapper function
MousePATHs = idConverter(MouseEGs, srcSpecies="MUSMU", destSpecies="MUSMU",
srcIDType="EG", destIDType="PATH")
```



```
##Convert from Yeast uniprot IDs to Human entrez gene IDs.
HumanEGs = idConverter(YeastUPSingles, "SACCE", "HOMSA")
```

```
## End(Not run)
```

KEGGFrame

KEGGFrame objects

Description

These objects each contain a data frame which is required to be composed of 2 columns. The 1st column are KEGG IDs. The second are the gene IDs that match to the KEGG IDs. There is also a slot for the organism that these annotations pertain to. `getKEGGFrameData` is just an accessor method and returns the data.frame contained in the KEGGFrame object and is mostly used by other code internally.

Details

The purpose of these objects is to create a safe way for annotation data about KEGG from non-traditional sources to be used for analysis packages like GSEABase and eventually Category.

Examples

```
## Make up an example
genes = c(2,9,9,10)
KEGGIDs = c("04610", "00232", "00983", "00232")
frameData = data.frame(cbind(KEGGIDs,genes))

library(AnnotationDbi)
frame=KEGGFrame(frameData,organism="Homo sapiens")

getKEGGFrameData(frame)
```

makeGOGraph

A convenience function to generate graphs based on the GO.db package

Description

`makeGOGraph` is a function to quickly convert any of the three Gene Ontologies in GO.db into a graphNEL object where each edge is given a weight of 1.

Usage

```
makeGOGraph(ont = c("bp", "mf", "cc"))
```

Arguments

ont Specifies the ontology: "cc", "bp" or "mf".

Author(s)

Marc Carlson

See Also

[GOTerms](#)

Examples

```
## makes a GO graph from the CC ontology
f <- makeGOGraph("cc")
```

make_eg_to_go_map *Create GO to Entrez Gene maps for chip-based packages*

Description

Create a new map object mapping Entrez ID to GO (or vice versa) given a chip annotation data package.

This is a temporary solution until a more general pluggable map solution comes online.

Usage

```
make_eg_to_go_map(chip)
```

Arguments

chip The name of the annotation data package.

Value

Either a Go3AnnDbMap or a RevGo3AnnDbMap.

Author(s)

Seth Falcon and Herve Pages

Examples

```
library("hgu95av2.db")

eg2go = make_eg_to_go_map("hgu95av2.db")
sample(eg2go, 2)

go2eg = make_go_to_eg_map("hgu95av2.db")
sample(go2eg, 2)
```

print.probetable	<i>Print method for probetable objects</i>
------------------	--

Description

Prints `class(x)`, `nrow(x)` and `ncol(x)`, but not the elements of `x`. The motivation for having this method is that methods from the package base such as `print.data.frame` will try to print the values of all elements of `x`, which can take inconveniently much time and screen space if `x` is large.

Usage

```
## S3 method for class probetable
print(x, maxrows, ...)
```

Arguments

<code>x</code>	an object of S3-class probetable.
<code>maxrows</code>	maximum number of rows to print.
<code>...</code>	further arguments that get ignored.

See Also

[print.data.frame](#)

Examples

```
a = as.data.frame(matrix(runif(1e6), ncol=1e3))
class(a) = c("probetable", class(a))
print(a)
print(as.matrix(a[2:3, 4:6]))
```

 supportedSeqnameStyles

List the supported seqname styles for all supported organisms

Description

Lists out the available seqname styles for all organisms supported by the seqnames.db database.

Usage

```
supportedSeqnameMappings()
findSequenceRenamingMaps(seqnames, style, best.only=TRUE, drop=TRUE)
supportedSeqnameStyles()
isSupportedSeqnamesStyle(style, species)
extractSeqnameSet(style, species)
listAllSupportedSeqnameStyles()
listAllSupportedStylesBySpecies(species)
supportedSeqnames()
testSeqnames(styles, seqnames, species)
```

Arguments

best.only	if TRUE (the default), then only the "best" sequence renaming maps (i.e. the rows with less NAs) are returned.
drop	if TRUE (the default), then a vector is returned instead of a matrix when the matrix has only 1 row.
seqnames	the seqnames. These are given as a character vector and are the labels attached to the chromosomes in a genome.
style	a character vector with a single element to specify the style.
species	The genus and species of the organism in question separated by a single space. Don't forget to capitalize the genus.
styles	same as style, but expecting a character vector which could have multiple elements.

Details

supportedSeqnameMappings: Returns the list of all supported seqname mappings, one per supported organism. Each mapping is represented as a data frame with 1 column per seqname style and 1 row per chromosome name (not all chromosomes of a given organism necessarily belong to the mapping).

findSequenceRenamingMaps: Returns a matrix with 1 column per supplied sequence name and 1 row per sequence renaming map compatible with the specified style. If `best.only` is TRUE (the default), only the "best" renaming maps (i.e. the rows with less NAs) are returned.

supportedSeqnameStyles: Different organizations have different naming conventions for how they name the biologically defined sequence elements (usually chromosomes) for each organism

they support. The seqnames.db package contains a database that defines these different conventions. The supportedSeqnameStyles function allows users to discover which conventions are currently encoded by the seqnames DB.

`isSupportedSeqnamesStyle`: Returns TRUE or FALSE depending on whether or not a suspected style and species are legitimately defined in seqnames.db.

`extractSeqnameSet`: Extracts the seqnames for a single style and species.

`listAllSupportedSeqnameStyles`: Returns a list of character vectors where each character vector contains the seqnames for a particular style. This effectively dumps the whole seqnames.db DB into a single list object.

`listAllSupportedStylesBySpecies`: List out only the supported styles for a particular species.

`supportedSeqnames`: This just lists all possible seqnames for the database as a single unique character vector.

`testSeqnames`: Takes a character vector of styles, a set of seqnames and a species and determines for each style whether or not the seqnames given are a match. Returns a TRUE/FALSE vector of the same length as styles.

Value

A character list containing character vectors with the names of all seqname styles for each supported species. The names of the list are the species names for each supported organism.

Author(s)

Marc Carlson

Examples

```
supportedSeqnameMappings()
findSequenceRenamingMaps(c("chrII", "chrIII", "chrM"), "NCBI")
findSequenceRenamingMaps(c("chrII", "chrIII", "chrM"), "Ensembl")

library("TxDb.Hsapiens.UCSC.hg19.knownGene")
txdb = TxDb.Hsapiens.UCSC.hg19.knownGene
species = species(txdb)
style = "NCBI"

supportedSeqnameStyles()

isSupportedSeqnamesStyle(style, species)

extractSeqnameSet(style=style, species=species)

listAllSupportedSeqnameStyles()

supportedSeqnames()

styles = c("NCBI", "UCSC")
seqnames = as.character(c(1:5, "Pt", "Mt"))
```

```
testSeqnames(styles, seqnames, species)
```

toggleProbes

Methods for getting/setting the filters on a Bimap object

Description

These methods are part of the [Bimap](#) interface (see [?Bimap](#) for a quick overview of the [Bimap](#) objects and their interface).

Some of these methods are for getting or setting the filtering status on a [Bimap](#) object so that the mapping object can toggle between displaying all probes, only single probes (the default) or only multiply matching probes.

Other methods are for viewing or setting the filter threshold value on a [InpAnnDbBimap](#) object.

Usage

```
## Making a Bimap object that does not prefilter to remove probes that
## match multiple genes:
toggleProbes(x, value)
hasMultiProbes(x) ##T/F test for exposure of single probes
hasSingleProbes(x) ##T/F test for exposure of multiply matched probes

## Looking at the SQL filter values for a Bimap
getBimapFilters(x)
## Setting the filter on an InpAnnDbBimap object
setInpBimapFilter(x,value)
```

Arguments

x	A Bimap object.
value	A character vector containing the new value that the Bimap should use as the filter. Or the value to toggle a probe mapping to: "all", "single", or "multiple".

Details

`toggleProbes(x)` is a methods for creating [Bimaps](#) that have an alternate filter for which probes get exposed based upon whether these probes map to multiple genes or not.

`hasMultiProbes(x)` and `hasSingleProbes(x)` are provided to give a quick test about whether or not such probes are exposed in a given mapping.

`getBimapFilters(x)` will list all the SQL filters applied to a [Bimap](#) object.

`setInpBimapFilters(x)` will allow you to pass a value as a character string which will be used as a filter. In order to be useful with the [InpAnnDbBimap](#) objects provided in the [inparanoid](#) packages, this value needs to be a digit number written as a percentage. So for example "80 is owing to the nature of the [inparanoid](#) data set.

Value

A [Bimap](#) object of the same subtype as x for `exposeAllProbes(x)`, `maskMultiProbes(x)` and `maskSingleProbes(x)`.

A TRUE or FALSE value in the case of `hasMultiProbes(x)` and `hasSingleProbes(x)`.

Author(s)

M. Carlson

See Also

[Bimap](#), [Bimap-keys](#), [Bimap-direction](#), [BimapFormatting](#), [Bimap-envirAPI](#), [nhit](#)

Examples

```
## Make a Bimap that contains all the probes
require("hgu95av2.db")
mapWithMultiProbes <- toggleProbes(hgu95av2ENTREZID, "all")
count.mappedLkeys(hgu95av2ENTREZID)
count.mappedLkeys(mapWithMultiProbes)

## Check that it has both multiply and singly matching probes:
hasMultiProbes(mapWithMultiProbes)
hasSingleProbes(mapWithMultiProbes)

## Make it have Multi probes ONLY:
OnlyMultiProbes = toggleProbes(mapWithMultiProbes, "multiple")
hasMultiProbes(OnlyMultiProbes)
hasSingleProbes(OnlyMultiProbes)

## Convert back to a default map with only single probes exposed
OnlySingleProbes = toggleProbes(OnlyMultiProbes, "single")
hasMultiProbes(OnlySingleProbes)
hasSingleProbes(OnlySingleProbes)

## List the filters on the inparanoid mapping
# library(hom.Dm.inp.db)
# getBimapFilters(hom.Dm.inpANOGA)

## Here is how you can make a mapping with a
##different filter than the default:
# f80 = setInpBimapFilter(hom.Dm.inpANOGA, "80%")
# dim(hom.Dm.inpANOGA)
# dim(f80)
```

toSQLStringSet	<i>Convert a vector to a quoted string for use as a SQL value list</i>
----------------	--

Description

Given a vector, this function returns a string with each element of the input coerced to character, quoted, and separated by ",".

Usage

```
toSQLStringSet(names)
```

Arguments

names	A vector of values to quote
-------	-----------------------------

Details

If names is a character vector with elements containing single quotes, these quotes will be doubled so as to escape the quote in SQL.

Value

A character vector of length one that represents the input vector as a SQL value list. Each element is single quoted and elements are comma separated.

Note

Do not use sQuote for generating SQL as that function is intended for display purposes only. In some locales, sQuote will generate fancy quotes which will break your SQL.

Author(s)

Herve Pages

Examples

```
toSQLStringSet(letters[1:4])  
toSQLStringSet(c("foo", "abcd", "bar"))
```

unlist2 *A replacement for unlist() that does not mangle the names*

Description

unlist2 is a replacement for `base::unlist()` that does not mangle the names.

Usage

```
unlist2(x, recursive=TRUE, use.names=TRUE, what.names="inherited")
```

Arguments

`x`, `recursive`, `use.names`
 See ?unlist.
`what.names` "inherited" or "full".

Details

Use this function if you don't like the mangled names returned by the standard `unlist` function from the base package. Using `unlist` with annotation data is dangerous and it is highly recommended to use `unlist2` instead.

Author(s)

Herve Pages

See Also

[unlist](#)

Examples

```
x <- list(A=c(b=-4, 2, b=7), B=3:-1, c(a=1, a=-2), C=list(c(2:-1, d=55), e=99))
unlist(x)
unlist2(x)

library(hgu95av2.db)
egids <- c("10", "100", "1000")
egids2pbids <- mget(egids, revmap(hgu95av2ENTREZID))
egids2pbids

unlist(egids2pbids) # 1001, 1002, 10001 and 10002 are not real
                   # Entrez ids but are the result of unlist()
                   # mangling the names!

unlist2(egids2pbids) # much cleaner! yes the names are not unique
                    # but at least they are correct...
```

Index

*Topic **classes**

- AnnDbObj-objects, 4
- AnnotationDb-objects, 7
- Bimap, 10
- GOFrame, 23
- GOTerms-class, 25
- KEGGFrame, 33

*Topic **interface**

- Bimap, 10
- Bimap-envirAPI, 16
- GOFrame, 23
- KEGGFrame, 33

*Topic **manip**

- ACCNUM, 2
- GOID, 24
- HOMO_SAPIENS, 26
- inpIDMapper, 30
- makeGOGraph, 33
- supportedSeqnameStyles, 36
- toSQLStringSet, 40
- unlist2, 41

*Topic **methods**

- AnnDbObj-objects, 4
- AnnotationDb-objects, 7
- Bimap-direction, 13
- Bimap-envirAPI, 16
- Bimap-keys, 17
- Bimap-toTable, 19
- BimapFormatting, 22
- GOTerms-class, 25
- toggleProbes, 38

*Topic **print**

- print.probetable, 35

*Topic **utilities**

- ACCNUM, 2
- AnnDbPkg-checker, 6
- GOID, 24
- HOMO_SAPIENS, 26
- makeGOGraph, 33

- toSQLStringSet, 40

- unlist2, 41

- [,Bimap-method (Bimap-keys), 17

- [[,Bimap-method (Bimap-envirAPI), 16

- \$,Bimap-method (Bimap-envirAPI), 16

- ACCNUM, 2

- ACYRTHOSIPHON_PISUM (HOMO_SAPIENS), 26

- AEDES_AEGYPTI (HOMO_SAPIENS), 26

- AgiAnnDbMap (Bimap), 10

- AgiAnnDbMap-class (Bimap), 10

- ALIAS (ACCNUM), 2

- AnnDbBimap, 4, 14

- AnnDbBimap (Bimap), 10

- AnnDbBimap-class (Bimap), 10

- AnnDbMap (Bimap), 10

- AnnDbMap-class (Bimap), 10

- AnnDbObj (AnnDbObj-objects), 4

- AnnDbObj-class (AnnDbObj-objects), 4

- AnnDbObj-objects, 4

- AnnDbPkg-checker, 6

- AnnotationDb, 19

- AnnotationDb (AnnotationDb-objects), 7

- AnnotationDb-class

- (AnnotationDb-objects), 7

- AnnotationDb-objects, 7

- AnnotationDbi-defunct, 9

- AnnotationDbi-deprecated, 9

- ANOPHELES_GAMBIAE (HOMO_SAPIENS), 26

- APIS_MELLIFERA (HOMO_SAPIENS), 26

- ARABIDOPSIS_THALIANA (HOMO_SAPIENS), 26

- ARACYC (ACCNUM), 2

- ARACYCENZYME (ACCNUM), 2

- as.character, AnnDbBimap-method
(BimapFormatting), 22

- as.character, FlatBimap-method
(BimapFormatting), 22

- as.data.frame, Bimap-method
(Bimap-toTable), 19

- as.list (BimapFormatting), 22

- as.list,AgiAnnDbMap-method
(BimapFormatting), 22
- as.list,Bimap-method (BimapFormatting),
22
- as.list,FlatBimap-method
(BimapFormatting), 22
- as.list,GoAnnDbBimap-method
(BimapFormatting), 22
- as.list,GOTermsAnnDbBimap-method
(BimapFormatting), 22
- as.list,IpiAnnDbMap-method
(BimapFormatting), 22
- ASPERGILLUS_FUMIGATUS (HOMO_SAPIENS), 26
- BATRACHOCHYTRIUM_DENDROBATIDIS
(HOMO_SAPIENS), 26
- Bimap, 4, 5, 8, 10, 13–21, 23, 38, 39
- Bimap-class (Bimap), 10
- Bimap-direction, 12, 13, 13, 39
- Bimap-envirAPI, 13, 15, 16, 19, 21, 23, 39
- Bimap-keys, 12, 13, 15, 17, 39
- Bimap-toTable, 12, 13, 19, 19
- BimapFormatting, 13, 15, 17, 19, 21, 22, 39
- BOMBYX_MORI (HOMO_SAPIENS), 26
- BOS_TAURUS (HOMO_SAPIENS), 26
- BRANCHIOSTOMA_FLORIDAE (HOMO_SAPIENS),
26
- BRUGIA_MALAYI (HOMO_SAPIENS), 26
- CAENORHABDITIS_BRENNERI (HOMO_SAPIENS),
26
- CAENORHABDITIS_BRIGGSAE (HOMO_SAPIENS),
26
- CAENORHABDITIS_ELEGANS (HOMO_SAPIENS),
26
- CAENORHABDITIS_JAPONICA (HOMO_SAPIENS),
26
- CAENORHABDITIS_REMANEI (HOMO_SAPIENS),
26
- CANDIDA_ALBICANS (HOMO_SAPIENS), 26
- CANDIDA_GLABRATA (HOMO_SAPIENS), 26
- CANIS_FAMILIARIS (HOMO_SAPIENS), 26
- CAPITELLA_SPI (HOMO_SAPIENS), 26
- cat, 5
- CAVIA_PORCELLUS (HOMO_SAPIENS), 26
- checkMAPCOUNTS (AnnDbPkg-checker), 6
- ChipDb-class (AnnotationDb-objects), 7
- CHLAMYDOMONAS_REINHARDTII
(HOMO_SAPIENS), 26
- CHR (ACCNUM), 2
- CHRLOC (ACCNUM), 2
- CHRLOCEND (ACCNUM), 2
- CIONA_INTESTINALIS (HOMO_SAPIENS), 26
- CIONA_SAVIGNYI (HOMO_SAPIENS), 26
- class:AgiAnnDbMap (Bimap), 10
- class:AnnDbBimap (Bimap), 10
- class:AnnDbMap (Bimap), 10
- class:AnnDbObj (AnnDbObj-objects), 4
- class:AnnotationDb
(AnnotationDb-objects), 7
- class:Bimap (Bimap), 10
- class:Go3AnnDbBimap (Bimap), 10
- class:GOAllFrame (GOFrame), 23
- class:GoAnnDbBimap (Bimap), 10
- class:GOFrame (GOFrame), 23
- class:GOTerms (GOTerms-class), 25
- class:GOTermsAnnDbBimap (Bimap), 10
- class:IpiAnnDbMap (Bimap), 10
- class:KEGGFrame (KEGGFrame), 33
- class:ProbeAnnDbBimap (Bimap), 10
- class:ProbeAnnDbMap (Bimap), 10
- class:ProbeGo3AnnDbBimap (Bimap), 10
- class:ProbeIpiAnnDbMap (Bimap), 10
- COCCIDIOIDES_IMMITIS (HOMO_SAPIENS), 26
- colmetanames (Bimap-toTable), 19
- colmetanames, AnnDbBimap-method
(Bimap-toTable), 19
- colmetanames, FlatBimap-method
(Bimap-toTable), 19
- colnames (Bimap-toTable), 19
- colnames, AnnDbBimap-method
(Bimap-toTable), 19
- colnames, FlatBimap-method
(Bimap-toTable), 19
- cols (AnnotationDb-objects), 7
- columns, 19
- columns (AnnotationDb-objects), 7
- columns, AnnotationDb-method
(AnnotationDb-objects), 7
- columns, ChipDb-method
(AnnotationDb-objects), 7
- columns, GODb-method
(AnnotationDb-objects), 7
- columns, InparanoidDb-method
(AnnotationDb-objects), 7
- columns, OrgDb-method
(AnnotationDb-objects), 7

- columns, ReactomeDb-method
(AnnotationDb-objects), 7
- COMMON (ACCNUM), 2
- contents, 17
- contents, Bimap-method (Bimap-envirAPI),
16
- COPRINOPSIS_CINEREUS (HOMO_SAPIENS), 26
- count.links (Bimap-toTable), 19
- count.links, Bimap-method
(Bimap-toTable), 19
- count.links, Go3AnnDbBimap-method
(Bimap-toTable), 19
- count.mappedkeys (Bimap-keys), 17
- count.mappedkeys, ANY-method
(Bimap-keys), 17
- count.mappedkeys, Bimap-method
(Bimap-keys), 17
- count.mappedLkeys (Bimap-direction), 13
- count.mappedLkeys, AgiAnnDbMap-method
(Bimap-direction), 13
- count.mappedLkeys, AnnDbBimap-method
(Bimap-direction), 13
- count.mappedLkeys, Bimap-method
(Bimap-direction), 13
- count.mappedLkeys, Go3AnnDbBimap-method
(Bimap-direction), 13
- count.mappedRkeys (Bimap-direction), 13
- count.mappedRkeys, AnnDbBimap-method
(Bimap-direction), 13
- count.mappedRkeys, AnnDbMap-method
(Bimap-direction), 13
- count.mappedRkeys, Bimap-method
(Bimap-direction), 13
- count.mappedRkeys, Go3AnnDbBimap-method
(Bimap-direction), 13
- CRYPTOCOCCUS_NEOFORMANS (HOMO_SAPIENS),
26
- CRYPTOSPORIDIUM_HOMINIS (HOMO_SAPIENS),
26
- CRYPTOSPORIDIUM_PARVUM (HOMO_SAPIENS),
26
- CULEX_PAPIENS (HOMO_SAPIENS), 26
- CYANIDIOSCHYZON_MEROLAE (HOMO_SAPIENS),
26

- DANIO_RERIO (HOMO_SAPIENS), 26
- DAPHNIA_PULEX (HOMO_SAPIENS), 26
- dbconn (AnnDbObj-objects), 4
- dbconn, AnnDbObj-method
(AnnDbObj-objects), 4
- dbConn, AnnotationDb-method
(AnnotationDb-objects), 7
- dbconn, environment-method
(AnnDbObj-objects), 4
- dbConnect, 5, 8
- dbfile (AnnDbObj-objects), 4
- dbfile, AnnDbObj-method
(AnnDbObj-objects), 4
- dbfile, environment-method
(AnnDbObj-objects), 4
- dbGetQuery, 5, 8
- dbInfo (AnnDbObj-objects), 4
- dbInfo, AnnDbObj-method
(AnnDbObj-objects), 4
- dbInfo, DBIConnection-method
(AnnDbObj-objects), 4
- dbInfo, environment-method
(AnnDbObj-objects), 4
- dbListFields, 5, 8
- dbListTables, 5, 8
- dbmeta (AnnDbObj-objects), 4
- dbmeta, AnnDbObj-method
(AnnDbObj-objects), 4
- dbmeta, DBIConnection-method
(AnnDbObj-objects), 4
- dbmeta, environment-method
(AnnDbObj-objects), 4
- dbschema (AnnDbObj-objects), 4
- dbschema, AnnDbObj-method
(AnnDbObj-objects), 4
- dbschema, DBIConnection-method
(AnnDbObj-objects), 4
- dbschema, environment-method
(AnnDbObj-objects), 4
- DEBARYOMYCES_HANSENII (HOMO_SAPIENS), 26
- DEFINITION (GOID), 24
- Definition (GOTerms-class), 25
- Definition, character-method
(GOTerms-class), 25
- Definition, GOTerms-method
(GOTerms-class), 25
- Definition, GOTermsAnnDbBimap-method
(GOTerms-class), 25
- Defunct, 9
- Deprecated, 9
- DESCRIPTION (ACCNUM), 2

- DICTYOSTELIUM_DISCOIDEUM
 (HOMO_SAPIENS), 26
 dim, Bimap-method (Bimap-toTable), 19
 direction, 18
 direction (Bimap-direction), 13
 direction, AnnDbBimap-method
 (Bimap-direction), 13
 direction, FlatBimap-method
 (Bimap-direction), 13
 direction<- (Bimap-direction), 13
 direction<-, AnnDbBimap-method
 (Bimap-direction), 13
 direction<-, AnnDbMap-method
 (Bimap-direction), 13
 direction<-, FlatBimap-method
 (Bimap-direction), 13
 DROSOPHILA_ANANASSAE (HOMO_SAPIENS), 26
 DROSOPHILA_GRIMSHAWI (HOMO_SAPIENS), 26
 DROSOPHILA_MELANOGASTER (HOMO_SAPIENS),
 26
 DROSOPHILA_MOJAVENSIS (HOMO_SAPIENS), 26
 DROSOPHILA_PSEUDOOBSCURA
 (HOMO_SAPIENS), 26
 DROSOPHILA_VIRILIS (HOMO_SAPIENS), 26
 DROSOPHILA_WILLISTONI (HOMO_SAPIENS), 26

 eapply, 17
 eapply (Bimap-envirAPI), 16
 eapply, Bimap-method (Bimap-envirAPI), 16
 ENSEMBL (ACCNUM), 2
 ENSEMBLPROT (ACCNUM), 2
 ENSEMBLTRANS (ACCNUM), 2
 ENTAMOEBA_HISTOLYTICA (HOMO_SAPIENS), 26
 ENTREZID (ACCNUM), 2
 ENZYME (ACCNUM), 2
 EQUUS_CABALLUS (HOMO_SAPIENS), 26
 ESCHERICHIA_COLIK12 (HOMO_SAPIENS), 26
 EVIDENCE (ACCNUM), 2
 EVIDENCEALL (ACCNUM), 2
 exists, 17
 exists (Bimap-envirAPI), 16
 exists, ANY, ANY, Bimap-method
 (Bimap-envirAPI), 16
 exists, ANY, Bimap, missing-method
 (Bimap-envirAPI), 16
 extractSeqnameSet
 (supportedSeqnameStyles), 36

 findSequenceRenamingMaps
 (supportedSeqnameStyles), 36
 FUSARIUM_GRAMINEARUM (HOMO_SAPIENS), 26

 GALLUS_GALLUS (HOMO_SAPIENS), 26
 GASTEROSTEUS_ACULEATUS (HOMO_SAPIENS),
 26
 GENENAME (ACCNUM), 2
 get, 17
 get (Bimap-envirAPI), 16
 get, ANY, ANY, Bimap-method
 (Bimap-envirAPI), 16
 get, ANY, Bimap, missing-method
 (Bimap-envirAPI), 16
 getBimapFilters (toggleProbes), 38
 getBimapFilters, AnnDbBimap-method
 (toggleProbes), 38
 getGOFrameData (GOFrame), 23
 getGOFrameData, GOAllFrame-method
 (GOFrame), 23
 getGOFrameData, GOFrame-method
 (GOFrame), 23
 getKEGGFrameData (KEGGFrame), 33
 getKEGGFrameData, KEGGAllFrame-method
 (KEGGFrame), 33
 getKEGGFrameData, KEGGFrame-method
 (KEGGFrame), 33
 GIARDIA_LAMBLIA (HOMO_SAPIENS), 26
 GO (ACCNUM), 2
 Go3AnnDbBimap (Bimap), 10
 Go3AnnDbBimap-class (Bimap), 10
 GOALL (ACCNUM), 2
 GOAllFrame (GOFrame), 23
 GOAllFrame, GOFrame-method (GOFrame), 23
 GOAllFrame-class (GOFrame), 23
 GoAnnDbBimap (Bimap), 10
 GoAnnDbBimap-class (Bimap), 10
 GODb-class (AnnotationDb-objects), 7
 GOFrame, 23
 GOFrame, data.frame, character-method
 (GOFrame), 23
 GOFrame, data.frame, missing-method
 (GOFrame), 23
 GOFrame-class (GOFrame), 23
 GOID, 24
 GOID, character-method (GOTerms-class),
 25
 GOID, GOTerms-method (GOTerms-class), 25
 GOID, GOTermsAnnDbBimap-method
 (GOTerms-class), 25

- GOTerms, 34
- GOTerms (GOTerms-class), 25
- GOTerms-class, 25
- GOTermsAnnDbBimap (Bimap), 10
- GOTermsAnnDbBimap-class (Bimap), 10
- hasMultiProbes (toggleProbes), 38
- hasMultiProbes, ProbeAnnDbBimap-method (toggleProbes), 38
- hasMultiProbes, ProbeAnnDbMap-method (toggleProbes), 38
- hasMultiProbes, ProbeGo3AnnDbBimap-method (toggleProbes), 38
- hasMultiProbes, ProbeIpiAnnDbMap-method (toggleProbes), 38
- hasSingleProbes (toggleProbes), 38
- hasSingleProbes, ProbeAnnDbBimap-method (toggleProbes), 38
- hasSingleProbes, ProbeAnnDbMap-method (toggleProbes), 38
- hasSingleProbes, ProbeGo3AnnDbBimap-method (toggleProbes), 38
- hasSingleProbes, ProbeIpiAnnDbMap-method (toggleProbes), 38
- head, 20
- head (Bimap-toTable), 19
- head, FlatBimap-method (Bimap-toTable), 19
- HELOBDELLA_ROBUSTA (HOMO_SAPIENS), 26
- HOMO_SAPIENS, 26
- idConverter (inpIDMapper), 30
- initialize, GOTerms-method (GOTerms-class), 25
- InparanoidDb-class (AnnotationDb-objects), 7
- inpIDMapper, 30
- INTERPRO (ACCNUM), 2
- intraIDMapper (inpIDMapper), 30
- IPI (ACCNUM), 2
- IpiAnnDbMap (Bimap), 10
- IpiAnnDbMap-class (Bimap), 10
- isNA (Bimap-keys), 17
- isNA, ANY-method (Bimap-keys), 17
- isNA, Bimap-method (Bimap-keys), 17
- isNA, environment-method (Bimap-keys), 17
- isSupportedSeqnamesStyle (supportedSeqnameStyles), 36
- IXODES_SCAPULARIS (HOMO_SAPIENS), 26
- KEGGFrame, 33
- KEGGFrame, data.frame, character-method (KEGGFrame), 33
- KEGGFrame, data.frame, missing-method (KEGGFrame), 33
- KEGGFrame-class (KEGGFrame), 33
- keyname (Bimap-toTable), 19
- keyname, Bimap-method (Bimap-toTable), 19
- keys, 14
- keys (AnnotationDb-objects), 7
- keys, Bimap-method (Bimap-keys), 17
- keys, ChipDb-method (AnnotationDb-objects), 7
- keys, GODb-method (AnnotationDb-objects), 7
- keys, InparanoidDb-method (AnnotationDb-objects), 7
- keys, OrgDb-method (AnnotationDb-objects), 7
- keys, ReactomeDb-method (AnnotationDb-objects), 7
- keys<- (Bimap-keys), 17
- keys<-, Bimap-method (Bimap-keys), 17
- keytypes (AnnotationDb-objects), 7
- keytypes, ChipDb-method (AnnotationDb-objects), 7
- keytypes, GODb-method (AnnotationDb-objects), 7
- keytypes, InparanoidDb-method (AnnotationDb-objects), 7
- keytypes, OrgDb-method (AnnotationDb-objects), 7
- keytypes, ReactomeDb-method (AnnotationDb-objects), 7
- KLUYVEROMYCES_LACTIS (HOMO_SAPIENS), 26
- LEISHMANIA_MAJOR (HOMO_SAPIENS), 26
- length, Bimap-method (Bimap-keys), 17
- links (Bimap-toTable), 19
- links, AnnDbBimap-method (Bimap-toTable), 19
- links, Bimap-method (Bimap-toTable), 19
- links, FlatBimap-method (Bimap-toTable), 19
- links, Go3AnnDbBimap-method (Bimap-toTable), 19
- listAllSupportedSeqnameStyles (supportedSeqnameStyles), 36

- listAllSupportedStylesBySpecies
(supportedSeqnameStyles), 36
- Lkeyname (Bimap-toTable), 19
- Lkeyname, AnnDbBimap-method
(Bimap-toTable), 19
- Lkeyname, Bimap-method (Bimap-toTable),
19
- Lkeys (Bimap-direction), 13
- Lkeys, AnnDbBimap-method
(Bimap-direction), 13
- Lkeys, FlatBimap-method
(Bimap-direction), 13
- Lkeys, ProbeAnnDbBimap-method
(Bimap-direction), 13
- Lkeys, ProbeAnnDbMap-method
(Bimap-direction), 13
- Lkeys, ProbeGo3AnnDbBimap-method
(Bimap-direction), 13
- Lkeys, ProbeIpiAnnDbMap-method
(Bimap-direction), 13
- Lkeys<- (Bimap-direction), 13
- Lkeys<-, AnnDbBimap-method
(Bimap-direction), 13
- Lkeys<-, FlatBimap-method
(Bimap-direction), 13
- Llength (Bimap-direction), 13
- Llength, AnnDbBimap-method
(Bimap-direction), 13
- Llength, Bimap-method (Bimap-direction),
13
- Llength, ProbeAnnDbBimap-method
(Bimap-direction), 13
- Llength, ProbeAnnDbMap-method
(Bimap-direction), 13
- Llength, ProbeGo3AnnDbBimap-method
(Bimap-direction), 13
- Llength, ProbeIpiAnnDbMap-method
(Bimap-direction), 13
- loadDb (AnnotationDb-objects), 7
- loadDb, character, character, character-method
(AnnotationDb-objects), 7
- loadDb, character, missing, missing-method
(AnnotationDb-objects), 7
- LOTTIA_GIGANTEA (HOMO_SAPIENS), 26
- ls, 17
- ls (Bimap-envirAPI), 16
- ls, Bimap-method (Bimap-envirAPI), 16
- MACACA_MULATTA (HOMO_SAPIENS), 26
- MAGNAPORTHE_GRISEA (HOMO_SAPIENS), 26
- make_eg_to_go_map, 34
- make_go_to_eg_map (make_eg_to_go_map),
34
- makeARABIDOPSISCHIP_DB
(AnnotationDbi-defunct), 9
- makeBOVINECHIP_DB
(AnnotationDbi-defunct), 9
- makeCANINECHIP_DB
(AnnotationDbi-defunct), 9
- makeCHICKENCHIP_DB
(AnnotationDbi-defunct), 9
- makeECOLICHIP_DB
(AnnotationDbi-defunct), 9
- makeFLYCHIP_DB (AnnotationDbi-defunct),
9
- makeGOGraph, 26, 33
- makeHUMANCHIP_DB
(AnnotationDbi-defunct), 9
- makeMOUSECHIP_DB
(AnnotationDbi-defunct), 9
- makePIGCHIP_DB (AnnotationDbi-defunct),
9
- makeRATCHIP_DB (AnnotationDbi-defunct),
9
- makeRHESUSCHIP_DB
(AnnotationDbi-deprecated), 9
- makeWORMCHIP_DB
(AnnotationDbi-defunct), 9
- makeYEASTCHIP_DB
(AnnotationDbi-defunct), 9
- makeZEBRAFISHCHIP_DB
(AnnotationDbi-defunct), 9
- MAP (ACCNUM), 2
- mappedkeys (Bimap-keys), 17
- mappedkeys, Bimap-method (Bimap-keys), 17
- mappedkeys, environment-method
(Bimap-keys), 17
- mappedkeys, vector-method (Bimap-keys),
17
- mappedLkeys (Bimap-direction), 13
- mappedLkeys, AgiAnnDbMap-method
(Bimap-direction), 13
- mappedLkeys, AnnDbBimap-method
(Bimap-direction), 13
- mappedLkeys, FlatBimap-method
(Bimap-direction), 13
- mappedLkeys, Go3AnnDbBimap-method

- (Bimap-direction), 13
- mappedRkeys (Bimap-direction), 13
- mappedRkeys, AnnDbBimap-method (Bimap-direction), 13
- mappedRkeys, AnnDbMap-method (Bimap-direction), 13
- mappedRkeys, FlatBimap-method (Bimap-direction), 13
- mappedRkeys, Go3AnnDbBimap-method (Bimap-direction), 13
- metadata, AnnotationDb-method (AnnotationDb-objects), 7
- mget, 17
- mget (Bimap-envirAPI), 16
- mget, ANY, Bimap-method (Bimap-envirAPI), 16
- mget, Bimap-method (Bimap-envirAPI), 16
- MONODELPHIS_DOMESTICA (HOMO_SAPIENS), 26
- MONOSIGA_BREVICOLLIS (HOMO_SAPIENS), 26
- MUS_MUSCULUS (HOMO_SAPIENS), 26
- names, AnnotationDb-method (AnnotationDb-objects), 7
- NASONIA_VITRIPENNIS (HOMO_SAPIENS), 26
- ncol (Bimap-toTable), 19
- ncol, Bimap-method (Bimap-toTable), 19
- NEMATOSTELLA_VECTENSIS (HOMO_SAPIENS), 26
- NEUROSPORA_CRASSA (HOMO_SAPIENS), 26
- nhit, 15, 39
- nhit (Bimap-toTable), 19
- nhit, Bimap-method (Bimap-toTable), 19
- nhit, environment-method (Bimap-toTable), 19
- nhit, list-method (Bimap-toTable), 19
- nrow (Bimap-toTable), 19
- nrow, AnnDbBimap-method (Bimap-toTable), 19
- nrow, AnnDbTable-method (Bimap-toTable), 19
- nrow, Bimap-method (Bimap-toTable), 19
- nrow, FlatBimap-method (Bimap-toTable), 19
- nrow, Go3AnnDbBimap-method (Bimap-toTable), 19
- OMIM (ACCNUM), 2
- ONTOLOGY (GOID), 24
- Ontology (GOTerms-class), 25
- Ontology, character-method (GOTerms-class), 25
- Ontology, GOTerms-method (GOTerms-class), 25
- Ontology, GOTermsAnnDbBimap-method (GOTerms-class), 25
- ONTOLOGYALL (ACCNUM), 2
- ORF (ACCNUM), 2
- OrgDb-class (AnnotationDb-objects), 7
- ORNITHORHYNCHUS_ANATINUS (HOMO_SAPIENS), 26
- ORYZA_SATIVA (HOMO_SAPIENS), 26
- ORYZIAS_LATIPES (HOMO_SAPIENS), 26
- OSTREOCOCCUS_TAURI (HOMO_SAPIENS), 26
- PAN_TROGLODYTES (HOMO_SAPIENS), 26
- PATH (ACCNUM), 2
- PEDICULUS_HUMANUS (HOMO_SAPIENS), 26
- PFAM (ACCNUM), 2
- PHYSCOMITRELLA_PATENS (HOMO_SAPIENS), 26
- PHYTOPHTHORA_RAMORUM (HOMO_SAPIENS), 26
- PHYTOPHTHORA_SOJAE (HOMO_SAPIENS), 26
- PLASMODIUM_FALCIPARUM (HOMO_SAPIENS), 26
- PLASMODIUM_VIVAX (HOMO_SAPIENS), 26
- PMID (ACCNUM), 2
- PONGO_PYGMAEUS (HOMO_SAPIENS), 26
- POPULUS_TRICHOCARPA (HOMO_SAPIENS), 26
- print.data.frame, 35
- print.probetable, 35
- PRISTIONCHUS_PACIFICUS (HOMO_SAPIENS), 26
- ProbeAnnDbBimap (Bimap), 10
- ProbeAnnDbBimap-class (Bimap), 10
- ProbeAnnDbMap (Bimap), 10
- ProbeAnnDbMap-class (Bimap), 10
- ProbeGo3AnnDbBimap (Bimap), 10
- ProbeGo3AnnDbBimap-class (Bimap), 10
- PROBEID (ACCNUM), 2
- ProbeIpiAnnDbMap (Bimap), 10
- ProbeIpiAnnDbMap-class (Bimap), 10
- PROSITE (ACCNUM), 2
- PUCCINIA_GRAMINIS (HOMO_SAPIENS), 26
- Rattribnames (Bimap-toTable), 19
- Rattribnames, AnnDbBimap-method (Bimap-toTable), 19
- Rattribnames, Bimap-method (Bimap-toTable), 19
- Rattribnames<- (Bimap-toTable), 19

- Rattribnames<-, AnnDbBimap-method (Bimap-toTable), 19
- Rattribnames<-, FlatBimap-method (Bimap-toTable), 19
- Rattribnames<-, Go3AnnDbBimap-method (Bimap-toTable), 19
- RATTUS_NORVEGICUS (HOMO_SAPIENS), 26
- ReactomeDb-class (AnnotationDb-objects), 7
- REFSEQ (ACCNUM), 2
- revmap (Bimap-direction), 13
- revmap, AnnDbBimap-method (Bimap-direction), 13
- revmap, Bimap-method (Bimap-direction), 13
- revmap, environment-method (Bimap-direction), 13
- revmap, list-method (Bimap-direction), 13
- RHIZOPUS_ORYZAE (HOMO_SAPIENS), 26
- Rkeyname (Bimap-toTable), 19
- Rkeyname, AnnDbBimap-method (Bimap-toTable), 19
- Rkeyname, Bimap-method (Bimap-toTable), 19
- Rkeys (Bimap-direction), 13
- Rkeys, AnnDbBimap-method (Bimap-direction), 13
- Rkeys, AnnDbMap-method (Bimap-direction), 13
- Rkeys, FlatBimap-method (Bimap-direction), 13
- Rkeys, Go3AnnDbBimap-method (Bimap-direction), 13
- Rkeys<- (Bimap-direction), 13
- Rkeys<-, AnnDbBimap-method (Bimap-direction), 13
- Rkeys<-, FlatBimap-method (Bimap-direction), 13
- Rlength (Bimap-direction), 13
- Rlength, AnnDbBimap-method (Bimap-direction), 13
- Rlength, AnnDbMap-method (Bimap-direction), 13
- Rlength, Bimap-method (Bimap-direction), 13
- Rlength, Go3AnnDbBimap-method (Bimap-direction), 13
- SACCHAROMYCES_CEREVISIAE (HOMO_SAPIENS), 26
- sample, 17
- sample (Bimap-envirAPI), 16
- sample, Bimap-method (Bimap-envirAPI), 16
- sample, environment-method (Bimap-envirAPI), 16
- saveDb (AnnotationDb-objects), 7
- saveDb, AnnotationDb-method (AnnotationDb-objects), 7
- SCHISTOSOMA_MANSONI (HOMO_SAPIENS), 26
- SCHIZOSACCHAROMYCES_POMBE (HOMO_SAPIENS), 26
- SCLEROTINIA_SCLEROTIORUM (HOMO_SAPIENS), 26
- Secondary (GOTerms-class), 25
- Secondary, character-method (GOTerms-class), 25
- Secondary, GOTerms-method (GOTerms-class), 25
- Secondary, GOTermsAnnDbBimap-method (GOTerms-class), 25
- select, 19
- select (AnnotationDb-objects), 7
- select, ChipDb-method (AnnotationDb-objects), 7
- select, GODb-method (AnnotationDb-objects), 7
- select, InparanoidDb-method (AnnotationDb-objects), 7
- select, OrgDb-method (AnnotationDb-objects), 7
- select, ReactomeDb-method (AnnotationDb-objects), 7
- setInpBimapFilter (toggleProbes), 38
- setInpBimapFilter, InpAnnDbBimap-method (toggleProbes), 38
- SGD (ACCNUM), 2
- show, AnnDbBimap-method (Bimap), 10
- show, AnnDbTable-method (Bimap-keys), 17
- show, AnnotationDb-method (AnnotationDb-objects), 7
- show, FlatBimap-method (Bimap), 10
- show, GOTerms-method (GOTerms-class), 25
- SMART (ACCNUM), 2
- SORGHUM_BICOLOR (HOMO_SAPIENS), 26
- species (AnnotationDb-objects), 7
- species, AnnotationDb-method (AnnotationDb-objects), 7

- STAGONOSPORA_NODORUM (HOMO_SAPIENS), 26
 STRONGYLOCENTROTUS_PURPURATUS
 (HOMO_SAPIENS), 26
 subset (Bimap-direction), 13
 subset, AnnDbBimap-method
 (Bimap-direction), 13
 subset, Bimap-method (Bimap-direction),
 13
 summary, AnnDbBimap-method (Bimap), 10
 summary, Bimap-method (Bimap), 10
 supportedSeqnameMappings
 (supportedSeqnameStyles), 36
 supportedSeqnames
 (supportedSeqnameStyles), 36
 supportedSeqnameStyles, 36
 SYMBOL (ACCNUM), 2
 Synonym (GOTerms-class), 25
 Synonym, character-method
 (GOTerms-class), 25
 Synonym, GOTerms-method (GOTerms-class),
 25
 Synonym, GOTermsAnnDbBimap-method
 (GOTerms-class), 25
- tagname (Bimap-toTable), 19
 tagname, AnnDbBimap-method
 (Bimap-toTable), 19
 tagname, Bimap-method (Bimap-toTable), 19
 tail, 20
 tail (Bimap-toTable), 19
 tail, FlatBimap-method (Bimap-toTable),
 19
- TAIR (ACCNUM), 2
 TAKIFUGU_RUBRIPES (HOMO_SAPIENS), 26
 TERM (GOID), 24
 Term (GOTerms-class), 25
 Term, character-method (GOTerms-class),
 25
 Term, GOTerms-method (GOTerms-class), 25
 Term, GOTermsAnnDbBimap-method
 (GOTerms-class), 25
 testSeqnames (supportedSeqnameStyles),
 36
- TETRAHYMENA_THERMOPHILA (HOMO_SAPIENS),
 26
 TETRAODON_NIGROVIRIDIS (HOMO_SAPIENS),
 26
 THALASSIOSIRA_PSEUDONANA
 (HOMO_SAPIENS), 26
- THEILERIA_ANNULATA (HOMO_SAPIENS), 26
 THEILERIA_PARVA (HOMO_SAPIENS), 26
 toggleProbes, 38
 toggleProbes, ProbeAnnDbBimap-method
 (toggleProbes), 38
 toggleProbes, ProbeAnnDbMap-method
 (toggleProbes), 38
 toggleProbes, ProbeGo3AnnDbBimap-method
 (toggleProbes), 38
 toggleProbes, ProbeIpiAnnDbMap-method
 (toggleProbes), 38
 toSQLStringSet, 40
 toTable (Bimap-toTable), 19
 toTable, Bimap-method (Bimap-toTable), 19
 toTable, FlatBimap-method
 (Bimap-toTable), 19
 TRIBOLIUM_CASTANEUM (HOMO_SAPIENS), 26
 TRICHOMONAS_VAGINALIS (HOMO_SAPIENS), 26
 TRICHOPLAX_ADHAERENS (HOMO_SAPIENS), 26
 TRYPANOSOMA_CRUZI (HOMO_SAPIENS), 26
- UNIGENE (ACCNUM), 2
 UNIPROT (ACCNUM), 2
 unlist, 41
 unlist2, 41
 USTILAGO_MAYDIS (HOMO_SAPIENS), 26
- XENOPUS_TROPICALIS (HOMO_SAPIENS), 26
- YARROWIA_LIPOLYTICA (HOMO_SAPIENS), 26