

Package ‘r3Cseq’

April 5, 2014

Version 1.8.0

Date 10-25-2012

Title Analysis of Chromosome Conformation Capture and Next-generation Sequencing (3C-seq)

Author Supat Thongjuea, Bergen Center for Computational Science, Norway <supat.thongjuea@bccs.uib.no>

Maintainer Supat Thongjuea <supat.thongjuea@bccs.uib.no>

Depends

GenomicRanges,Rsamtools,data.table,rtracklayer,VGAM,qvalue,RColorBrewer,sqldf,methods

Suggests

BSgenome.Mmusculus.UCSC.mm9,BSgenome.Hsapiens.UCSC.hg18,BSgenome.Hsapiens.UCSC.hg19

Description This package is an implementation of data analysis for the long-range interactions from 3C-seq assay.

License GPL-3

URL <http://r3cseq.genereg.net>

biocViews Preprocessing, Sequencing, HighThroughputSequencing

Collate AllClasses.R AllGenerics.R Export.R FunctionInCommon.R
FunctionsForBatchAnalysis.R RestrictionEnzymeFunctions.R
FunctionsForNoReplicationAnalysis.R Report.R Visualize3Cseq.R Annotation.R

R topics documented:

calculateBatchRPM	2
calculateRPM	3
contrCoverage	4
contrInteractionRegions	4
contrRawData	5
contrReadCount	5
contrRPM	6

enzymeDb	6
expCoverage	7
expInteractionRegions	7
export3Cseq2bedGraph	8
export3CseqRawReads2bedGraph	8
exportBatchInteractions2text	9
exportInteractions2text	10
expRawData	11
expReadCount	11
expRPM	12
generate3CseqReport	13
getBatchInteractions	13
getBatchRawReads	14
getBatchReadCountPerRestrictionFragment	15
getBatchReadCountPerWindow	16
getContrInteractionsInRefseq	17
getCoverage	17
getExpInteractionsInRefseq	18
getInteractions	19
getRawReads	20
getReadCountPerRestrictionFragment	20
getReadCountPerWindow	21
getViewpoint	22
hg18refGene	23
hg19refGene	23
mm9refGene	23
Myb_prom_FB	23
Myb_prom_FL	23
plot3Cecdf	24
plotDomainogramNearViewpoint	24
plotInteractionsNearViewpoint	25
plotInteractionsPerChromosome	25
plotOverviewInteractions	26
r3Cseq-class	27
r3CseqCommon-class	28
r3CseqInBatch-class	29

Index **31**

calculateBatchRPM *calculate read per million (RPM) for replicates analysis*

Description

Normalize 3C-Seq data by transforming raw reads to read per million per each region for replication analysis

Usage

```
calculateBatchRPM(object, normalized_method=c("powerlawFittedRPM", "normalRPM"))
```

Arguments

```
object          r3CseqInBatch object
normalized_method
                 character. method of normalization (default=powerlawFittedRPM)
```

Author(s)

S. Thongjuea

See Also

[calculateRPM](#), [expRPM](#) [contrRPM](#)

Examples

```
#See the vignette
```

calculateRPM	<i>calculate read per million (RPM)</i>
--------------	---

Description

Normalize 3C-Seq data by transforming raw reads to read per million per each region

Usage

```
calculateRPM(object, normalized_method=c("powerlawFittedRPM", "normalRPM"))
```

Arguments

```
object          r3Cseq object
normalized_method
                 character. method of normalization (default=powerlawFittedRPM)
```

Author(s)

S. Thongjuea

See Also

[contrRPM](#), [expRPM](#), [calculateBatchRPM](#)

Examples

```
#See the vignette
```

contrCoverage *This method has been removed.*

Description

This method has been removed.

contrInteractionRegions
get interaction regions from the control

Description

get all identified interaction regions from the control

Usage

contrInteractionRegions(object)

Arguments

object r3Cseq or r3CseqInBatch object

Value

The candidate interaction regions show in the IRange object

Author(s)

S. Thongjuea

See Also

[expInteractionRegions](#), [getInteractions](#)

Examples

#See the vignette

contrRawData *Accessors for the 'contrRawData' slot of a r3Cseq object.*

Description

The 'contrRawData' slot of hold the raw aligned reads data in the GRanges object.

Usage

```
## S4 method for signature r3Cseq
contrRawData(object)
## S4 replacement method for signature r3Cseq
contrRawData(object) <- value
```

Arguments

object	r3Cseq object
value	a GRanges object of aligned reads

Author(s)

S. Thongjuea

See Also

[expRawData](#)

Examples

```
#See the vignette
```

contrReadCount *get read count per region for the control*

Description

get the read count per region for the control

Usage

```
contrReadCount(object)
```

Arguments

object	r3Cseq object
--------	---------------

Author(s)

S. Thongjuea

See Also[expReadCount](#), [getReadCountPerRestrictionFragment](#)**Examples**

#See the vignette

contrRPM	<i>get read per million (RPM) for the control</i>
----------	---

Description

get the normalized 3C-seq data (RPM) for the control

Usage

contrRPM(object)

Arguments

object r3Cseq or r3CseqInBatch object

Author(s)

S. Thongjuea

See Also[calculateRPM](#), [expRPM](#)**Examples**

#See the vignette

enzymeDb	<i>Rebase The Restriction Enzyme Database</i>
----------	---

Description

The database includes all restriction enzyme information from the REBASE database.

References<http://rebase.neb.com/rebase/rebase.html>

expCoverage *This method has been removed.*

Description

This method has been removed.

expInteractionRegions *get interaction regions from the experiment*

Description

get identified interaction regions from the experiment

Usage

```
expInteractionRegions(object)
```

Arguments

object r3Cseq or r3CseqInBatch object

Value

The candidate interaction regions show in the IRange object

Author(s)

S. Thongjuea

See Also

[getInteractions](#), [contrInteractionRegions](#)

Examples

```
#See the vignette
```

export3Cseq2bedGraph *export interaction regions to the 'bedGraph' format*

Description

export interaction regions from RagedData to the bedGraph format, which suitable for uploading to the UCSC genome browser

Usage

```
export3Cseq2bedGraph(object, datatype=c("rpm", "read_count"))
```

Arguments

object	r3Cseq object, The object might contain the interaction regions generated by function getInteractions
datatype	read_count : read count per restriction fragment rpm : normalized read per million per restriction fragment

Value

The text file in 'bedGraph' format

Author(s)

S. Thongjuea

See Also

[exportInteractions2text](#)

Examples

```
#See the vignette
```

export3CseqRawReads2bedGraph
export the interaction signal from the raw reads to the 'bedGraph' format

Description

export interaction regions signal to the bedGraph format, which suitable for uploading to the UCSC genome browser

Usage

`export3CseqRawReads2bedGraph(object)`

Arguments

`object` `r3Cseq` object

Value

The text file in 'bedGraph' format

Author(s)

S. Thongjuea

See Also

[exportInteractions2text](#), [export3Cseq2bedGraph](#),

Examples

#See the vignette

`exportBatchInteractions2text`

export identified interaction regions to the tab separated format for replicates analysis

Description

export interaction regions from RagedData to the tab separated format for replicates analysis

Usage

`exportBatchInteractions2text(object)`

Arguments

`object` `r3CseqInBatch` object

Value

The text file in the tab separated format

Author(s)

S. Thongjuea

See Also

[export3Cseq2bedGraph](#), [exportInteractions2text](#)

Examples

```
#See the vignette
```

```
exportInteractions2text
```

export identified interaction regions to the tab separated format

Description

export interaction regions from RagedData to the tab separated format

Usage

```
exportInteractions2text(object)
```

Arguments

object r3Cseq object

Value

The text file in the tab separated format

Author(s)

S. Thongjuea

See Also

[export3Cseq2bedGraph](#)

Examples

```
#See the vignette
```

expRawData	<i>Accessors for the 'expRawData' slot of a r3Cseq object.</i>
------------	--

Description

The 'expRawData' slot of hold the raw aligned reads data in the GRanges object.

Usage

```
## S4 method for signature r3Cseq
expRawData(object)
## S4 replacement method for signature r3Cseq
expRawData(object) <- value
```

Arguments

object	r3Cseq object
value	a GRanges object of aligned reads

Author(s)

S. Thongjuea

See Also

[expRawData](#)

Examples

```
#See the vignette
```

expReadCount	<i>get read count per region for the experiment</i>
--------------	---

Description

get the read count per region for the experiment

Usage

```
expReadCount(object)
```

Arguments

object	r3Cseq
--------	--------

Author(s)

S. Thongjuea

See Also

[contrReadCount](#), [getReadCountPerRestrictionFragment](#)

Examples

```
#See the vignette
```

expRPM

get read per million (RPM) for the experiment

Description

get the normalized 3C-seq data (RPM) for the experiment

Usage

```
expRPM(object)
```

Arguments

```
object          r3Cseq or r3CseqInBatch
```

Author(s)

S. Thongjuea

See Also

[calculateRPM](#), [contrRPM](#)

Examples

```
#See the vignette
```

generate3CseqReport *generate reports for analysis results from r3Cseq*

Description

generate reports for analysis results from r3Cseq, the report contains all plots in one pdf file and a text separated out put file.

Usage

```
generate3CseqReport(obj)
```

Arguments

obj r3Cseq or r3CseqInBatch object

Value

The text file in the tab separated format and the pdf file of all plots

Author(s)

S. Thongjuea

See Also

[exportInteractions2text](#), [plotOverviewInteractions](#), [plotInteractionsPerChromosome](#), [plotInteractionsNearViewpoint](#)

Examples

```
#See the vignette
```

getBatchInteractions *calculate z-score, assign p-value and q-value for each interaction region for replicates data sets*

Description

Calculate z-score, assign p-value and q-value to each interaction regions for replicates data sets

Usage

```
getBatchInteractions(object,method=c("union","intersection"),smoothing.parameter=0.1,fdr=0.05)
```

Arguments

object	r3Cseq object
method	character. The method for combining biological replicates for 3C-Seq analysis (default = "union")
smoothing.parameter	A level at which cubic smoothing spline for the spar (see vsmooth.spline) input parameter. Must be in (0.06,0.4] (default=0.1)
fdr	A level at which to control the FDR. Must be in (0,1] (default=0.05)

Value

The interaction regions show in the RangedData

Author(s)

S. Thongjuea

See Also

[getInteractions vsmooth.spline](#)

Examples

```
#See the vignette
```

getBatchRawReads	<i>Get aligned reads from the replicates BAM files</i>
------------------	--

Description

Reading in the input BAM files from the 3C-Seq replicates analysis and then save files as the local GRanged object .rData files

Usage

```
getBatchRawReads(object)
```

Arguments

object	r3CseqInBatch object
--------	----------------------

Value

The GRangedData represents the aligned reads from the BAM file

Author(s)

S. Thongjuea

See Also

[getRawReads](#),

Examples

#See the vignette

`getBatchReadCountPerRestrictionFragment`
count reads for replicates analysis

Description

Counts the number of reads from 3C-Seq data per each restriction fragment for replicates analysis

Usage

```
getBatchReadCountPerRestrictionFragment(object, getReadsMethod = c("wholeReads", "adjacentFragmentEnds"), nFragmentExcludedReadsNearViewpoint=2)
```

Arguments

`object` `r3CseqInBatch` object
`getReadsMethod` character. To count all reads found in the particular restriction fragment uses `wholeReads` option. To count reads found around the edge of restriction fragment both 5'utr and 3'utr uses `adjacentFragmentEndsReads` option (default=`wholeReads`)
`nFragmentExcludedReadsNearViewpoint`
Numeric. The number of excluded fragments around the viewpoint, reads found in these fragments will be removed from the analysis (default=2)

Value

The `RangedData` represents the number of reads per each restriction fragment

Author(s)

S. Thongjuea

See Also

[getReadCountPerWindow](#), [getReadCountPerRestrictionFragment](#)

Examples

#See the vignette

`getBatchReadCountPerWindow`*count reads per window size for replicates analysis*

Description

Counts the number of reads from 3C-Seq data per each window size for replicates analysis

Usage

```
getBatchReadCountPerWindow(object, windowSize=5e3, nFragmentExcludedReadsNearViewpoint=2)
```

Arguments

`object` `r3CseqInBatch` object

`windowSize` Numeric. non-overlapping window size for counting reads (default=5e3)

`nFragmentExcludedReadsNearViewpoint`

Numeric. The number of excluded fragments around the viewpoint, reads found in these fragments will be removed from the analysis (default=2)

Value

The `RangedData` represents the number of reads per each window size

Author(s)

S. Thongjuea

See Also

[getReadCountPerRestrictionFragment](#), [getBatchReadCountPerRestrictionFragment](#), [getReadCountPerWindow](#),

Examples

```
#See the vignette
```

getContrInteractionsInRefseq
identified significant interaction regions for RefSeq genes

Description

Get a list of genes that contain strong interaction signals in the control

Usage

```
getContrInteractionsInRefseq(obj, cutoff.qvalue=0.05, expanded_upstream=50e3, expanded_downstream=10e3)
```

Arguments

obj obj is r3Cseq or r3CseqInBatch object
cutoff.qvalue Numeric. The cutoff q-value (default=0.05)
expanded_upstream Numeric. The expanded distance from the upstream of a gene start (default=50e3)
expanded_downstream Numeric. The expanded distance from the downstream of a gene end (default =10e3)

Value

List of identified genes, which contain strong interaction signals

Author(s)

S. Thongjuea

See Also

[getContrInteractionsInRefseq](#)

Examples

```
# See the vignette
```

getCoverage *This method has been removed.*

Description

This method has been removed.

`getExpInteractionsInRefseq`*identified significant interaction regions for RefSeq genes*

Description

Get a list of genes that contain strong interaction signals in the experiment

Usage

```
getExpInteractionsInRefseq(obj, cutoff.qvalue=0.05, expanded_upstream=50e3, expanded_downstream=10e3)
```

Arguments

`obj` `obj` is `r3Cseq` or `r3CseqInBatch` object
`cutoff.qvalue` Numeric. The cutoff q-value (default=0.05)
`expanded_upstream` Numeric. The expanded distance from the upstream of a gene start (default=50e3)
`expanded_downstream` Numeric. The expanded distance from the downstream of a gene end (default=10e3)

Value

List of identified genes, which contain strong interaction signals

Author(s)

S. Thongjuea

See Also

[getContrInteractionsInRefseq](#)

Examples

```
# See the vignette
```

getInteractions	<i>calculate z-score, assign p-value and q-value for each interaction region</i>
-----------------	--

Description

Calculate z-score, assign p-value and q-value to each interaction regions

Usage

```
getInteractions(object, smoothing.parameter=0.1, fdr=0.05)
```

Arguments

object r3Cseq object

smoothing.parameter

A level at which cubic smoothing spline for the spar (see vsmooth.spline) input parameter. Must be in (0.06,0.4] (default=0.1)

fdr A level at which to control the FDR. Must be in (0,1] (default=0.05)

Value

The interaction regions show in the RangedData

Author(s)

S. Thongjuea

See Also

[getBatchInteractions vsmooth.spline](#)

Examples

```
#See the vignette
```

`getRawReads`*Get aligned reads from the BAM file*

Description

Reading in the input BAM file and then store it in the GRanged object

Usage

```
getRawReads(object)
```

Arguments

object r3Cseq object

Value

The GRangedData represents the aligned reads from the BAM file

Author(s)

S. Thongjuea

See Also

[getBatchRawReads](#),

Examples

```
#See the vignette
```

`getReadCountPerRestrictionFragment`*count reads per resitrcition fragment*

Description

Counts the number of reads from 3C-Seq data per each restriction fragment

Usage

```
getReadCountPerRestrictionFragment(object, getReadsMethod = c("wholeReads", "adjacentFragmentEndsReads"),  
nFragmentExcludedReadsNearViewpoint=2)
```

Arguments

object r3Cseq object

getReadsMethod character. To count all reads found in the particular restriction fragment uses wholeReads option. To count reads found around the edge of restriction fragment both 5'utr and 3'utr uses adjacentFragmentEndsReads option (default=wholeReads)

nFragmentExcludedReadsNearViewpoint
 Numeric. The number of excluded fragments around the viewpoint, reads found in these fragments will be removed from the analysis (default=2)

Value

The RangedData represents the number of reads per each restriction fragment

Author(s)

S. Thongjuea

See Also

[getReadCountPerWindow](#), [getBatchReadCountPerRestrictionFragment](#)

Examples

```
#See the vignette
```

`getReadCountPerWindow` *count reads per window size*

Description

Counts the number of reads from 3C-Seq data per each window size

Usage

```
getReadCountPerWindow(object, windowSize=5e3, nFragmentExcludedReadsNearViewpoint=2, mode=c("non-overl
```

Arguments

object r3Cseq object

windowSize Numeric. non-overlapping window size for counting reads (default=5e3)

nFragmentExcludedReadsNearViewpoint
 Numeric. The number of excluded fragments around the viewpoint, reads found in these fragments will be removed from the analysis (default=2)

mode character. The window-based modes analysis (default="non-overlapping")

Value

The RangedData represents the number of reads per each window size

Author(s)

S. Thongjuea

See Also

[getReadCountPerRestrictionFragment](#),

Examples

```
#See the vignette
```

getViewpoint	<i>get the viewpoint of 3C-seq data</i>
--------------	---

Description

The viewpoint is the bait of 3C method, which can be a promoter region of an interested gene, an enhancer, and a transcription factor binding region.

Usage

```
getViewpoint(obj)
```

Arguments

obj r3Cseq or r3CseqInBatch object

Value

The viewpoint shows in the IRanges

Author(s)

S. Thongjuea

Examples

```
#See the vignette
```

hg18refGene	<i>hg18's refGenes</i>
-------------	------------------------

Description

The human (hg18) reference genes from UCSC

hg19refGene	<i>hg19's refGenes</i>
-------------	------------------------

Description

The human (hg19) reference genes from UCSC

mm9refGene	<i>mm9's refGenes</i>
------------	-----------------------

Description

The mouse (mm9) reference genes from UCSC

Myb_prom_FB	<i>Myb_prom_FB a data set for the example of r3Cseq analysis</i>
-------------	--

Description

The example aligned reads generated by 3C-Seq protocol from fetal brain. The promoter region of the Myb's gene was selected as the viewpoint. This data was transformed from aligned reads shown in the BAM file to GRanged object by using Rsamtools.

Myb_prom_FL	<i>Myb_prom_FL a data set for the example of r3Cseq analysis</i>
-------------	--

Description

The example aligned reads generated by 3C-Seq protocol from fetal liver. The promoter region of the Myb's gene was selected as the viewpoint. This data was transformed from aligned reads shown in the BAM file to GRanged object by using Rsamtools.

plot3Cecdf *This method has been removed.*

Description

This method has been removed.

plotDomainogramNearViewpoint
Plot domainogram of interaction regions near the viewpoint

Description

Plot domainogram of interaction regions near the viewpoint

Usage

```
plotDomainogramNearViewpoint(object, smoothing.parameter=0.1, distance=5e5, maximum_window=25e3, view=c
```

Arguments

object	r3Cseq or r3CseqInBatch object
smoothing.parameter	A level at which cubic smoothing spline for the spar (see vsmooth.spline) input parameter. Must be in (0.06,0.4] (default=0.1)
distance	Numeric. The distance relative to the viewpoint (default=5e5)
maximum_window	Numeric. The maximum windowing (default=25e3). We normally compute the interaction regions per window starting from 2Kb to maximum window (default=25kb) to make the interaction matrix for visualizing the domainogram.
view	character. The selected view of data (default="experiment")

Value

Plots of domainogram for interaction regions close to the viewpoint

Author(s)

S. Thongjuea

See Also

[plotOverviewInteractions](#), [plotInteractionsPerChromosome](#), [plotInteractionsNearViewpoint](#)

Examples

```
# See the vignette
```

`plotInteractionsNearViewpoint`
Plot identified interaction regions near the viewpoint

Description

Plot identified interaction regions near the viewpoint

Usage

```
plotInteractionsNearViewpoint(obj, distance=5e5)
```

Arguments

`obj` `obj` is `r3Cseq` or `r3CseqInBatch` object
`distance` Numeric. The distance relative to the viewpoint (default=5e5)

Value

Plots of identified interaction regions close to the viewpoint

Author(s)

S. Thongjuea

See Also

[plotOverviewInteractions](#), [plotInteractionsPerChromosome](#), [plotDomainogramNearViewpoint](#)

Examples

```
# See the vignette
```

`plotInteractionsPerChromosome`
Plot interaction regions per each chromosome of interest

Description

Plot the distribution of interaction regions per each chromosome

Usage

```
plotInteractionsPerChromosome(obj, chromosomeName)
```

Arguments

obj obj is r3Cseq or r3CseqInBatch object.
chromosomeName Character. The input chromosome name (e.g. "chr1")

Value

Plots of interaction regions per chromosome.

Author(s)

S. Thongjuea

See Also

[plotInteractionsNearViewpoint](#), [plotOverviewInteractions](#), [plotDomainogramNearViewpoint](#)

Examples

```
# See the vignette
```

plotOverviewInteractions

Plot overview of identified interaction regions for genome-wide

Description

Plot the distribution of identified interaction regions across genome

Usage

```
plotOverviewInteractions(obj, cutoff.qvalue=0.05)
```

Arguments

obj obj is r3Cseq or r3CseqInBatch object
cutoff.qvalue Numeric. The cutoff q-value (default=0.05)

Value

Plots of identified 3C-Seq interaction regions genome-wide

Author(s)

S. Thongjuea

See Also

[plotInteractionsNearViewpoint](#), [plotInteractionsPerChromosome](#), [plotDomainogramNearViewpoint](#)

Examples

```
# See the vignette
```

r3Cseq-class	<i>r3Cseq objects</i>
--------------	-----------------------

Description

The r3Cseq class is the extended class from r3CseqCommon class. It is a general container for storing and manipulating a set of input parameters, RangeData of interactions regions from r3Cseq analysis, and the raw reads GRanged data of the genome-wide interaction signal generated by next-generation sequencing.

Extends

Class r3CseqCommon, directly.

Slots

organismName Object of class "character" the version of particular assembly genome from UCSC (e.g. mm9, hg18, hg19). The package supports three genome assemblies consisting of mouse (mm9), and human (hg18, hg19).

restrictionEnzyme Object of class "character" this is the primary restriction enzyme name using in 3C-Seq experiment

viewpoint_chromosome Object of class "character" chromosome name of where is the viewpoint located eg. chr10, chrX etc.

viewpoint_primer_forward Object of class "character" the forward primer DNA sequences for the viewpoint amplification

viewpoint_primer_reverse Object of class "character" the reverse primer DNA sequences for the viewpoint amplification

expReadCount Object of class "RangedData" the read count in experiment

contrReadCount Object of class "RangedData" the read count in control

expRPM Object of class "RangedData" the normalized read read per million in experiment

contrRPM Object of class "RangedData" the normalized read read per million in control

expInteractionRegions Object of class "RangedData" the identified interaction regions in experiment

contrInteractionRegions Object of class "RangedData" the identified interaction regions in control

isControlInvolved Object of class "logical" the logical to ask whether the control is involved in the analysis or not

alignedReadsBamExpFile Object of class "character" the file name of experiment in BAM format

alignedReadsBamContrFile Object of class "character" the file name of control in BAM format

expLabel Object of class "character" the experiment name

contrLabel Object of class "character" the control name

expLibrarySize Object of class "integer" the library size of experiment

contrLibrarySize Object of class "integer" the library size of control

expReadLength Object of class "integer" the read length of experiment

contrReadLength Object of class "integer" the read length of experiment

expRawData Object of class "GRanges" the raw reads found in experiment

contrRawData Object of class "GRanges" the raw reads found in control

Author(s)

S. Thongjuea

See Also

[r3CseqCommon](#), [r3CseqInBatch](#)

Examples

```
# See the vignette
```

r3CseqCommon-class *r3CseqCommon objects*

Description

The `r3CseqCommon` class is a general container for storing and manipulating a set of input parameters, `RangeData` of interactions regions from `r3Cseq` analysis. It is a root class for `r3Cseq` and `r3CseqInBatch` classes.

Slots

`organismName` Object of class "character" the version of particular assembly genome from UCSC (e.g. mm9, hg18, hg19) . The package supports three genome assemblies consisting of mouse (mm9), and human (hg18, hg19).

`restrictionEnzyme` Object of class "character" this is the primary restriction enzyme name using in 3C-Seq experiment

`viewpoint_chromosome` Object of class "character" chromosome name of where is the viewpoint located eg. chr10, chrX etc.

viewpoint_primer_forward Object of class "character" the forward primer DNA sequences for the viewpoint amplification

viewpoint_primer_reverse Object of class "character" the reverse primer DNA sequences for the viewpoint amplification

expReadCount Object of class "RangedData" the read count in experiment

contrReadCount Object of class "RangedData" the read count in control

expRPM Object of class "RangedData" the normalized read read per million in experiment

contrRPM Object of class "RangedData" the normalized read read per million in control

expInteractionRegions Object of class "RangedData" the identified interaction regions in experiment

contrInteractionRegions Object of class "RangedData" the identified interaction regions in control

isControlInvolved Object of class "logical" the logical to ask whether the control is involved in the analysis or not

Author(s)

S. Thongjuea

See Also

[r3Cseq](#), [r3CseqInBatch](#)

Examples

```
# See the vignette
```

r3CseqInBatch-class *r3CseqInBatch* objects

Description

The r3CseqInBatch class is the extended class from r3CseqCommon class. It is a general container for storing and manipulating a set of input parameters, RangedData of interactions regions from r3Cseq analysis for replicates data sets.

Extends

Class r3CseqCommon, directly.

Slots

organismName Object of class "character" the version of particular assembly genome from UCSC (e.g. mm9, hg18, hg19) . The package supports three genome assemblies consisting of mouse (mm9), and human (hg18, hg19).

restrictionEnzyme Object of class "character" this is the primary restriction enzyme name using in 3C-Seq experiment

viewpoint_chromosome Object of class "character" chromosome name of where is the viewpoint located eg. chr10, chrX etc.

viewpoint_primer_forward Object of class "character" the forward primer DNA sequences for the viewpoint amplification

viewpoint_primer_reverse Object of class "character" the reverse primer DNA sequences for the viewpoint amplification

expReadCount Object of class "RangedData" the read count in experiment

contrReadCount Object of class "RangedData" the read count in control

expRPM Object of class "RangedData" the normalized read read per million in experiment

contrRPM Object of class "RangedData" the normalized read read per million in control

expInteractionRegions Object of class "RangedData" the identified interaction regions in experiment

contrInteractionRegions Object of class "RangedData" the identified interaction regions in control

isControlInvolved Object of class "logical" the logical to ask whether the control is involved in the analysis or not

bamFilesDirectory Object of class "character" the path name of directory that contains BAM files

BamExpFiles Object of class "vector" the file names of BAM files in the experiment

BamContrFiles Object of class "vector" the file names of BAM files in the control

expBatchLabel Object of class "vector" the labeled experiment names

contrBatchLabel Object of class "vector" the labeled control names

readCountTable Object of class "RangedData" the read count table

RPMsTable Object of class "RangedData" the normalized read per million table

expBatchLibrarySize Object of class "vector" the library size of each experiment

contrBatchLibrarySize Object of class "vector" the library size of each control

Author(s)

S. Thongjuea

See Also

[r3CseqCommon](#), [r3CseqInBatch](#)

Examples

```
# See the vignette
```

Index

*Topic **classes**

r3Cseq-class, 27
r3CseqCommon-class, 28
r3CseqInBatch-class, 29

*Topic **datasets**

enzymeDb, 6
hg18refGene, 23
hg19refGene, 23
mm9refGene, 23
Myb_prom_FB, 23
Myb_prom_FL, 23

calculateBatchRPM, 2, 3
calculateBatchRPM, r3CseqInBatch-method
(calculateBatchRPM), 2
calculateRPM, 3, 3, 6, 12
calculateRPM, r3Cseq-method
(calculateRPM), 3
contrCoverage, 4
contrCoverage, r3Cseq-method
(contrCoverage), 4
contrInteractionRegions, 4, 7
contrInteractionRegions, r3CseqCommon-method
(contrInteractionRegions), 4
contrRawData, 5
contrRawData, r3Cseq-method
(contrRawData), 5
contrRawData<- (contrRawData), 5
contrRawData<- , r3Cseq-method
(contrRawData), 5
contrReadCount, 5, 12
contrReadCount, r3CseqCommon-method
(contrReadCount), 5
contrRPM, 3, 6, 12
contrRPM, r3CseqCommon-method
(contrRPM), 6

enzymeDb, 6
expCoverage, 7

expCoverage, r3Cseq-method
(expCoverage), 7
expInteractionRegions, 4, 7
expInteractionRegions, r3CseqCommon-method
(expInteractionRegions), 7
export3Cseq2bedGraph, 8, 9, 10
export3Cseq2bedGraph, r3Cseq-method
(export3Cseq2bedGraph), 8
export3CseqRawReads2bedGraph, 8
export3CseqRawReads2bedGraph, r3Cseq-method
(export3CseqRawReads2bedGraph),
8
exportBatchInteractions2text, 9
exportBatchInteractions2text, r3CseqInBatch-method
(exportBatchInteractions2text),
9
exportInteractions2text, 8, 9, 10, 10, 13
exportInteractions2text, r3Cseq-method
(exportInteractions2text), 10
expRawData, 5, 11, 11
expRawData, r3Cseq-method (expRawData),
11
expRawData<- (expRawData), 11
expRawData<- , r3Cseq-method
(expRawData), 11
expReadCount, 6, 11
expReadCount, r3CseqCommon-method
(expReadCount), 11
expRPM, 3, 6, 12
expRPM, r3CseqCommon-method (expRPM), 12
generate3CseqReport, 13
generate3CseqReport, r3Cseq-method
(generate3CseqReport), 13
generate3CseqReport, r3CseqInBatch-method
(generate3CseqReport), 13
getBatchInteractions, 13, 19
getBatchInteractions, r3CseqInBatch-method
(getBatchInteractions), 13
getBatchRawReads, 14, 20

- getBatchRawReads, r3CseqInBatch-method
(getBatchRawReads), [14](#)
- getBatchReadCountPerRestrictionFragment,
[15](#), [16](#), [21](#)
- getBatchReadCountPerRestrictionFragment, r3CseqInBatch-method
(getBatchReadCountPerRestrictionFragment), [24](#)
- getBatchReadCountPerWindow, [16](#)
- getBatchReadCountPerWindow, r3CseqInBatch-method
(getBatchReadCountPerWindow), [16](#)
- getContrInteractionsInRefseq, [17](#), [17](#), [18](#)
- getContrInteractionsInRefseq, r3Cseq-method
(getContrInteractionsInRefseq), [17](#)
- getCoverage, [17](#)
- getCoverage, r3Cseq-method
(getCoverage), [17](#)
- getExpInteractionsInRefseq, [18](#)
- getExpInteractionsInRefseq, r3Cseq-method
(getExpInteractionsInRefseq), [18](#)
- getInteractions, [4](#), [7](#), [8](#), [14](#), [19](#)
- getInteractions, r3Cseq-method
(getInteractions), [19](#)
- getRawReads, [15](#), [20](#)
- getRawReads, r3Cseq-method
(getRawReads), [20](#)
- getReadCountPerRestrictionFragment, [6](#),
[12](#), [15](#), [16](#), [20](#), [22](#)
- getReadCountPerRestrictionFragment, r3Cseq-method
(getReadCountPerRestrictionFragment), [20](#)
- getReadCountPerWindow, [15](#), [16](#), [21](#), [21](#)
- getReadCountPerWindow, r3Cseq-method
(getReadCountPerWindow), [21](#)
- getViewpoint, [22](#)
- getViewpoint, r3Cseq-method
(getViewpoint), [22](#)

- hg18refGene, [23](#)
- hg19refGene, [23](#)

- mm9refGene, [23](#)
- Myb_prom_FB, [23](#)
- Myb_prom_FL, [23](#)

- plot3Cecdf, [24](#)
- plot3Cecdf, r3Cseq-method (plot3Cecdf),
[24](#)
- plotDomainogramNearViewpoint, [24](#), [25](#)–[27](#)
- plotDomainogramNearViewpoint, r3Cseq-method
(plotDomainogramNearViewpoint), [24](#)
- plotInteractionsNearViewpoint, [13](#), [24](#),
[25](#), [26](#), [27](#)
- plotInteractionsNearViewpoint, r3Cseq-method
(plotInteractionsNearViewpoint),
[25](#)
- plotInteractionsPerChromosome, [13](#), [24](#),
[25](#), [25](#), [27](#)
- plotInteractionsPerChromosome, r3Cseq-method
(plotInteractionsPerChromosome),
[25](#)
- plotOverviewInteractions, [13](#), [24](#), [25](#), [26](#),
[26](#)
- plotOverviewInteractions, r3Cseq-method
(plotOverviewInteractions), [26](#)

- r3Cseq, [29](#)
- r3Cseq (r3Cseq-class), [27](#)
- r3Cseq-class, [27](#)
- r3CseqCommon, [28](#), [30](#)
- r3CseqCommon (r3CseqCommon-class), [28](#)
- r3CseqCommon-class, [28](#)
- r3CseqInBatch, [28](#)–[30](#)
- r3CseqInBatch (r3CseqInBatch-class), [29](#)
- r3CseqInBatch-class, [29](#)

- vsmooth.spline, [14](#), [19](#)