

org.Sc.sgd.db

October 16, 2009

R topics documented:

org.Sc.sgdALIAS	1
org.Sc.sgd.db	2
org.Sc.sgdCHRLNGTHS	3
org.Sc.sgdCHRLOC	3
org.Sc.sgdCHR	4
org.Sc.sgdCOMMON2ORF	4
org.Sc.sgd_dbconn	5
org.Sc.sgdDESCRIPTION	6
org.Sc.sgdENSEMBL	7
org.Sc.sgdENTREZID	8
org.Sc.sgdENZYME	8
org.Sc.sgdGENENAME	9
org.Sc.sgdGO2ALLORFS	10
org.Sc.sgdGO	11
org.Sc.sgdINTERPRO	13
org.Sc.sgdMAPCOUNTS	13
org.Sc.sgdORGANISM	14
org.Sc.sgdPATH	14
org.Sc.sgdPFAM	15
org.Sc.sgdPMID	16
org.Sc.sgdREFSEQ	17
org.Sc.sgdREJECTORF	18
org.Sc.sgdSGD	18
org.Sc.sgdSMART	19
org.Sc.sgdUNIPROT	19
Index	21

org.Sc.sgdALIAS *Map Open Reading Frame (ORF) Identifiers to Alias Gene Names*

Description

A set of gene names may have been used to report yeast genes represented by ORF identifiers. One of these names is chosen to be the primary gene name, and the others are considered aliases. This R object provides mappings between the primary name and aliases.

Details

Each primary name maps to a vector of alias names. If there are no aliases, the vector will contain NA.

Annotation based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

References

<http://www.yeastgenome.org/DownloadContents.shtml>

Examples

```
x <- org.Sc.sgdALIAS
# Get the probe identifiers that are mapped to alias names
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the alias names for the first five probes
  xx[1:5]
  # For the first probe
  xx[[1]]
}
```

org.Sc.sgd.db

Bioconductor annotation data package

Description

Welcome to the org.Sc.sgd.db annotation Package. This is an organism specific package. The purpose is to provide detailed information about the species abbreviated in the second part of the package name org.Sc.sgd.db. "Sc" is for *Saccharomyces cerevisiae*. This package is updated biannually.

You can learn what objects this package supports with the following command:

```
ls("package:org.Sc.sgd.db")
```

Each of these objects has their own manual page detailing where relevant data was obtained along with examples of how to use it. Many of these objects also have a reverse map available. When this is true, expect to usually find relevant information on the same manual page as the forward map.

Examples

```
ls("package:org.Sc.sgd.db")
```

```
org.Sc.sgdCHRLENGTHS
```

A named vector for the length of each of the chromosomes

Description

org.Sc.sgdCHRLENGTHS provides the length measured in base pairs for each of the chromosomes.

Details

This is a named vector with chromosome numbers as the names and the corresponding lengths for chromosomes as the values.

Total lengths of chromosomes were derived by calculating the number of base pairs on the sequence string for each chromosome.

Examples

```
tt <- org.Sc.sgdCHRLENGTHS
# Length of chromosome 1
tt["1"]
```

```
org.Sc.sgdCHRLOC
```

ORF IDs to Chromosomal Location

Description

org.Sc.sgdCHRLOC is an R object that maps ORF identifiers to the starting position of the gene. The position of a gene is measured as the number of base pairs.

The CHRLOCEND mapping is the same as the CHRLOC mapping except that it specifies the ending base of a gene instead of the start.

Details

Each ORF identifier maps to a named vector of chromosomal locations, where the name indicates the chromosome.

Chromosomal locations on both the sense and antisense strands are measured as the number of base pairs from the p (5' end of the sense strand) to q (3' end of the sense strand) arms. Chromosomal locations on the antisense strand have a leading "-" sign (e. g. -1234567).

Since some genes have multiple start sites, this field can map to multiple locations.

Mappings were based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

Examples

```
x <- org.Sc.sgdCHRLoc
# Get the ORF identifiers that are mapped to chromosome locations
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the CHRLoc for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdCHR

Map ORF IDs to Chromosomes

Description

org.Sc.sgdCHR is an R object that provides mappings between ORF identifiers and the chromosome that contains the gene of interest.

Details

Each ORF identifier maps to a vector of a chromosome.

Mappings were based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

Examples

```
x <- org.Sc.sgdCHR
# Get the ORF identifiers that are mapped to a chromosome
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the CHR for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdCOMMON2ORF

Map Between Yeast Common Names and ORF Identifiers

Description

org.Sc.sgdCOMMON2ORF is an R object that maps the yeast common names (gene names and aliases) to the corresponding yeast ORF identifiers.

Details

Each yeast common name, either gene name or alias, maps to a vector of ORF identifiers. This mapping is the reverse mappings of org.Sc.sgdGENENAME.

Mappings were based on data provided by:

Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

Examples

```
# Convert to a list
xx <- as.list(org.Sc.sgdCOMMON2ORF)
# Remove probes that do not map in COMMON2ORF
xx <- xx[!is.na(xx)]
if(length(xx) > 0){
  # Gets the ORF identifiers for the first five gene names/alias
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgd_dbconn *Collect information about the package annotation DB*

Description

Some convenience functions for getting a connection object to (or collecting information about) the package annotation DB.

Usage

```
org.Sc.sgd_dbconn()
org.Sc.sgd_dbfile()
org.Sc.sgd_dbschema(file="", show.indices=FALSE)
org.Sc.sgd_dbInfo()
```

Arguments

`file` A connection, or a character string naming the file to print to (see the `file` argument of the `cat` function for the details).

`show.indices` The CREATE INDEX statements are not shown by default. Use `show.indices=TRUE` to get them.

Details

`org.Sc.sgd_dbconn` returns a connection object to the package annotation DB. **IMPORTANT:** Don't call `dbDisconnect` on the connection object returned by `org.Sc.sgd_dbconn` or you will break all the `AnnDbObj` objects defined in this package!

`org.Sc.sgd_dbfile` returns the path (character string) to the package annotation DB (this is an SQLite file).

`org.Sc.sgd_dbschema` prints the schema definition of the package annotation DB.

`org.Sc.sgd_dbInfo` prints other information about the package annotation DB.

Value

org.Sc.sgd_dbconn: a DBIConnection object representing an open connection to the package annotation DB.

org.Sc.sgd_dbfile: a character string with the path to the package annotation DB.

org.Sc.sgd_dbschema: none (invisible NULL).

org.Sc.sgd_dbInfo: none (invisible NULL).

See Also

[dbGetQuery](#), [dbConnect](#), [dbconn](#), [dbfile](#), [dbschema](#), [dbInfo](#)

Examples

```
## Count the number of rows in the "sgd" table:
dbGetQuery(org.Sc.sgd_dbconn(), "SELECT COUNT(*) FROM sgd")

## The connection object returned by org.Sc.sgd_dbconn() was created with:
dbConnect(SQLite(), dbname=org.Sc.sgd_dbfile(), cache_size=64000, synchronous=0)

org.Sc.sgd_dbschema()

org.Sc.sgd_dbInfo()
```

```
org.Sc.sgdDESCRIPTION
```

An annotation data file that maps Open Reading Frame (ORF) identifiers to textural descriptions of the corresponding genes

Description

org.Sc.sgdDESCRIPTION maps yeast ORF identifiers to descriptive information about genes corresponding to the ORF identifiers

Details

This is an R object containing key and value pairs. Keys are ORF identifiers and values are the corresponding descriptions of genes. Values are vectors of length 1. Probe identifiers that can not be mapped to descriptive information are assigned a value NA.

Annotation based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

References

<http://www.yeastgenome.org/DownloadContents.shtml>

Examples

```
x <- org.Sc.sgdDESCRIPTION
# Get the probe identifiers that are mapped to gene descriptions
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the gene descriptions for the first five probes
  xx[1:5]
  # For the first probe
  xx[[1]]
}
```

org.Sc.sgdENSEMBL *Map Ensembl gene accession numbers with Entrez Gene identifiers*

Description

org.Sc.sgdENSEMBL is an R object that contains mappings between Entrez Gene identifiers and Ensembl gene accession numbers.

Details

This object is a simple mapping of Entrez Gene identifiers <http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=gene> to Ensembl gene Accession Numbers.

Mappings were based on data provided by ensembl: <http://www.ensembl.org/biomart/martview/>

Examples

```
x <- org.Sc.sgdENSEMBL
# Get the entrez gene IDs that are mapped to an Ensembl ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the Ensembl gene IDs for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
#For the reverse map ENSEMBL2ORF:
# Convert to a list
xx <- as.list(org.Sc.sgdENSEMBL2ORF)
if(length(xx) > 0){
  # Gets the entrez gene IDs for the first five Ensembl IDs
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdENTREZID *Map Systematic ORF identifiers with Entrez Gene identifiers*

Description

org.Sc.sgdENTREZID is an R object that contains mappings between Systematic ORF accession numbers and NCBI Entrez Gene identifiers.

Details

This object is a simple mapping of Entrez Gene identifiers <http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=gene> to systematic ORF locus Accession Numbers.

Mappings were based on data provided by: Entrez Gene (<ftp://ftp.ncbi.nlm.nih.gov/gene/DATA>) on 2009-Apr15

Examples

```
x <- org.Sc.sgdENTREZID
# Get the ORF IDs that are mapped to an Entrez Gene ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the Entrez gene IDs for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdENZYME *Map between ORF IDs and Enzyme Commission (EC) Numbers*

Description

org.Sc.sgdENZYME is an R object that provides mappings between ORF identifiers and EC numbers.

Details

Each ORF identifier maps to a named vector containing the EC number that corresponds to the enzyme produced by that gene. The name corresponds to the ORF identifier. If this information is unknown, the vector will contain an NA.

Enzyme Commission numbers are assigned by the Nomenclature Committee of the International Union of Biochemistry and Molecular Biology <http://www.chem.qmw.ac.uk/iubmb/enzyme/> to allow enzymes to be identified.

An Enzyme Commission number is of the format EC x.y.z.w, where x, y, z, and w are numeric numbers. In org.Sc.sgdENZYME2ORF, EC is dropped from the Enzyme Commission numbers.

Enzyme Commission numbers have corresponding names that describe the functions of enzymes in such a way that EC x is a more general description than EC x.y that in turn is a more general description than EC x.y.z. The top level EC numbers and names are listed below:

EC 1 oxidoreductases

EC 2 transferases

EC 3 hydrolases

EC 4 lyases

EC 5 isomerases

EC 6 ligases

The EC name for a given EC number can be viewed at <http://www.chem.qmul.ac.uk/iupac/jcbrn/index.html#6>

Mappings between ORF identifiers and enzyme identifiers were obtained using files provided by: KEGG GENOME (<ftp://ftp.genome.jp/pub/kegg/genomes>) on 2009-Mar10

For the reverse map, each EC number maps to a named vector containing the ORF identifier that corresponds to the gene that produces that enzyme. The name of the vector corresponds to the EC number.

References

<ftp://ftp.genome.ad.jp/pub/kegg/pathways>

Examples

```
x <- org.Sc.sgdENZYME
# Get the ORF identifiers that are mapped to an EC number
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the ENZYME id for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
# For the reverse map:
# Convert to a list
xx <- as.list(org.Sc.sgdENZYME2ORF)
if(length(xx) > 0){
  # Gets the ORF identifiers for the first five enzyme
  #commission numbers
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdGENENAME *Map between ORF IDs and Genes*

Description

org.Sc.sgdGENENAME is an R object that maps ORF identifiers to the corresponding gene name.

Details

Each ORF identifier maps to a named vector containing the gene name. The vector name corresponds to the ORF identifier. If the gene name is unknown, the vector will contain an NA.

Gene names currently include both the official (validated by a nomenclature committee) and preferred names (interim selected for display) for genes. Efforts are being made to differentiate the two by adding a name to the vector.

Mappings were based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

Examples

```
x <- org.Sc.sgdGENENAME
# Get the gene names that are mapped to an ORF identifier
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the GENE NAME for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdGO2ALLORFS

*Map Between Gene Ontology (GO) Identifiers and all ORF Identifiers
in the subtree*

Description

org.Sc.sgdGO2ALLORFS is an R object that provides mappings between a given GO identifier and all ORF identifiers annotated at that GO term or one of its children in the GO ontology.

Details

GO consists of three ontologies—molecular function (MF), biological process (BP), and cellular component (CC). All ontologies are structured as directed acyclic graphs (DAGs). Each node in each DAG (tree) is a GO term (id) associated with a named vector of manufacturer identifiers. The name associated with each ORF id corresponds to the evidence code for that GO identifier. This object org.Sc.sgdGO2ALLORFS maps between a given GO identifier and all ORF identifiers annotated at that GO term or one of its children in the GO ontology.

The evidence code indicates what kind of evidence supports the association between the GO and Entrez Gene identifiers. Evidence codes currently in use include:

- IMP - inferred from mutant phenotype
- IGI - inferred from genetic interaction
- IPI - inferred from physical interaction
- ISS - inferred from sequence similarity
- IDA - inferred from direct assay
- IEP - inferred from expression pattern

IEA - inferred from electronic annotation

TAS - traceable author statement

NAS - non-traceable author statement

ND - no biological data available

IC - inferred by curator

A GO identifier may be mapped to the same ORF identifier more than once but the evidence code can be different. Mappings between Gene Ontology identifiers and Gene Ontology terms and other information are available in a separate data package named GO.

Mappings were based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02 and Gene Ontology (<ftp://ftp.geneontology.org/pub/go/godatabase/archive/latest>) on 200903

References

<ftp://ftp.ncbi.nlm.nih.gov/gene/DATA/>

Examples

```
# Convert to a list
xx <- as.list(org.Sc.sgdGO2ALLORFS)
if(length(xx) > 0){
  # Gets the ORF identifiers for the top 2nd and 3rd GO identifiers
  goids <- xx[2:3]
  # Gets all the ORF identifiers for the first element of goids
  goids[[1]]
  # Evidence code for the mappings
  names(goids[[1]])
}
```

org.Sc.sgdGO

Map between ORF IDs and Gene Ontology (GO)

Description

org.Sc.sgdGO is an R object that provides mappings between ORF identifiers and the GO identifiers that they are directly associated with. This mapping and its reverse mapping do NOT associate the child terms from the GO ontology with the gene. Only the directly evidenced terms are represented here.

Details

Each ORF identifier is mapped to a list of lists. The names on the outer list are GO identifiers. Each inner list consists of three named elements: GOID, Ontology, and Evidence.

The GOID element matches the GO identifier named in the outer list and is included for convenience when processing the data using 'lapply'.

The Ontology element indicates which of the three Gene Ontology categories this identifier belongs to. The categories are biological process (BP), cellular component (CC), and molecular function (MF).

The Evidence element contains a code indicating what kind of evidence supports the association of the GO identifier to the Entrez Gene id. The evidence codes in use include:

IMP: inferred from mutant phenotype
 IGI: inferred from genetic interaction
 IPI: inferred from physical interaction
 ISS: inferred from sequence similarity
 IDA: inferred from direct assay
 IEP: inferred from expression pattern
 IEA: inferred from electronic annotation
 TAS: traceable author statement
 NAS: non-traceable author statement
 ND: no biological data available
 IC: inferred by curator

Mappings between ORF identifiers and GO information were obtained through their mappings to ORF identifiers. NAs are assigned to ORF identifiers that can not be mapped to any Gene Ontology information. Mappings between Gene Ontology identifiers and Gene Ontology terms and other information are available in a separate data package named GO.

Mappings were based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

For the reverse map org.Sc.sgdGO2ORF, each GO term maps to a named vector of ORF identifiers. A GO identifier may be mapped to the same ORF identifier more than once but the evidence code can be different. Mappings between Gene Ontology identifiers and Gene Ontology terms and other information are available in a separate data package named GO.

References

<ftp://ftp.ncbi.nlm.nih.gov/gene/DATA/>

See Also

[org.Sc.sgdGO2ALLORFS.](#)

Examples

```
x <- org.Sc.sgdGO
# Get the ORF identifiers that are mapped to a GO ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Try the first one
  got <- xx[[1]]
  got[[1]][["GOID"]]
  got[[1]][["Ontology"]]
  got[[1]][["Evidence"]]
}
# For the reverse map:
# Convert to a list
xx <- as.list(org.Sc.sgdGO2ORF)
if(length(xx) > 0){
  # Gets the ORF ids for the top 2nd and 3rd GO identifiers
  goids <- xx[2:3]
```

```

# Gets the ORF ids for the first element of goids
goids[[1]]
# Evidence code for the mappings
names(goids[[1]])
}

```

org.Sc.sgdINTERPRO *Map Yeast Systematic Names to InterPro IDs*

Description

org.Sc.sgdINTERPRO is an R object that provides mappings between yeast ORF identifiers and the associated InterPro identifiers.

Details

Each yeast ORF identifier maps to a vector of InterPro identifiers.

Mappings were based on data provided by:

Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

References

InterPro website: <http://www.ebi.ac.uk/interpro/>

Examples

```

# Convert to a list
xxx <- as.list(org.Sc.sgdINTERPRO)
# randomly display 10 probes
sample(xxx, 10)

```

org.Sc.sgdMAPCOUNTS

Number of mapped keys for the maps in package org.Sc.sgd.db

Description

org.Sc.sgdMAPCOUNTS provides the "map count" (i.e. the count of mapped keys) for each map in package org.Sc.sgd.db.

Details

This "map count" information is precalculated and stored in the package annotation DB. This allows some quality control and is used by the [checkMAPCOUNTS](#) function defined in AnnotationDbi to compare and validate different methods (like `count.mappedkeys(x)` or `sum(!is.na(as.list(x)))`) for getting the "map count" of a given map.

See Also

[mappedkeys](#), [count.mappedkeys](#), [checkMAPCOUNTS](#)

Examples

```

org.Sc.sgdMAPCOUNTS
mapnames <- names(org.Sc.sgdMAPCOUNTS)
org.Sc.sgdMAPCOUNTS[mapnames[1]]
x <- get(mapnames[1])
sum(!is.na(as.list(x)))
count.mappedkeys(x) # much faster!

## Check the "map count" of all the maps in package org.Sc.sgd.db
checkMAPCOUNTS("org.Sc.sgd.db")

```

org.Sc.sgdORGANISM *The Organism for org.Sc.sgd*

Description

org.Sc.sgdORGANISM is an R object that contains a single item: a character string that names the organism for which org.Sc.sgd was built.

Details

Although the package name is suggestive of the organism for which it was built, org.Sc.sgdORGANISM provides a simple way to programmatically extract the organism name.

Examples

```
org.Sc.sgdORGANISM
```

org.Sc.sgdPATH *Mappings between ORF identifiers and KEGG pathway identifiers*

Description

KEGG (Kyoto Encyclopedia of Genes and Genomes) maintains pathway data for various organisms. org.Sc.sgdPATH maps ORF identifiers to the identifiers used by KEGG for pathways. The reverse map org.Sc.sgdPATH2ORF maps back from KEGG pathway IDs to the ORF identifiers.

Details

Each KEGG pathway has a name and identifier. Pathway name for a given pathway identifier can be obtained using the KEGG data package that can either be built using AnnBuilder or downloaded from Bioconductor <http://www.bioconductor.org>.

Graphic presentations of pathways are searchable at url <http://www.genome.ad.jp/kegg/pathway.html> by using pathway identifiers as keys.

Mappings were based on data provided by: KEGG GENOME (<ftp://ftp.genome.jp/pub/kegg/genomes>) on 2009-Mar10

References

<http://www.genome.ad.jp/kegg/>

Examples

```
x <- org.Sc.sgdPATH
# Get the ORF identifiers that are mapped to a KEGG pathway ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the PATH for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
# Convert the object to a list
xx <- as.list(org.Sc.sgdPATH2ORF)
# Remove pathway identifiers that do not map to any ORF id
xx <- xx[!is.na(xx)]
if(length(xx) > 0){
  # The ORF identifiers for the first two elements of XX
  xx[1:2]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdPFAM

Map Entrez Gene IDs to Pfam IDs

Description

org.Sc.sgdPFAM is an R object that provides mappings between an entrez gene identifier and the associated Pfam identifiers.

Details

Each entrez gene identifier maps to a named vector of Pfam identifiers. The name for each Pfam identifier is the IPI accession number where this Pfam identifier is found.

If the Pfam is a named NA, it means that the associated Entrez Gene id of this entrez gene identifier is found in an IPI entry of the IPI database, but there is no Pfam identifier in the entry.

If the Pfam is a non-named NA, it means that the associated Entrez Gene id of this entrez gene identifier is not found in any IPI entry of the IPI database.

Mappings were based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

References

Kersey P. J., Duarte J., Williams A., Karavidopoulou Y., Birney E., Apweiler R. The International Protein Index: An integrated database for proteomics experiments. Proteomics 4(7): 1985-1988 (2004) <http://www.ebi.ac.uk/IPI/IPIhelp.html>

Examples

```
x <- org.Sc.sgdPFAM
# Get the entrez gene identifiers that are mapped to any Pfam ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
# randomly display 10 genes
sample(xx, 10)
```

org.Sc.sgdPMID *Map between ORF Identifiers and PubMed Identifiers*

Description

org.Sc.sgdPMID is an R object that provides mappings between ORF identifiers and PubMed identifiers.

Details

Each ORF identifier is mapped to a named vector of PubMed identifiers. The name associated with each vector corresponds to the ORF identifier. The length of the vector may be one or greater, depending on how many PubMed identifiers a given ORF identifier is mapped to. An NA is reported for any ORF identifier that cannot be mapped to a PubMed identifier.

Titles, abstracts, and possibly full texts of articles can be obtained from PubMed by providing a valid PubMed identifier. The pubmed function of annotate can also be used for the same purpose.

Mappings were based on data provided by: Yeast Genome (ftp://genome-ftp.stanford.edu/pub/yeast/data_download) on 2009-May02

References

<http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=PubMed>

Examples

```
x <- org.Sc.sgdPMID
# Get the ORF identifiers that are mapped to any PubMed ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0){
  # The ORF identifiers for the first two elements of XX
  xx[1:2]
  # Get the first one
  xx[[1]]
  if(interactive() && !is.null(xx[[1]]) && !is.na(xx[[1]]))
    && require(annotate)){
    # Gets article information as XML files
    xmls <- pubmed(xx[[1]], disp = "data")
    # Views article information using a browser
    pubmed(xx[[1]], disp = "browser")
  }
}
```



```

# Convert the object to a list
xx <- as.list(org.Sc.sgdPMID2ORF)
if(length(xx) > 0){
  # The ORF identifiers for the first two elements of XX
  xx[1:2]
  # Get the first one
  xx[[1]]
  if(interactive() && require(annotate)){
    # Gets article information as XML files for a PubMed id
    xmls <- pubmed(names(xx)[1], disp = "data")
    # Views article information using a browser
    pubmed(names(xx)[1], disp = "browser")
  }
}

```

org.Sc.sgdREFSEQ *Map between systematic ORF identifiers and RefSeq Identifiers*

Description

org.Sc.sgdREFSEQ is an R object that provides mappings between systematic ORF identifiers and RefSeq identifiers.

Details

Each systematic ORF identifier is mapped to a named vector of RefSeq identifiers. The name represents the systematic ORF identifier and the vector contains all RefSeq identifiers that can be mapped to that entrez gene identifier. The length of the vector may be one or greater, depending on how many RefSeq identifiers a given systematic ORF identifier can be mapped to. An NA is reported for any entrez gene identifier that cannot be mapped to a RefSeq identifier at this time.

RefSeq identifiers differ in format according to the type of record the identifiers are for as shown below:

NG_XXXXX: RefSeq accessions for genomic region (nucleotide) records

NM_XXXXX: RefSeq accessions for mRNA records

NC_XXXXX: RefSeq accessions for chromosome records

NP_XXXXX: RefSeq accessions for protein records

XR_XXXXX: RefSeq accessions for model RNAs that are not associated with protein products

XM_XXXXX: RefSeq accessions for model mRNA records

XP_XXXXX: RefSeq accessions for model protein records

Where XXXXX is a sequence of integers.

NCBI <http://www.ncbi.nlm.nih.gov/RefSeq/> allows users to query the RefSeq database using RefSeq identifiers.

Mappings were based on data provided by: Entrez Gene (<ftp://ftp.ncbi.nlm.nih.gov/gene/DATA>) on 2009-Apr15

References

<http://www.ncbi.nlm.nih.gov> <http://www.ncbi.nlm.nih.gov/RefSeq/>

Examples

```
x <- org.Sc.sgdREFSEQ
# Get the systematic ORF identifiers that are mapped to any RefSeq ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the REFSEQ for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdREJECTORF

Rejected Yeast Genes (ORF)

Description

This is based upon Real and rejected yeast ORFs from Kellis et al. (2003) to list the rejected genes by this criteria.

Details

A character vector which contains yeast ORFs which are rejected in the reading frame conservation (RFC) test in Kellis et al. (2003).

References

Manolis Kellis, Nick Patterson, Matthew Endrizzi, Bruce Birren and Eric S. Lander, Sequencing and comparison of yeast species to identify genes and regulatory elements. Nature 423, 241-254 (15 May 2003)

Examples

```
head(org.Sc.sgdREJECTORF)
```

org.Sc.sgdSGD

Map Systematic ORF identifiers with SGD accession numbers

Description

org.Sc.sgdSGD is an R object that contains mappings between Systematic ORF accessions and SGD accession numbers.

Details

This object is a simple mapping of Systematic ORF Accession Numbers to SGD identifiers.

Examples

```
x <- org.Sc.sgdSGD
# Get the Systematic ORF Accessions that are mapped to a SGD ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the SGD gene IDs for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

org.Sc.sgdSMART *Map Yeast ORF Identifiers to SMART IDs*

Description

org.Sc.sgdSMART is an R object that provides mappings between yeast ORF Identifiers and the associated SMART identifiers.

Details

Each yeast systematic name maps to a vector of SMART identifiers.

Mappings were based on data provided by:

Saccharomyces Genome Database

Package built on Thu Mar 15 18:04:19 2007

References

SMART website: <http://smart.embl-heidelberg.de/>

Examples

```
# Convert to a list
xxx <- as.list(org.Sc.sgdSMART)
# randomly display 10 probes
sample(xxx, 10)
```

org.Sc.sgdUNIPROT *Map Uniprot accession numbers with Systematic ORF identifiers*

Description

org.Sc.sgdUNIPROT is an R object that contains mappings between Systematic ORF identifiers and Uniprot accession numbers.

Details

This object is a simple mapping of Systematic ORF identifiers <http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=gene> to Uniprot Accession Numbers.

Mappings were based on data provided by: Entrez Gene (<ftp://ftp.ncbi.nlm.nih.gov/gene/DATA>) on 2009-Apr15

Examples

```
x <- org.Sc.sgdUNIPROT
# Get the Systematic ORF IDs that are mapped to a Uniprot ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the Uniprot gene IDs for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

Index

*Topic **datasets**

- org.Sc.sgd.db, [2](#)
- org.Sc.sgd_dbconn, [5](#)
- org.Sc.sgdALIAS, [1](#)
- org.Sc.sgdCHR, [3](#)
- org.Sc.sgdCHRLNGTHS, [2](#)
- org.Sc.sgdCHRLOC, [3](#)
- org.Sc.sgdCOMMON2ORF, [4](#)
- org.Sc.sgdDESCRIPTION, [6](#)
- org.Sc.sgdENSEMBL, [7](#)
- org.Sc.sgdENTREZID, [7](#)
- org.Sc.sgdENZYME, [8](#)
- org.Sc.sgdGENENAME, [9](#)
- org.Sc.sgdGO, [11](#)
- org.Sc.sgdGO2ALLORFS, [10](#)
- org.Sc.sgdINTERPRO, [12](#)
- org.Sc.sgdMAPCOUNTS, [13](#)
- org.Sc.sgdORGANISM, [14](#)
- org.Sc.sgdPATH, [14](#)
- org.Sc.sgdPFAM, [15](#)
- org.Sc.sgdPMID, [16](#)
- org.Sc.sgdREFSEQ, [17](#)
- org.Sc.sgdREJECTORF, [18](#)
- org.Sc.sgdSGD, [18](#)
- org.Sc.sgdSMART, [19](#)
- org.Sc.sgdUNIPROT, [19](#)

*Topic **utilities**

- org.Sc.sgd_dbconn, [5](#)

AnnDbObj, [5](#)

cat, [5](#)

checkMAPCOUNTS, [13](#)

count.mappedkeys, [13](#)

dbconn, [5](#)

dbConnect, [5](#)

dbDisconnect, [5](#)

dbfile, [5](#)

dbGetQuery, [5](#)

dbInfo, [5](#)

dbschema, [5](#)

mappedkeys, [13](#)

- org.Sc.sgd (*org.Sc.sgd.db*), [2](#)
- org.Sc.sgd.db, [2](#)
- org.Sc.sgd_dbconn, [5](#)
- org.Sc.sgd_dbfile
 - (*org.Sc.sgd_dbconn*), [5](#)
- org.Sc.sgd_dbInfo
 - (*org.Sc.sgd_dbconn*), [5](#)
- org.Sc.sgd_dbschema
 - (*org.Sc.sgd_dbconn*), [5](#)
- org.Sc.sgdALIAS, [1](#)
- org.Sc.sgdALIAS2ORF
 - (*org.Sc.sgdALIAS*), [1](#)
- org.Sc.sgdCHR, [3](#)
- org.Sc.sgdCHRLNGTHS, [2](#)
- org.Sc.sgdCHRLOC, [3](#)
- org.Sc.sgdCHRLOCEND
 - (*org.Sc.sgdCHRLOC*), [3](#)
- org.Sc.sgdCOMMON2ORF, [4](#)
- org.Sc.sgdDESCRIPTION, [6](#)
- org.Sc.sgdENSEMBL, [7](#)
- org.Sc.sgdENSEMBL2ORF
 - (*org.Sc.sgdENSEMBL*), [7](#)
- org.Sc.sgdENTREZID, [7](#)
- org.Sc.sgdENZYME, [8](#)
- org.Sc.sgdENZYME2ORF
 - (*org.Sc.sgdENZYME*), [8](#)
- org.Sc.sgdGENENAME, [9](#)
- org.Sc.sgdGO, [11](#)
- org.Sc.sgdGO2ALLORFS, [10](#), [12](#)
- org.Sc.sgdGO2ORF (*org.Sc.sgdGO*),
[11](#)
- org.Sc.sgdINTERPRO, [12](#)
- org.Sc.sgdMAPCOUNTS, [13](#)
- org.Sc.sgdORGANISM, [14](#)
- org.Sc.sgdPATH, [14](#)
- org.Sc.sgdPATH2ORF
 - (*org.Sc.sgdPATH*), [14](#)
- org.Sc.sgdPFAM, [15](#)
- org.Sc.sgdPMID, [16](#)
- org.Sc.sgdPMID2ORF
 - (*org.Sc.sgdPMID*), [16](#)
- org.Sc.sgdREFSEQ, [17](#)
- org.Sc.sgdREJECTORF, [18](#)

org.Sc.sgdSGD, [18](#)
org.Sc.sgdSMART, [19](#)
org.Sc.sgdUNIPROT, [19](#)