

# harbChIP

October 25, 2011

---

allhex

*utility function: get all hexamers in upstream sequence for an ORF*

---

## Description

utility function: get all hexamers in upstream sequence for an ORF

## Usage

```
allhex(orf, usobj)
```

## Arguments

orf	character string, ORF name
usobj	upstreamSeqs object

## Details

computes Biostrings Views

## Value

computes Biostrings Views

## Author(s)

Vince Carey <stvjc@channing.harvard.edu>

## Examples

```
data(sceUpstr)
allhex("YAL001C", sceUpstr)
```

---

buildUpstreamSeqs2 *workflow component - build an upstreamSeqs instance from a FASTA read*

---

### Description

workflow component – build an upstreamSeqs instance from a FASTA read

### Usage

```
buildUpstreamSeqs2(fastaRead, organism="sce", provenance="harmen")
```

### Arguments

fastaRead	results of a readFASTA from Biostrings
organism	string naming organism
provenance	string or structure describing provenance

### Details

generates an instance of upstreamSeqs

### Value

generates an instance of upstreamSeqs

### Author(s)

Vince Carey <stvjc@channing.harvard.edu>

### Examples

```
# x = readFASTA(...)
# y = buildUpstreamSeqs2(x)
```

---

chkMotif4TF *analyze relationship between motif frequency and binding intensity for*

---

### Description

analyze relationship between motif frequency and binding intensity for selected motif and TF

### Usage

```
chkMotif4TF(motif, TF, chset, upstr, bthresh=2, countthresh=0)
```

**Arguments**

motif	character string in alphabet known to Biostrings
TF	name of a TF (sample name in the ChIP-chip data structure chset)
chset	an ExpressionSet instance harboring ChIP-chip data
upstr	an instance of upstreamSeqs
bthresh	threshold for binding intensity results to declare TF 'bound' to the upstream region
countthresh	threshold for motif count to be considered 'present' in upstream region

**Details**

Uses `countPattern` to perform motif count.

**Value**

a list with elements `call`, `table`, and `test`, the latter providing the result of `fisher.test`

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**Examples**

```
# slow
## Not run:
data(harbChIP)
data(sceUpstr)
chkMotif4TF("CGGCCG", "RDS1", harbChIP, sceUpstr)

## End(Not run)
```

---

harbChIP

*Experimental Data Package: harbChIP*

---

**Description**

binding ratios and intergenic region data from a ChIP-chip experiment in yeast

**Usage**

```
data(harbChIP)
```

**Format**

The format is: An `ExpressionSetObject` with covariates:

- `txFac`: transcription factor symbol from Harbison website CSV file columnnames

**Note**

derived from web site [jura.wi.mit.edu/young\\_public/regulatory\\_code/GWLD.html](http://jura.wi.mit.edu/young_public/regulatory_code/GWLD.html), binding ratios

**Examples**

```

data(harbChIP)
harbChIP
experimentData(harbChIP)
exprs(harbChIP)[1:6,1:7]
dim(exprs(harbChIP))
pData(featureData(harbChIP))[1:6,]

```

---

sceUpstr

*Biostrings representations of S. cerevisiae upstream regions*


---

**Description**

Biostrings representations of *S. cerevisiae* upstream regions

**Usage**

```
data(sceUpstr)
```

**Details**

environment-based S4 object with DNAstring elements

**Value**

environment-based S4 object with DNAstring elements

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**Examples**

```

data(sceUpstr)
sceUpstr
getUpstream("YAL001C", sceUpstr)

```

---

upstreamSeqs-class *Class "upstreamSeqs"*


---

**Description**

Container for a collection of upstream sequences

**Objects from the Class**

Objects can be created by calls of the form `new("upstreamSeqs", ...)`. Environments are used to store collections of DNAstrings.

### Slots

**seqs:** Object of class "environment" ~~  
**chrom:** Object of class "environment" ~~  
**revComp:** Object of class "environment" ~~  
**type:** Object of class "environment" ~~  
**organism:** Object of class "character" ~~  
**provenance:** Object of class "ANY" ~~

### Methods

**Nmers** signature(n = "numeric", orf = "character", usobj = "upstreamSeqs"): obtain all subsequences of length n as view elements of a DNA string  
**keys** signature(x = "upstreamSeqs"): ...  
**organism** signature(x = "upstreamSeqs"): ...  
**seqs** signature(x = "upstreamSeqs"): ...  
**show** signature(object = "upstreamSeqs"): ...

### Author(s)

Vince Carey <stvjc@channing.harvard.edu>

### Examples

```
showClass("upstreamSeqs")
data(sceUpstr)
sceUpstr
keys(sceUpstr)[1:5]
```

# Index

## \*Topic classes

upstreamSeqs-class, 4

## \*Topic datasets

harbChIP, 3

## \*Topic models

allhex, 1

buildUpstreamSeqs2, 2

chkMotif4TF, 2

sceUpstr, 4

allhex, 1

buildUpstreamSeqs2, 2

chkAllUS (*chkMotif4TF*), 2

chkMotif4TF, 2

countPattern, 3

fisher.test, 3

getUpstream (*upstreamSeqs-class*),  
4

harbChIP, 3

keys (*upstreamSeqs-class*), 4

keys, upstreamSeqs-method  
(*upstreamSeqs-class*), 4

Nmers (*upstreamSeqs-class*), 4

Nmers, numeric, character, upstreamSeqs-method  
(*upstreamSeqs-class*), 4

organism (*upstreamSeqs-class*), 4

organism, upstreamSeqs-method  
(*upstreamSeqs-class*), 4

sceUpstr, 4

seqs (*upstreamSeqs-class*), 4

seqs, upstreamSeqs-method  
(*upstreamSeqs-class*), 4

show, upstreamSeqs-method  
(*upstreamSeqs-class*), 4

upstreamSeqs-class, 4