

Package ‘GENE.E’

October 9, 2015

Type Package

Title Interact with GENE-E from R

Version 1.8.0

Date 2013-03-01

Author Joshua Gould

Maintainer Joshua Gould <jgould@broadinstitute.org>

Depends R (>= 2.7.0), rhdf5 (>= 2.8.0), RCurl (>= 1.6-6)

Imports rhdf5, RCurl

Suggests RUnit, BiocGenerics, knitr, golubEsets (>= 1.0)

SystemRequirements GENE-E software.

Description Interactive exploration of matrices in GENE-E.

License GPL-2

URL <http://www.broadinstitute.org/cancer/software/GENE-E>

VignetteBuilder knitr

biocViews ThirdPartyClient

NeedsCompilation no

R topics documented:

from.genee	2
to.genee	2

Index	4
--------------	----------

from.genee

from.genee

Description

R interface to get selection from GENE-E.

Usage

```
from.genee(url='http://localhost:9998')
```

Arguments

url GENE-E URL.

Details

Gets selection from GENE-E. If no rows or columns are selected, the full dataset is returned.

Value

List containing row.annotations, column.annotations, and matrix.

Examples

```
# not run
# z = from.genee();
```

to.genee

to.genee

Description

R interface to view a matrix in GENE-E

Usage

```
to.genee(mdat, row.annotations=NULL, column.annotations=NULL, show.rownames=T, show.colnames=T, row.
```

Arguments

<code>mdat</code>	a matrix.
<code>row.annotations</code>	a data frame containing row annotations.
<code>column.annotations</code>	a data frame containing column annotations.
<code>show.rownames</code>	Whether to show the row names of the matrix in GENE-E.
<code>show.colnames</code>	Whether to show the column names of the matrix in GENE-E.
<code>row.hclust</code>	An object of class <code>hclust</code> to show in GENE-E. If provided, the matrix and annotations will be reordered to reflect the tree produced by the clustering process.
<code>column.hclust</code>	An object of class <code>hclust</code> to show in GENE-E. If provided, the matrix and annotations will be reordered to reflect the tree produced by the clustering process.
<code>url</code>	GENE-E URL.

Details

R interface to GENE-E.

Examples

```
# not run
# z = matrix(rnorm(30),nrow=5,ncol=6);
# row.names(z) <- LETTERS[1:NROW(z)];
# colnames(z) <- LETTERS[1:NCOL(z)];
# row.annotations <- data.frame(y=1:5, char = I(letters[1:5]))
# L3 <- LETTERS[1:3]
# column.annotations <- data.frame(y=1:6, char = I(letters[1:6]), fac=sample(L3, 6, replace=TRUE))
# to.genee(z, row.annotations, column.annotations, column.hclust=hclust(dist(t(z))));
```

Index

from.genee, [2](#)

to.genee, [2](#)