

Package ‘gscreend’

October 17, 2020

Type Package

Title Analysis of pooled genetic screens

Version 1.2.0

Description Package for the analysis of pooled genetic screens (e.g. CRISPR-KO). The analysis of such screens is based on the comparison of gRNA abundances before and after a cell proliferation phase. The gscreend packages takes gRNA counts as input and allows detection of genes whose knockout decreases or increases cell proliferation.

License GPL-3

Encoding UTF-8

LazyData false

Depends R (>= 3.6)

Imports SummarizedExperiment, nloptr, fGarch, methods, BiocParallel, graphics

Suggests knitr, testthat

VignetteBuilder knitr

RoxygenNote 6.1.1

biocViews Software, StatisticalMethod, PooledScreens, CRISPR

URL <https://github.com/imkeller/gscreend>

BugReports <https://github.com/imkeller/gscreend/issues>

git_url <https://git.bioconductor.org/packages/gscreend>

git_branch RELEASE_3_11

git_last_commit 63ed3c3

git_last_commit_date 2020-04-27

Date/Publication 2020-10-16

Author Katharina Imkeller [cre, aut],
Wolfgang Huber [aut]

Maintainer Katharina Imkeller <k.imkeller@dkfz.de>

R topics documented:

createPoolScreenExp	2
GeneData	3
GeneData,PoolScreenExp-method	3
plotModelParameters	4
plotReplicateCorrelation	5
PoolScreenExp-class	5
ResultsTable	6
RunGscreen	6
sgRNAData	7
sgRNAData,PoolScreenExp-method	8

Index	9
--------------	----------

createPoolScreenExp *Create PoolScreenExp Experiment*

Description

Create PoolScreenExp Experiment

Usage

```
createPoolScreenExp(data)
```

Arguments

data Input data object containing gRNA level data (SummarizedExperiment)

Value

object PoolScreenExp object

Examples

```
raw_counts <- read.table(
  system.file('extdata', 'simulated_counts.txt',
    package = 'gscreen'),
  header=TRUE)

counts_matrix <- cbind(raw_counts$library0, raw_counts$R0_0, raw_counts$R1_0)

rowData <- data.frame(sgRNA_id = raw_counts$sgrna_id,
  gene = raw_counts$Gene)

colData <- data.frame(samplename = c('library', 'R1', 'R2'),
  timepoint = c('T0', 'T1', 'T1'))

library(SummarizedExperiment)
se <- SummarizedExperiment(assays=list(counts=counts_matrix),
  rowData=rowData, colData=colData)

# create a PoolScreenExp experiment
```

```
pse <- createPoolScreenExp(se)
```

GeneData

GeneData: set and retrieve GeneData of PoolScreenExp

Description

GeneData: set and retrieve GeneData of PoolScreenExp

Usage

```
GeneData(x)
```

Arguments

x PoolScreenExp object

Value

Gene slot of the object

Examples

```
# import a PoolScreenExp object that has been generated using
# RunGscreeend()
pse_an <- readRDS(
  system.file('extdata', 'gscreeend_analysed_experiment.RData',
  package = 'gscreeend'))

GeneData(pse_an)
```

GeneData, PoolScreenExp-method

Accessor function for the Gene slot of the PoolScreenExp class

Description

Accessor function for the Gene slot of the PoolScreenExp class

Usage

```
## S4 method for signature 'PoolScreenExp'
GeneData(x)
```

Arguments

x PoolScreenExp object

Value

Gene slot of the object

Examples

```
# import a PoolScreenExp object that has been generated using
# RunGscreen()
pse_an <- readRDS(
  system.file('extdata', 'gscreen_analysed_experiment.RData',
    package = 'gscreen'))

GeneData(pse_an)
```

plotModelParameters *Plot model parameters from the fitting*

Description

Plot model parameters from the fitting

Usage

```
plotModelParameters(object)
```

Arguments

object PoolScreenExp object

Value

plot

Examples

```
# import a PoolScreenExp object that has been generated using
# RunGscreen()
pse_an <- readRDS(
  system.file('extdata', 'gscreen_analysed_experiment.RData',
    package = 'gscreen'))
plotModelParameters(pse_an)
```

```
plotReplicateCorrelation
      Plot replicate correlation
```

Description

Plot replicate correlation

Usage

```
plotReplicateCorrelation(object, rep1 = "R1", rep2 = "R2")
```

Arguments

object	PoolScreenExp object
rep1	Name of replicate 1
rep2	Name of replicate 2

Value

replicate_plot

Examples

```
# import a PoolScreenExp object that has been generated using RunGscreen()
pse_an <- readRDS(
  system.file('extdata', 'gscreend_analysed_experiment.RData',
  package = 'gscreend'))
plotReplicateCorrelation(pse_an, rep1 = 'R1', rep2 = 'R2')
```

```
PoolScreenExp-class   Class to store pooled CRISPR screening experiment
```

Description

The poolScreenExp class is an S4 class used to store sgRNA and gene related data as well as parameters necessary for statistical model.

Slots

sgRNAData A SummarizedExperiment containing the data related to sgRNAs.
 FittingIntervals A vector defining the limits of the intervals used for fitting of null model.
 LFCModelParameters A vector of parameters estimated when fitting the null model.
 GeneData SummarizedExperiment containing the data related to genes.
 FittingOptions A named list with options for fitting: IntervalFraction - fraction of sgRNAs used in every fitting interval (default 0.1), alphaCutoff - alpha cutoff for alpha RRA algorithm (default: 0.05).

ResultsTable	<i>Extract a results table</i>
--------------	--------------------------------

Description

Extract a results table

Usage

```
ResultsTable(object, direction = "negative")
```

Arguments

object	PoolScreenExp object
direction	Whether the table should contain information on positive or negative fold changes ['negative' 'positive']

Value

plot

Examples

```
# import a PoolScreenExp object that has been generated using
# RunGscorend()
pse_an <- readRDS(
  system.file('extdata', 'gscorend_analysed_experiment.RData',
  package = 'gscorend'))
ResultsTable(pse_an, direction = 'negative')
```

RunGscorend	<i>run gscorend</i>
-------------	---------------------

Description

run gscorend

Usage

```
RunGscorend(object, quant1 = 0.1, quant2 = 0.9, alphacutoff = 0.05)
```

Arguments

object	PoolScreenExp object
quant1	lower quantile for least quantile of squares regression (default: 0.1)
quant2	upper quantile for least quantile of squares regression (default: 0.9)
alphacutoff	alpha cutoff for alpha-RRA (default: 0.05)

Value

object

Examples

```
raw_counts <- read.table(
  system.file('extdata', 'simulated_counts.txt',
    package = 'gscreeend'),
  header=TRUE)

# Create the PoolScreenExp to be analyzed
counts_matrix <- cbind(raw_counts$library0, raw_counts$R0_0, raw_counts$R1_0)

rowData <- data.frame(sgRNA_id = raw_counts$sgrna_id,
  gene = raw_counts$Gene)

colData <- data.frame(samplename = c('library', 'R1', 'R2'),
  timepoint = c('T0', 'T1', 'T1'))

library(SummarizedExperiment)
se <- SummarizedExperiment(assays=list(counts=counts_matrix),
  rowData=rowData, colData=colData)

pse <- createPoolScreenExp(se)

# Run Analysis
pse_an <- RunGscreeend(pse)
```

sgRNAData

sgRNAData: set and retrieve sgRNAData of PoolScreenExp

Description

sgRNAData: set and retrieve sgRNAData of PoolScreenExp

Usage

```
sgRNAData(x)
```

Arguments

x PoolScreenExp object

Value

sgRNA slot of the object

Examples

```
# import a PoolScreenExp object that has been generated using
# RunGscreen()
pse_an <- readRDS(
  system.file('extdata', 'gscreen_analysed_experiment.RData',
    package = 'gscreen'))

sgRNAData(pse_an)
```

sgRNAData,PoolScreenExp-method

Accessor function for the sgRNA slot of the PoolScreenExp class

Description

Accessor function for the sgRNA slot of the PoolScreenExp class

Usage

```
## S4 method for signature 'PoolScreenExp'
sgRNAData(x)
```

Arguments

x PoolScreenExp object

Value

sgRNA slot of the object

Examples

```
# import a PoolScreenExp object that has been generated using
# RunGscreen()
pse_an <- readRDS(
  system.file('extdata', 'gscreen_analysed_experiment.RData',
    package = 'gscreen'))

sgRNAData(pse_an)
```

Index

`createPoolScreenExp`, [2](#)

`GeneData`, [3](#)

`GeneData`, `PoolScreenExp`-method, [3](#)

`plotModelParameters`, [4](#)

`plotReplicateCorrelation`, [5](#)

`PoolScreenExp`-class, [5](#)

`ResultsTable`, [6](#)

`RunGscreen`, [6](#)

`sgRNAData`, [7](#)

`sgRNAData`, `PoolScreenExp`-method, [8](#)