

# Package ‘debrowser’

October 14, 2021

**Type** Package

**Title** Interactive Differential Expression Analysis Browser

**Version** 1.20.1

**Date** 2020-12-07

**Author** Alper Kucukural <alper.kucukural@umassmed.edu>,  
Onur Yukselen <onur.yukselen@umassmed.edu>,  
Manuel Garber <manuel.garber@umassmed.edu>

**Maintainer** Alper Kucukural <alper.kucukural@umassmed.edu>

**Description** Bioinformatics platform containing interactive plots and tables for differential gene and region expression studies. Allows visualizing expression data much more deeply in an interactive and faster way. By changing the parameters, users can easily discover different parts of the data that like never have been done before. Manually creating and looking these plots takes time. With DEBrowser users can prepare plots without writing any code. Differential expression, PCA and clustering analysis are made on site and the results are shown in various plots such as scatter, bar, box, volcano, ma plots and Heatmaps.

**Depends** R (>= 3.5.0),

**License** GPL-3 + file LICENSE

**LazyData** true

**Imports** shiny, jsonlite, shinyjs, shinydashboard, shinyBS, gplots, DT, ggplot2, RColorBrewer, annotate, AnnotationDbi, DESeq2, DOSE, igraph, grDevices, graphics, stats, utils, GenomicRanges, IRanges, S4Vectors, SummarizedExperiment, stringi, reshape2, org.Hs.eg.db, org.Mm.eg.db, limma, edgeR, clusterProfiler, methods, sva, RCurl, enrichplot, colourpicker, plotly, heatmaply, Harman, pathview, apeglm, ashR

**RoxygenNote** 7.1.1

**Encoding** UTF-8

**Suggests** testthat, rmarkdown, knitr

**VignetteBuilder** knitr, rmarkdown

**URL** <https://github.com/UMMS-Biocore/debrowser>

**BugReports** <https://github.com/UMMS-Biocore/debrowser/issues/new>

**biocViews** Sequencing, ChIPSeq, RNASeq, DifferentialExpression,  
GeneExpression, Clustering, ImmunoOncology

**git\_url** <https://git.bioconductor.org/packages/debrowser>

**git\_branch** RELEASE\_3\_13

**git\_last\_commit** 3379462

**git\_last\_commit\_date** 2021-08-11

**Date/Publication** 2021-10-14

## R topics documented:

|  |    |
|--|----|
| actionButtonDE . . . . .                 | 6  |
| addDataCols . . . . .                    | 7  |
| addID . . . . .                          | 8  |
| all2all . . . . .                        | 8  |
| all2allControlsUI . . . . .              | 9  |
| applyFilters . . . . .                   | 9  |
| applyFiltersNew . . . . .                | 10 |
| applyFiltersToMergedComparison . . . . . | 10 |
| barMainPlotControlsUI . . . . .          | 11 |
| batchEffectUI . . . . .                  | 12 |
| batchMethod . . . . .                    | 12 |
| BoxMainPlotControlsUI . . . . .          | 13 |
| changeClusterOrder . . . . .             | 13 |
| checkCountData . . . . .                 | 14 |
| checkMetaData . . . . .                  | 15 |
| clusterData . . . . .                    | 15 |
| clustFunParamsUI . . . . .               | 16 |
| compareClust . . . . .                   | 16 |
| condSelectUI . . . . .                   | 17 |
| correctCombat . . . . .                  | 18 |
| correctHarman . . . . .                  | 18 |
| customColorsUI . . . . .                 | 19 |
| cutOffSelectionUI . . . . .              | 19 |
| dataLCFUI . . . . .                      | 20 |
| dataLoadUI . . . . .                     | 21 |
| debrowserall2all . . . . .               | 21 |
| debrowserbarmainplot . . . . .           | 22 |
| debrowserbatheffect . . . . .            | 23 |
| debrowserboxmainplot . . . . .           | 23 |
| debrowsercondselect . . . . .            | 24 |
| debrowserdataload . . . . .              | 25 |
| debrowserdeanalysis . . . . .            | 26 |
| debrowserdensityplot . . . . .           | 27 |

|  |    |
|--|----|
| debrowserheatmap . . . . .             | 27 |
| debrowserhistogram . . . . .           | 28 |
| debrowserIQRplot . . . . .             | 29 |
| debrowserlowcountfilter . . . . .      | 29 |
| debrowsermainplot . . . . .            | 30 |
| debrowserpcaplot . . . . .             | 31 |
| dendControlsUI . . . . .               | 31 |
| densityPlotControlsUI . . . . .        | 32 |
| deServer . . . . .                     | 33 |
| deUI . . . . .                         | 33 |
| distFunParamsUI . . . . .              | 34 |
| drawKEGG . . . . .                     | 34 |
| drawPCAExplained . . . . .             | 35 |
| fileTypes . . . . .                    | 36 |
| fileUploadBox . . . . .                | 36 |
| generateTestData . . . . .             | 37 |
| getAfterLoadMsg . . . . .              | 37 |
| getAll2AllPlotUI . . . . .             | 38 |
| getBarMainPlot . . . . .               | 39 |
| getBarMainPlotUI . . . . .             | 39 |
| getBoxMainPlot . . . . .               | 40 |
| getBoxMainPlotUI . . . . .             | 41 |
| getBSTableUI . . . . .                 | 41 |
| getColors . . . . .                    | 42 |
| getColorShapeSelection . . . . .       | 43 |
| getCompSelection . . . . .             | 43 |
| getConditionSelector . . . . .         | 44 |
| getConditionSelectorFromMeta . . . . . | 44 |
| getCondMsg . . . . .                   | 45 |
| getCutOffSelection . . . . .           | 46 |
| getDataAssesmentText . . . . .         | 46 |
| getDataForTables . . . . .             | 47 |
| getDataPreparationText . . . . .       | 48 |
| getDEAnalysisText . . . . .            | 48 |
| getDensityPlot . . . . .               | 49 |
| getDensityPlotUI . . . . .             | 49 |
| getDEResultsUI . . . . .               | 50 |
| getDomains . . . . .                   | 50 |
| getDown . . . . .                      | 51 |
| getDownloadSection . . . . .           | 51 |
| getEnrichDO . . . . .                  | 52 |
| getEnrichGO . . . . .                  | 53 |
| getEnrichKEGG . . . . .                | 54 |
| getEntrezIds . . . . .                 | 54 |
| getEntrezTable . . . . .               | 55 |
| getGeneList . . . . .                  | 56 |
| getGeneSetData . . . . .               | 57 |
| getGOLeftMenu . . . . .                | 57 |

|                                   |    |
|-----------------------------------|----|
| getGoPanel . . . . .              | 58 |
| getGOPlots . . . . .              | 58 |
| getGSEA . . . . .                 | 59 |
| getHeatmapUI . . . . .            | 60 |
| getHelpButton . . . . .           | 60 |
| getHideLegendOnOff . . . . .      | 61 |
| getHistogramUI . . . . .          | 61 |
| getIntroText . . . . .            | 62 |
| getIQRPlot . . . . .              | 62 |
| getIQRPlotUI . . . . .            | 63 |
| getJSLine . . . . .               | 63 |
| getKEGGModal . . . . .            | 64 |
| getLeftMenu . . . . .             | 64 |
| getLegendColors . . . . .         | 65 |
| getLegendRadio . . . . .          | 66 |
| getLegendSelect . . . . .         | 66 |
| getLevelOrder . . . . .           | 67 |
| getLoadingMsg . . . . .           | 67 |
| getLogo . . . . .                 | 68 |
| getMainPanel . . . . .            | 69 |
| getMainPlotsLeftMenu . . . . .    | 69 |
| getMainPlotUI . . . . .           | 70 |
| getMean . . . . .                 | 70 |
| getMergedComparison . . . . .     | 71 |
| getMetaSelector . . . . .         | 71 |
| getMethodDetails . . . . .        | 72 |
| getMostVariedList . . . . .       | 72 |
| getNormalizedMatrix . . . . .     | 73 |
| getOrganism . . . . .             | 74 |
| getOrganismBox . . . . .          | 74 |
| getOrganismPathway . . . . .      | 75 |
| getPCAcontolUpdatesJS . . . . .   | 75 |
| getPCAexplained . . . . .         | 76 |
| getPCAPlotUI . . . . .            | 77 |
| getPCselection . . . . .          | 77 |
| getPlotArea . . . . .             | 78 |
| getProgramTitle . . . . .         | 79 |
| getQAText . . . . .               | 79 |
| getQCLeftMenu . . . . .           | 80 |
| getQCPanel . . . . .              | 80 |
| getSampleDetails . . . . .        | 81 |
| getSampleNames . . . . .          | 82 |
| getSamples . . . . .              | 82 |
| getSearchData . . . . .           | 83 |
| getSelectedCols . . . . .         | 83 |
| getSelectedDatasetInput . . . . . | 84 |
| getSelectInputBox . . . . .       | 85 |
| getSelHeat . . . . .              | 85 |

|  |     |
|--|-----|
| getShapeColor . . . . .                  | 86  |
| getStartPlotsMsg . . . . .               | 87  |
| getStartupMsg . . . . .                  | 87  |
| getTableDetails . . . . .                | 88  |
| getTableModal . . . . .                  | 88  |
| getTableStyle . . . . .                  | 89  |
| getTabUpdateJS . . . . .                 | 90  |
| getTextOnOff . . . . .                   | 90  |
| getUp . . . . .                          | 91  |
| getUpDown . . . . .                      | 91  |
| getVariationData . . . . .               | 92  |
| get_conditions_given_selection . . . . . | 92  |
| heatmapControlsUI . . . . .              | 93  |
| heatmapJScore . . . . .                  | 94  |
| heatmapServer . . . . .                  | 94  |
| heatmapUI . . . . .                      | 95  |
| hideObj . . . . .                        | 96  |
| histogramControlsUI . . . . .            | 96  |
| installpack . . . . .                    | 97  |
| IQRPlotControlsUI . . . . .              | 97  |
| kmeansControlsUI . . . . .               | 98  |
| lcfMetRadio . . . . .                    | 98  |
| loadpack . . . . .                       | 99  |
| mainPlotControlsUI . . . . .             | 100 |
| mainScatterNew . . . . .                 | 100 |
| niceKmeans . . . . .                     | 101 |
| normalizationMethods . . . . .           | 102 |
| palUI . . . . .                          | 102 |
| panel.cor . . . . .                      | 103 |
| panel.hist . . . . .                     | 104 |
| pcaPlotControlsUI . . . . .              | 104 |
| plotData . . . . .                       | 105 |
| plotMarginsUI . . . . .                  | 105 |
| plotSizeMarginsUI . . . . .              | 106 |
| plotSizeUI . . . . .                     | 107 |
| plotTypeUI . . . . .                     | 108 |
| plot_pca . . . . .                       | 108 |
| prepDataContainer . . . . .              | 109 |
| prepDEOutput . . . . .                   | 110 |
| prepGroup . . . . .                      | 111 |
| prepHeatData . . . . .                   | 111 |
| prepPCADat . . . . .                     | 112 |
| push . . . . .                           | 112 |
| removeCols . . . . .                     | 113 |
| removeExtraCols . . . . .                | 114 |
| round_vals . . . . .                     | 114 |
| runDE . . . . .                          | 115 |
| runDESeq2 . . . . .                      | 115 |

|                            |     |
|----------------------------|-----|
| runEdgeR . . . . .         | 116 |
| runHeatmap . . . . .       | 117 |
| runHeatmap2 . . . . .      | 118 |
| runLimma . . . . .         | 119 |
| run_pca . . . . .          | 119 |
| selectConditions . . . . . | 120 |
| selectedInput . . . . .    | 121 |
| selectGroupInfo . . . . .  | 121 |
| sepRadio . . . . .         | 122 |
| setBatch . . . . .         | 123 |
| showObj . . . . .          | 123 |
| startDEBrowser . . . . .   | 124 |
| startHeatmap . . . . .     | 124 |
| textareaInput . . . . .    | 125 |
| togglePanels . . . . .     | 125 |

|              |            |
|--------------|------------|
| <b>Index</b> | <b>127</b> |
|--------------|------------|

---

|                |   |
|----------------|---|
| actionButtonDE | <i>Buttons including Action Buttons and Event Buttons</i> |
|----------------|---|

---

## Description

Creates an action button whose value is initially zero, and increments by one each time it is pressed.

## Usage

```
actionButtonDE(
  inputId,
  label,
  styleclass = "",
  size = "",
  block = FALSE,
  icon = NULL,
  css.class = "",
  ...
)
```

## Arguments

|            |   |
|------------|---|
| inputId    | Specifies the input slot that will be used to access the value.   |
| label      | The contents of the button—usually a text label, but you could also use any other HTML, like an image.                |
| styleclass | The Bootstrap styling class of the button—options are primary, info, success, warning, danger, inverse, link or blank |
| size       | The size of the button—options are large, small, mini   |
| block      | Whether the button should fill the block  |

|                        |   |
|------------------------|---|
| <code>icon</code>      | Display an icon for the button                                  |
| <code>css.class</code> | Any additional CSS class one wishes to add to the action button |
| <code>...</code>       | Other argument to feed into <code>shiny::actionButton</code>    |

**Examples**

```
actionButtonDE("goDE", "Go to DE Analysis")
```

---

|                          |                    |
|--------------------------|--------------------|
| <code>addDataCols</code> | <i>addDataCols</i> |
|--------------------------|--------------------|

---

**Description**

add additional data columns to de results

**Usage**

```
addDataCols(data = NULL, de_res = NULL, cols = NULL, conds = NULL)
```

**Arguments**

|                      |                |
|----------------------|----------------|
| <code>data,</code>   | loaded dataset |
| <code>de_res,</code> | de results     |
| <code>cols,</code>   | columns        |
| <code>conds,</code>  | inputconds     |

**Value**

data

**Examples**

```
x <- addDataCols()
```

addID                      *addID*

---

**Description**

Adds an id to the data frame being used.

**Usage**

```
addID(data = NULL)
```

**Arguments**

data,                      loaded dataset

**Value**

data

**Examples**

```
x <- addID()
```

---

all2all                      *all2all*

---

**Description**

Prepares all2all scatter plots for given datasets.

**Usage**

```
all2all(data, cex = 2)
```

**Arguments**

data,                      data that have the sample names in the header.  
cex                          text size

**Value**

all2all scatter plots

**Examples**

```
plot<-all2all(mtcars)
```



---

|                   |                          |
|-------------------|--------------------------|
| all2allControlsUI | <i>all2allControlsUI</i> |
|-------------------|--------------------------|

---

**Description**

Generates the controls in the left menu for an all2all plot

**Usage**

```
all2allControlsUI(id)
```

**Arguments**

id, namespace id

**Value**

returns the controls for left menu

**Note**

all2allControlsUI

**Examples**

```
x <- all2allControlsUI("bar")
```

---

|              |                     |
|--------------|---------------------|
| applyFilters | <i>applyFilters</i> |
|--------------|---------------------|

---

**Description**

Applies filters based on user selected parameters to be displayed within the DEBrowser.

**Usage**

```
applyFilters(filt_data = NULL, cols = NULL, conds = NULL, input = NULL)
```

**Arguments**

filt\_data, loaded dataset  
cols, selected samples  
conds, selected conditions  
input, input parameters

**Value**

data

**Examples**

```
x <- applyFilters()
```

---

|                              |                        |
|------------------------------|------------------------|
| <code>applyFiltersNew</code> | <i>applyFiltersNew</i> |
|------------------------------|------------------------|

---

**Description**

Apply filters based on foldChange cutoff and padj value. This function adds a "Legend" column with "Up", "Down" or "NS" values for visualization.

**Usage**

```
applyFiltersNew(data = NULL, input = NULL)
```

**Arguments**

|                      |                  |
|----------------------|------------------|
| <code>data</code> ,  | loaded dataset   |
| <code>input</code> , | input parameters |

**Value**

data

**Examples**

```
x <- applyFiltersNew()
```

---

|   |                                       |
|---|---------------------------------------|
| <code>applyFiltersToMergedComparison</code> | <i>applyFiltersToMergedComparison</i> |
|---|---------------------------------------|

---

**Description**

Gathers the merged comparison data to be used within the DEBrowser.

**Usage**

```
applyFiltersToMergedComparison(merged = NULL, nc = NULL, input = NULL)
```

**Arguments**

merged, merged data  
nc, the number of comparisons  
input, input params

**Value**

data

**Examples**

```
x <- applyFiltersToMergedComparison()
```

---

barMainPlotControlsUI *barMainPlotControlsUI*

---

**Description**

Generates the controls in the left menu for a bar main plot

**Usage**

```
barMainPlotControlsUI(id)
```

**Arguments**

id, namespace id

**Value**

returns the controls for left menu

**Note**

```
barMainPlotControlsUI
```

**Examples**

```
x <- barMainPlotControlsUI("bar")
```

---

|               |  |
|---------------|--|
| batchEffectUI | <i>batchEffectUI</i> Creates a panel to correct batch effect |
|---------------|--|

---

**Description**

batchEffectUI Creates a panel to correct batch effect

**Usage**

```
batchEffectUI(id)
```

**Arguments**

id, namespace id

**Value**

panel

**Examples**

```
x <- batchEffectUI("batcheffect")
```

---

|             |                    |
|-------------|--------------------|
| batchMethod | <i>batchMethod</i> |
|-------------|--------------------|

---

**Description**

select batch effect method

**Usage**

```
batchMethod(id)
```

**Arguments**

id, namespace id

**Value**

radio control

**Note**

batchMethod

**Examples**

```
x <- batchMethod("batch")
```

---

BoxMainPlotControlsUI *BoxMainPlotControlsUI*

---

**Description**

Generates the controls in the left menu for a Box main plot

**Usage**

```
BoxMainPlotControlsUI(id)
```

**Arguments**

id, namespace id

**Value**

returns the controls for left menu

**Note**

```
BoxMainPlotControlsUI
```

**Examples**

```
x <- BoxMainPlotControlsUI("box")
```

---

changeClusterOrder *changeClusterOrder*

---

**Description**

change order of K-means clusters

**Usage**

```
changeClusterOrder(order = NULL, cld = NULL)
```

**Arguments**

order, order  
cld, data

**Value**

heatmap plot area

**Note**

`changeClusterOrder`

**Examples**

```
x <- changeClusterOrder()
```

---

`checkCountData`

*checkCountData*

---

**Description**

Returns if there is a problem in the count data.

**Usage**

```
checkCountData(input = NULL)
```

**Arguments**

`input`, `inputs`

**Value**

error if there is a problem about the loaded data

**Note**

`checkCountData`

**Examples**

```
x <- checkCountData()
```

---

|               |                      |
|---------------|----------------------|
| checkMetaData | <i>checkMetaData</i> |
|---------------|----------------------|

---

**Description**

Returns if there is a problem in the count data.

**Usage**

```
checkMetaData(input = NULL, counttable = NULL)
```

**Arguments**

|             |            |
|-------------|------------|
| input,      | input      |
| counttable, | counttable |

**Value**

error if there is a problem about the loaded data

**Note**

checkMetaData

**Examples**

```
x <- checkMetaData()
```

---

|             |                    |
|-------------|--------------------|
| clusterData | <i>clusterData</i> |
|-------------|--------------------|

---

**Description**

Gathers the Cluster analysis data to be used within the GO Term plots.

**Usage**

```
clusterData(dat = NULL)
```

**Arguments**

|      |                     |
|------|---------------------|
| dat, | the data to cluster |
|------|---------------------|

**Value**

clustered data

**Note**

```
clusterData
```

**Examples**

```
mycluster <- clusterData()
```

---

```
clustFunParamsUI      clustFunParamsUI
```

---

**Description**

get cluster function parameter control

**Usage**

```
clustFunParamsUI()
```

**Value**

cluster params

**Note**

```
clustFunParamsUI
```

**Examples**

```
x <- clustFunParamsUI()
```

---

```
compareClust      compareClust
```

---

**Description**

Compares the clustered data to be displayed within the GO Term plots.

**Usage**

```
compareClust(  
  dat = NULL,  
  ont = "CC",  
  org = "org.Hs.eg.db",  
  fun = "enrichGO",  
  title = "Ontology Distribution Comparison",  
  pvalueCutoff = 0.01  
)
```



**Arguments**

dat, data to compare clusters  
ont, the ontology to use  
org, the organism used  
fun, fun  
title, title of the comparison  
pvalueCutoff, pvalueCutoff

**Value**

compared cluster

**Note**

compareClust

**Examples**

```
x <- compareClust()
```

---

condSelectUI

*condSelectUI Creates a panel to select samples for each condition*

---

**Description**

condSelectUI Creates a panel to select samples for each condition

**Usage**

```
condSelectUI()
```

**Value**

panel

**Examples**

```
x <- condSelectUI()
```

---

|               |   |
|---------------|---|
| correctCombat | <i>Correct Batch Effect using Combat in sva package</i> |
|---------------|---|

---

**Description**

Batch effect correction

**Usage**

```
correctCombat(input = NULL, idata = NULL, metadata = NULL)
```

**Arguments**

|           |              |
|-----------|--------------|
| input,    | input values |
| idata,    | data         |
| metadata, | metadata     |

**Value**

data

**Examples**

```
x<-correctCombat ()
```

---

|               |  |
|---------------|--|
| correctHarman | <i>Correct Batch Effect using Harman</i> |
|---------------|--|

---

**Description**

Batch effect correction

**Usage**

```
correctHarman(input = NULL, idata = NULL, metadata = NULL)
```

**Arguments**

|           |              |
|-----------|--------------|
| input,    | input values |
| idata,    | data         |
| metadata, | metadata     |

**Value**

data

**Examples**

```
x<-correctHarman ()
```

---

|                |                       |
|----------------|-----------------------|
| customColorsUI | <i>customColorsUI</i> |
|----------------|-----------------------|

---

**Description**

get Custom Color controls

**Usage**

```
customColorsUI(id)
```

**Arguments**

id, namespace ID

**Value**

color range

**Note**

getColRng

**Examples**

```
x <- customColorsUI("heatmap")
```

---

|                   |                          |
|-------------------|--------------------------|
| cutOffSelectionUI | <i>cutOffSelectionUI</i> |
|-------------------|--------------------------|

---

**Description**

Gathers the cut off selection for DE analysis

**Usage**

```
cutOffSelectionUI(id)
```

**Arguments**

id, namespace id

**Value**

returns the left menu according to the selected tab;

**Note**

cutOffSelectionUI

**Examples**

```
x <- cutOffSelectionUI("cutoff")
```

---

dataLCFUI

*dataLCFUI Creates a panel to filter low count genes and regions*

---

**Description**

dataLCFUI Creates a panel to filter low count genes and regions

**Usage**

```
dataLCFUI(id)
```

**Arguments**

id, namespace id

**Value**

panel

**Examples**

```
x <- dataLCFUI("lcf")
```

---

|            |                   |
|------------|-------------------|
| dataLoadUI | <i>dataLoadUI</i> |
|------------|-------------------|

---

**Description**

Creates a panel to upload the data

**Usage**

```
dataLoadUI(id)
```

**Arguments**

id, namespace id

**Value**

panel

**Examples**

```
x <- dataLoadUI("load")
```

---

|                  |                         |
|------------------|-------------------------|
| debrowserall2all | <i>debrowserall2all</i> |
|------------------|-------------------------|

---

**Description**

Module for a bar plot that can be used in data prep, main plots low count removal modules or any desired module

**Usage**

```
debrowserall2all(input, output, session, data = NULL, cex = 2)
```

**Arguments**

input, input variables  
output, output objects  
session, session  
data, a matrix that includes expression values  
cex, the size of the dots

**Value**

all2all plot

**Examples**

```
x <- debrowserall2all()
```

---

debrowserbarmainplot *debrowserbarmainplot*

---

**Description**

Module for a bar plot that can be used in data prep, main plots low count removal modules or any desired module

**Usage**

```
debrowserbarmainplot(  
  input,  
  output,  
  session,  
  data = NULL,  
  cols = NULL,  
  conds = NULL,  
  key = NULL  
)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| output,  | output objects                           |
| session, | session                                  |
| data,    | a matrix that includes expression values |
| cols,    | columns                                  |
| conds,   | conditions                               |
| key,     | the gene or region name                  |

**Value**

density plot

**Examples**

```
x <- debrowserbarmainplot()
```

---

debrowserbatcheffect *debrowserbatcheffect*

---

**Description**

Module to correct batch effect

**Usage**

```
debrowserbatcheffect(input, output, session, ldata = NULL)
```

**Arguments**

|          |                 |
|----------|-----------------|
| input,   | input variables |
| output,  | output objects  |
| session, | session         |
| ldata,   | loaded data     |

**Value**

main plot  
panel

**Examples**

```
x <- debrowserbatcheffect()
```

---

debrowserboxmainplot *debrowserboxmainplot*

---

**Description**

Module for a box plot that can be used in DEanalysis main part and used heatmaps

**Usage**

```
debrowserboxmainplot(  
  input = NULL,  
  output = NULL,  
  session = NULL,  
  data = NULL,  
  cols = NULL,  
  conds = NULL,  
  key = NULL  
)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| output,  | output objects                           |
| session, | session                                  |
| data,    | a matrix that includes expression values |
| cols,    | columns                                  |
| conds,   | conditions                               |
| key,     | the gene or region name                  |

**Value**

density plot

**Examples**

```
x <- debrowserboxmainplot()
```

---

debrowsercondselect    *debrowsercondselect*

---

**Description**

Condition selection This is not a module. Module construction didn't used here, just use it as functions not in a module.

**Usage**

```
debrowsercondselect(  
  input = NULL,  
  output = NULL,  
  session = NULL,  
  data = NULL,  
  metadata = NULL  
)
```

**Arguments**

|           |                 |
|-----------|-----------------|
| input,    | input variables |
| output,   | output objects  |
| session,  | session         |
| data,     | count data      |
| metadata, | metadata        |



**Value**

main plot  
panel

**Examples**

```
x <- debrowsercondselect()
```

---

debrowserdataload      *debrowserdataload*

---

**Description**

Module to load count data and metadata

**Usage**

```
debrowserdataload(  
  input = NULL,  
  output = NULL,  
  session = NULL,  
  nextpagebutton = NULL  
)
```

**Arguments**

input,                    input variables  
output,                   output objects  
session,                   session  
nextpagebutton,           the name of the next page button after loading the data

**Value**

main plot  
panel

**Examples**

```
x <- debrowserdataload()
```

---

debrowserdeanalysis    *debrowserdeanalysis*

---

### Description

Module to perform and visualize DE results.

### Usage

```
debrowserdeanalysis(  
  input = NULL,  
  output = NULL,  
  session = NULL,  
  data = NULL,  
  columns = NULL,  
  conds = NULL,  
  params = NULL  
)
```

### Arguments

|          |  |
|----------|--|
| input,   | input variables                          |
| output,  | output objects                           |
| session, | session                                  |
| data,    | a matrix that includes expression values |
| columns, | columns                                  |
| conds,   | conditions                               |
| params,  | de parameters                            |

### Value

DE panel

### Examples

```
x <- debrowserdeanalysis()
```

---

debrowserdensityplot *debrowserdensityplot*

---

**Description**

Module for a density plot that can be used in data prep and low count removal modules

**Usage**

```
debrowserdensityplot(input = NULL, output = NULL, session = NULL, data = NULL)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| output,  | output objects                           |
| session, | session                                  |
| data,    | a matrix that includes expression values |

**Value**

density plot

**Examples**

```
x <- debrowserdensityplot()
```

---

debrowserheatmap *debrowserheatmap*

---

**Description**

Heatmap module to create interactive heatmaps and get selected list from a heatmap

**Usage**

```
debrowserheatmap(input, output, session, expdata = NULL)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| output,  | output objects                           |
| session, | session                                  |
| expdata, | a matrix that includes expression values |

**Value**

heatmaply plot

**Examples**

```
x <- debrowserheatmap()
```

---

debrowserhistogram    *debrowserhistogram*

---

**Description**

Module for a histogram that can be used in data prep and low count removal modules

**Usage**

```
debrowserhistogram(input = NULL, output = NULL, session = NULL, data = NULL)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| output,  | output objects                           |
| session, | session                                  |
| data,    | a matrix that includes expression values |

**Value**

histogram

**Examples**

```
x <- debrowserhistogram()
```

---

debrowserIQRplot      *debrowserIQRplot*

---

**Description**

Module for an IQR plot that can be used in data prep and low count removal modules

**Usage**

```
debrowserIQRplot(input = NULL, output = NULL, session = NULL, data = NULL)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| output,  | output objects                           |
| session, | session                                  |
| data,    | a matrix that includes expression values |

**Value**

IQR

**Examples**

```
x <- debrowserIQRplot()
```

---

debrowserlowcountfilter  
*debrowserlowcountfilter*

---

**Description**

Module to filter low count genes/regions

**Usage**

```
debrowserlowcountfilter(  
  input = NULL,  
  output = NULL,  
  session = NULL,  
  ldata = NULL  
)
```

**Arguments**

|          |                 |
|----------|-----------------|
| input,   | input variables |
| output,  | output objects  |
| session, | session         |
| ldata,   | loaded data     |

**Value**

main plot  
panel

**Examples**

```
x <- debrowserlowcountfilter()
```

---

|                   |                          |
|-------------------|--------------------------|
| debrowsermainplot | <i>debrowsermainplot</i> |
|-------------------|--------------------------|

---

**Description**

Module for a scatter, volcano and ma plots that are going to be used as a mainplot in debrowser

**Usage**

```
debrowsermainplot(input = NULL, output = NULL, session = NULL, data = NULL)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| output,  | output objects                           |
| session, | session                                  |
| data,    | a matrix that includes expression values |

**Value**

main plot  
panel

**Examples**

```
x <- debrowsermainplot()
```

---

|                  |                         |
|------------------|-------------------------|
| debrowserpcaplot | <i>debrowserpcaplot</i> |
|------------------|-------------------------|

---

**Description**

Module for a pca plot with its loadings as a mainplot in debrowser

**Usage**

```
debrowserpcaplot(  
  input = NULL,  
  output = NULL,  
  session = NULL,  
  pccadata = NULL,  
  metadata = NULL  
)
```

**Arguments**

|           |  |
|-----------|--|
| input,    | input variables                          |
| output,   | output objects                           |
| session,  | session                                  |
| pccadata, | a matrix that includes expression values |
| metadata, | metadata to color the plots              |

**Value**

main plot  
panel

**Examples**

```
x <- debrowserpcaplot()
```

---

|                |                       |
|----------------|-----------------------|
| dendControlsUI | <i>dendControlsUI</i> |
|----------------|-----------------------|

---

**Description**

get distance metric parameters

**Usage**

```
dendControlsUI(id, dendtype = "Row")
```

**Arguments**

id,                    module ID  
dendtype,            Row or Col

**Value**

controls

**Note**

dendControlsUI

**Examples**

```
x <- dendControlsUI("heatmap")
```

---

*densityPlotControlsUI* *densityPlotControlsUI*

---

**Description**

Generates the controls in the left menu for a densityPlot

**Usage**

```
densityPlotControlsUI(id)
```

**Arguments**

id,                    namespace id

**Value**

returns the left menu

**Note**

densityPlotControlsUI

**Examples**

```
x <- densityPlotControlsUI("density")
```



---

|          |                 |
|----------|-----------------|
| deServer | <i>deServer</i> |
|----------|-----------------|

---

**Description**

Sets up shinyServer to be able to run DEBrowser interactively.

**Usage**

```
deServer(input, output, session)
```

**Arguments**

|          |                      |
|----------|----------------------|
| input,   | input params from UI |
| output,  | output params to UI  |
| session, | session variable     |

**Value**

the panel for main plots;

**Note**

deServer

**Examples**

```
deServer
```

---

|      |             |
|------|-------------|
| deUI | <i>deUI</i> |
|------|-------------|

---

**Description**

Creates a shinyUI to be able to run DEBrowser interactively.

**Usage**

```
deUI()
```

**Value**

the panel for main plots;

**Note**

deUI

**Examples**

```
x<-deUI()
```

---

|                 |                        |
|-----------------|------------------------|
| distFunParamsUI | <i>distFunParamsUI</i> |
|-----------------|------------------------|

---

**Description**

get distance metric parameters

**Usage**

```
distFunParamsUI()
```

**Value**

funParams

**Note**

distFunParamsUI

**Examples**

```
x <- distFunParamsUI()
```

---

|          |                 |
|----------|-----------------|
| drawKEGG | <i>drawKEGG</i> |
|----------|-----------------|

---

**Description**

draw KEGG pathway with expression values

**Usage**

```
drawKEGG(input = NULL, dat = NULL, pid = NULL)
```

**Arguments**

|        |                   |
|--------|-------------------|
| input, | input             |
| dat,   | expression matrix |
| pid,   | pathway id        |

**Value**

enriched DO

**Note**

drawKEGG

**Examples**

```
x <- drawKEGG()
```

---

|                               |  |
|-------------------------------|--|
| <code>drawPCAExplained</code> | <i>Creates a more detailed plot using the PCA results from the selected dataset.</i> |
|-------------------------------|--|

---

**Description**

Creates a more detailed plot using the PCA results from the selected dataset.

**Usage**

```
drawPCAExplained(explainedData = NULL)
```

**Arguments**

explainedData,  
selected data

**Value**

explained plot

**Examples**

```
x <- drawPCAExplained()
```

---

|           |                  |
|-----------|------------------|
| fileTypes | <i>fileTypes</i> |
|-----------|------------------|

---

**Description**

Returns fileTypes that are going to be used in creating fileUpload UI

**Usage**

```
fileTypes()
```

**Value**

file types

**Note**

fileTypes

**Examples**

```
x <- fileTypes()
```

---

|               |                      |
|---------------|----------------------|
| fileUploadBox | <i>fileUploadBox</i> |
|---------------|----------------------|

---

**Description**

File upload module

**Usage**

```
fileUploadBox(id = NULL, inputId = NULL, label = NULL)
```

**Arguments**

|          |               |
|----------|---------------|
| id,      | namespace id  |
| inputId, | input file ID |
| label,   | label         |

**Value**

radio control

**Note**

fileUploadBox

**Examples**

```
x <- fileUploadBox("meta", "metadata", "Metadata")
```

---

`generateTestData`      *generateTestData*

---

**Description**

This generates a test data that is suitable to main plots in debrowser

**Usage**

```
generateTestData(dat = NULL)
```

**Arguments**

dat,                    DESeq results will be generated for loaded data

**Value**

testData

**Examples**

```
x <- generateTestData()
```

---

`getAfterLoadMsg`      *getAfterLoadMsg*

---

**Description**

Generates and displays the message to be shown after loading data within the DEBrowser.

**Usage**

```
getAfterLoadMsg()
```

**Value**

return After Load Msg

**Note**

```
getAfterLoadMsg
```

**Examples**

```
x <- getAfterLoadMsg()
```

---

|                               |                         |
|-------------------------------|-------------------------|
| <code>getAll2AllPlotUI</code> | <i>getAll2AllPlotUI</i> |
|-------------------------------|-------------------------|

---

**Description**

all2all plots UI.

**Usage**

```
getAll2AllPlotUI(id)
```

**Arguments**

`id`, `namespace id`

**Value**

the panel for all2all plots;

**Note**

```
getAll2AllPlotUI
```

**Examples**

```
x <- getAll2AllPlotUI("bar")
```

---

`getBarMainPlot`      *getBarMainPlot*

---

**Description**

Makes Density plots

**Usage**

```
getBarMainPlot(  
  data = NULL,  
  cols = NULL,  
  conds = NULL,  
  key = NULL,  
  title = "",  
  input = NULL  
)
```

**Arguments**

|                      |                          |
|----------------------|--------------------------|
| <code>data</code> ,  | count or normalized data |
| <code>cols</code> ,  | cols                     |
| <code>conds</code> , | conds                    |
| <code>key</code> ,   | key                      |
| <code>title</code> , | title                    |
| <code>input</code> , | input                    |

**Examples**

```
getBarMainPlot()
```

---

`getBarMainPlotUI`      *getBarMainPlotUI*

---

**Description**

main bar plots UI.

**Usage**

```
getBarMainPlotUI(id)
```

**Arguments**

id, namespace id

**Value**

the panel for Density plots;

**Note**

`getBarMainPlotUI`

**Examples**

```
x <- getBarMainPlotUI("bar")
```

---

|                             |                       |
|-----------------------------|-----------------------|
| <code>getBoxMainPlot</code> | <i>getBoxMainPlot</i> |
|-----------------------------|-----------------------|

---

**Description**

Makes Density plots

**Usage**

```
getBoxMainPlot(  
  data = NULL,  
  cols = NULL,  
  conds = NULL,  
  key = NULL,  
  title = "",  
  input = NULL  
)
```

**Arguments**

data, count or normalized data  
cols, cols  
conds, conds  
key, key  
title, title  
input, input

**Examples**

```
getBoxMainPlot()
```



---

`getBoxMainPlotUI`      *getBoxMainPlotUI*

---

**Description**

main Box plots UI.

**Usage**

```
getBoxMainPlotUI(id)
```

**Arguments**

`id`,                    namespace id

**Value**

the panel for Density plots;

**Note**

`getBoxMainPlotUI`

**Examples**

```
x <- getBoxMainPlotUI("box")
```

---

`getBSTableUI`                    *getBSTableUI prepares a Modal to put a table*

---

**Description**

`getBSTableUI` prepares a Modal to put a table

**Usage**

```
getBSTableUI(  
  name = NULL,  
  label = NULL,  
  trigger = NULL,  
  size = "large",  
  modal = NULL  
)
```

**Arguments**

|          |                              |
|----------|------------------------------|
| name,    | name                         |
| label,   | label                        |
| trigger, | trigger button for the modal |
| size,    | size of the modal            |
| modal,   | modal yes/no                 |

**Value**

the modal

**Examples**

```
x<- getBSTableUI()
```

---

`getColor`s

*getColor*s

---

**Description**

get colors for the domains

**Usage**

```
getColor(s(domains = NULL))
```

**Arguments**

|          |                       |
|----------|-----------------------|
| domains, | domains to be colored |
|----------|-----------------------|

**Value**

colors

**Examples**

```
x<-getColor(s())
```

---

```
getColorShapeSelection  
    getColorShapeSelection
```

---

**Description**

Generates the fill and shape selection boxes for PCA plots. metadata file has to be loaded in this case

**Usage**

```
getColorShapeSelection(metadata = NULL, input = NULL, session = NULL)
```

**Arguments**

|           |                |
|-----------|----------------|
| metadata, | metadata table |
| input,    | input          |
| session,  | session        |

**Value**

Color and shape selection boxes

**Examples**

```
x <- getColorShapeSelection()
```

---

```
getCompSelection    getCompSelection
```

---

**Description**

Gathers the user selected comparison set to be used within the DEBrowser.

**Usage**

```
getCompSelection(name = NULL, count = NULL)
```

**Arguments**

|        |                             |
|--------|-----------------------------|
| name,  | the name of the selectInput |
| count, | comparison count            |

**Note**

```
getCompSelection
```

**Examples**

```
x <- getCompSelection(name="comp", count = 2)
```

---

```
getConditionSelector    getConditionSelector
```

---

**Description**

Selects user input conditions to run in DESeq.

**Usage**

```
getConditionSelector(num = 0, choices = NULL, selected = NULL)
```

**Arguments**

|           |                                 |
|-----------|---------------------------------|
| num,      | panel that is going to be shown |
| choices,  | sample list                     |
| selected, | selected smaple list            |

**Examples**

```
x <- getConditionSelector()
```

---

```
getConditionSelectorFromMeta  
                          getConditionSelectorFromMeta
```

---

**Description**

Selects user input conditions to run in DESeq from metadata

**Usage**

```
getConditionSelectorFromMeta(  
  metadata = NULL,  
  input = NULL,  
  index = 1,  
  num = 0,  
  choices = NULL,  
  selected = NULL  
)
```

**Arguments**

|           |                 |
|-----------|-----------------|
| metadata, | meta data table |
| input,    | input           |
| index,    | index           |
| num,      | num             |
| choices,  | choices         |
| selected, | selected        |

**Examples**

```
x <- getConditionSelectorFromMeta()
```

---

|            |                   |
|------------|-------------------|
| getCondMsg | <i>getCondMsg</i> |
|------------|-------------------|

---

**Description**

Generates and displays the current conditions and their samples within the DEBrower.

**Usage**

```
getCondMsg(dc = NULL, input = NULL, cols = NULL, conds = NULL)
```

**Arguments**

|        |                     |
|--------|---------------------|
| dc,    | columns             |
| input, | selected comparison |
| cols,  | columns             |
| conds, | selected conditions |

**Value**

return conditions

**Note**

getCondMsg

**Examples**

```
x <- getCondMsg()
```

---

`getCutOffSelection`     *getCutOffSelection*

---

**Description**

Gathers the cut off selection for DE analysis

**Usage**

```
getCutOffSelection(nc = 1)
```

**Arguments**

`nc`,                    total number of comparisons

**Value**

returns the left menu according to the selected tab;

**Note**

`getCutOffSelection`

**Examples**

```
x <- getCutOffSelection()
```

---

`getDataAssesmentText`     *getDataAssesmentText DataAssesment text*

---

**Description**

`getDataAssesmentText` DataAssesment text

**Usage**

```
getDataAssesmentText()
```

**Value**

help text for data assesment

**Examples**

```
x<- getDataAssesmentText()
```

---

getDataForTables      *getDataForTables* get data to fill up tables tab

---

### Description

getDataForTables get data to fill up tables tab

### Usage

```
getDataForTables(  
  input = NULL,  
  init_data = NULL,  
  filt_data = NULL,  
  selected = NULL,  
  getMostVaried = NULL,  
  mergedComp = NULL,  
  explainedData = NULL  
)
```

### Arguments

|                |                       |
|----------------|-----------------------|
| input,         | input parameters      |
| init_data,     | initial dataset       |
| filt_data,     | filt_data             |
| selected,      | selected genes        |
| getMostVaried, | most varied genes     |
| mergedComp,    | merged comparison set |
| explainedData, | pca gene set          |

### Value

data

### Examples

```
x <- getDataForTables()
```

---

getDataPreparationText

*getDataPreparationText DataPreparation text*

---

**Description**

getDataPreparationText DataPreparation text

**Usage**

```
getDataPreparationText()
```

**Value**

help text for data preparation

**Examples**

```
x<- getDataPreparationText()
```

---

getDEAnalysisText

*getDEAnalysisText DEAnalysis text*

---

**Description**

getDEAnalysisText DEAnalysis text

**Usage**

```
getDEAnalysisText()
```

**Value**

help text for DE Analysis

**Examples**

```
x<- getDEAnalysisText()
```



---

`getDensityPlot`      *getDensityPlot*

---

**Description**

Makes Density plots

**Usage**

```
getDensityPlot(data = NULL, input = NULL, title = "")
```

**Arguments**

|                      |                          |
|----------------------|--------------------------|
| <code>data</code> ,  | count or normalized data |
| <code>input</code> , | input                    |
| <code>title</code> , | title                    |

**Examples**

```
getDensityPlot()
```

---

`getDensityPlotUI`      *getDensityPlotUI*

---

**Description**

Density plot UI.

**Usage**

```
getDensityPlotUI(id)
```

**Arguments**

|                   |              |
|-------------------|--------------|
| <code>id</code> , | namespace id |
|-------------------|--------------|

**Value**

the panel for Density plots;

**Note**

```
getDensityPlotUI
```

**Examples**

```
x <- getDensityPlotUI("density")
```

---

|                |   |
|----------------|---|
| getDEResultsUI | <i>getDEResultsUI</i> Creates a panel to visualize DE results |
|----------------|---|

---

**Description**

getDEResultsUI Creates a panel to visualize DE results

**Usage**

```
getDEResultsUI(id)
```

**Arguments**

id, namespace id

**Value**

panel

**Examples**

```
x <- getDEResultsUI("batcheffect")
```

---

|            |                   |
|------------|-------------------|
| getDomains | <i>getDomains</i> |
|------------|-------------------|

---

**Description**

Get domains for the main plots.

**Usage**

```
getDomains(filt_data = NULL)
```

**Arguments**

filt\_data, data to get the domains

**Value**

domains

**Examples**

```
x<-getDomains()
```

---

getDown                    *getDown get down regulated data*

---

**Description**

getDown get down regulated data

**Usage**

```
getDown(filt_data = NULL)
```

**Arguments**

filt\_data,            filt\_data

**Value**

data

**Examples**

```
x <- getDown()
```

---

getDownloadSection        *getDownloadSection*

---

**Description**

download section button and dataset selection box in the menu for user to download selected data.

**Usage**

```
getDownloadSection(choices = NULL)
```

**Arguments**

choices,                main vs. QC section

**Value**

the panel for download section in the menu;

**Note**

```
getDownloadSection
```

**Examples**

```
x<- getDownloadSection()
```

---

```
getEnrichDO
```

```
getEnrichDO
```

---

**Description**

Gathers the Enriched DO Term analysis data to be used within the GO Term plots.

**Usage**

```
getEnrichDO(genelist = NULL, pvalueCutoff = 0.01)
```

**Arguments**

```
genelist,      gene list  
pvalueCutoff, the p value cutoff
```

**Value**

```
enriched DO
```

**Note**

```
getEnrichDO
```

**Examples**

```
x <- getEnrichDO()
```

---

|             |                    |
|-------------|--------------------|
| getEnrichGO | <i>getEnrichGO</i> |
|-------------|--------------------|

---

**Description**

Gathers the Enriched GO Term analysis data to be used within the GO Term plots.

**Usage**

```
getEnrichGO(  
  genelist = NULL,  
  pvalueCutoff = 0.01,  
  org = "org.Hs.eg.db",  
  ont = "CC"  
)
```

**Arguments**

|               |                   |
|---------------|-------------------|
| genelist,     | gene list         |
| pvalueCutoff, | p value cutoff    |
| org,          | the organism used |
| ont,          | the ontology used |

**Value**

Enriched GO

**Note**

getEnrichGO

**Examples**

```
x <- getEnrichGO()
```

---

|                            |                      |
|----------------------------|----------------------|
| <code>getEnrichKEGG</code> | <i>getEnrichKEGG</i> |
|----------------------------|----------------------|

---

**Description**

Gathers the Enriched KEGG analysis data to be used within the GO Term plots.

**Usage**

```
getEnrichKEGG(genelist = NULL, pvalueCutoff = 0.01, org = "org.Hs.eg.db")
```

**Arguments**

|                             |                    |
|-----------------------------|--------------------|
| <code>genelist</code> ,     | gene list          |
| <code>pvalueCutoff</code> , | the p value cutoff |
| <code>org</code> ,          | the organism used  |

**Value**

Enriched KEGG

**Note**

`getEnrichKEGG`

**Examples**

```
x <- getEnrichKEGG()
```

---

|                           |                     |
|---------------------------|---------------------|
| <code>getEntrezIds</code> | <i>getEntrezIds</i> |
|---------------------------|---------------------|

---

**Description**

Gathers the gene list to use for GOTerm analysis.

**Usage**

```
getEntrezIds(genes = NULL, org = "org.Hs.eg.db")
```

**Arguments**

|                      |   |
|----------------------|---|
| <code>genes</code> , | gene list with fold changes                   |
| <code>org</code> ,   | organism for gene symbol entrez ID conversion |

**Value**

ENTREZ ID list

**Note**

GOTerm  
getEntrezIds symbol to ENTREZ ID conversion

**Examples**

```
x <- getEntrezIds()
```

---

|                |                       |
|----------------|-----------------------|
| getEntrezTable | <i>getEntrezTable</i> |
|----------------|-----------------------|

---

**Description**

Gathers the entrezIds of the genes in given list and their data

**Usage**

```
getEntrezTable(genes = NULL, dat = NULL, org = "org.Hs.eg.db")
```

**Arguments**

genes,            gene list  
dat,             data matrix  
org,             organism for gene symbol entrez ID conversion

**Value**

table with the entrez IDs in the rownames

**Note**

GOTerm  
getEntrezTable symbol to ENTREZ ID conversion

**Examples**

```
x <- getEntrezTable()
```

---

|             |                    |
|-------------|--------------------|
| getGeneList | <i>getGeneList</i> |
|-------------|--------------------|

---

**Description**

Gathers the gene list to use for GOTerm analysis.

**Usage**

```
getGeneList(  
  genes = NULL,  
  org = "org.Hs.eg.db",  
  fromType = "SYMBOL",  
  toType = c("ENTREZID")  
)
```

**Arguments**

|           |   |
|-----------|---|
| genes,    | gene list                                     |
| org,      | organism for gene symbol entrez ID conversion |
| fromType, | from Type                                     |
| toType,   | to Type                                       |

**Value**

ENTREZ ID list

**Note**

GOTerm  
getGeneList symbol to ENTREZ ID conversion

**Examples**

```
x <- getGeneList(c('OCLN', 'ABCC2'))
```



---

|                             |                       |
|-----------------------------|-----------------------|
| <code>getGeneSetData</code> | <i>getGeneSetData</i> |
|-----------------------------|-----------------------|

---

**Description**

Gathers the specified gene set list to be used within the DEBrowser.

**Usage**

```
getGeneSetData(data = NULL, geneset = NULL)
```

**Arguments**

|                        |                |
|------------------------|----------------|
| <code>data</code> ,    | loaded dataset |
| <code>geneset</code> , | given gene set |

**Value**

data

**Examples**

```
x <- getGeneSetData()
```

---

|                            |                      |
|----------------------------|----------------------|
| <code>getGOLeftMenu</code> | <i>getGOLeftMenu</i> |
|----------------------------|----------------------|

---

**Description**

Generates the GO Left menu to be displayed within the DEBrowser.

**Usage**

```
getGOLeftMenu()
```

**Value**

returns the left menu according to the selected tab;

**Note**

`getGOLeftMenu`

**Examples**

```
x <- getGOLeftMenu()
```

getGoPanel

*getGoPanel*

---

**Description**

Creates go term analysis panel within the shiny display.

**Usage**

```
getGoPanel()
```

**Value**

the panel for go term analysis;

**Note**

getGoPanel

**Examples**

```
x <- getGoPanel()
```

---

getGOPlots

*getGOPlots*

---

**Description**

Go term analysis panel. Generates appropriate GO plot based on user selection.

**Usage**

```
getGOPlots(dataset = NULL, GSEARes = NULL, input = NULL)
```

**Arguments**

|          |                  |
|----------|------------------|
| dataset, | the dataset used |
| GSEARes, | GSEA results     |
| input,   | input params     |

**Value**

the panel for go plots;

**Note**`getGOPlots`**Examples**

```
x<- getGOPlots()
```

---

`getGSEA`*getGSEA*

---

**Description**

Gathers the Enriched KEGG analysis data to be used within the GO Term plots.

**Usage**

```
getGSEA(  
  dataset = NULL,  
  pvalueCutoff = 0.01,  
  org = "org.Hs.eg.db",  
  sortfield = "log2FoldChange"  
)
```

**Arguments**

|                            |                      |
|----------------------------|----------------------|
| <code>dataset,</code>      | <code>dataset</code> |
| <code>pvalueCutoff,</code> | the p value cutoff   |
| <code>org,</code>          | the organism used    |
| <code>sortfield,</code>    | sort field for GSEA  |

**Value**`GSEA`**Note**`getGSEA`**Examples**

```
x <- getGSEA()
```

---

|              |                     |
|--------------|---------------------|
| getHeatmapUI | <i>getHeatmapUI</i> |
|--------------|---------------------|

---

**Description**

Generates the left menu to be used for heatmap plots

**Usage**

```
getHeatmapUI(id)
```

**Arguments**

id,                    module ID

**Value**

heatmap plot area

**Note**

getHeatmapUI

**Examples**

```
x <- getHeatmapUI("heatmap")
```

---

|               |  |
|---------------|--|
| getHelpButton | <i>getHelpButton prepares a helpbutton for to go to a specific site in the documentation</i> |
|---------------|--|

---

**Description**

getHelpButton prepares a helpbutton for to go to a specific site in the documentation

**Usage**

```
getHelpButton(name = NULL, link = NULL)
```

**Arguments**

name,                    name that are going to come after info  
link,                    link of the help

**Value**

the info button

**Examples**

```
x<- getHelpButton()
```

---

`getHideLegendOnOff`      *getHideLegendOnOff*

---

**Description**

hide legend

**Usage**

```
getHideLegendOnOff(id = "pca")
```

**Arguments**

id,                    namespace id

**Examples**

```
x <- getHideLegendOnOff("pca")
```

---

`getHistogramUI`              *getHistogramUI*

---

**Description**

Histogram plots UI.

**Usage**

```
getHistogramUI(id)
```

**Arguments**

id,                    namespace id

**Value**

the panel for PCA plots;

**Note**

`getHistogramUI`

**Examples**

```
x <- getHistogramUI("histogram")
```

---

|              |                                |
|--------------|--------------------------------|
| getIntroText | <i>getIntroText Intro text</i> |
|--------------|--------------------------------|

---

**Description**

getIntroText Intro text

**Usage**

```
getIntroText()
```

**Value**

the JS for tab updates

**Examples**

```
x<- getIntroText()
```

---

|            |                   |
|------------|-------------------|
| getIQRPlot | <i>getIQRPlot</i> |
|------------|-------------------|

---

**Description**

Makes IQR boxplot plot

**Usage**

```
getIQRPlot(data = NULL, input = NULL, title = "")
```

**Arguments**

|        |                          |
|--------|--------------------------|
| data,  | count or normalized data |
| input, | input                    |
| title, | title                    |

**Examples**

```
getIQRPlot()
```

---

|              |                     |
|--------------|---------------------|
| getIQRPlotUI | <i>getIQRPlotUI</i> |
|--------------|---------------------|

---

**Description**

IQR plot UI.

**Usage**

```
getIQRPlotUI(id)
```

**Arguments**

id, namespace id

**Value**

the panel for IQR plots;

**Note**

```
getIQRPlotUI
```

**Examples**

```
x <- getIQRPlotUI("IQR")
```

---

|           |                  |
|-----------|------------------|
| getJSLine | <i>getJSLine</i> |
|-----------|------------------|

---

**Description**

heatmap JS code for selection functionality

**Usage**

```
getJSLine()
```

**Value**

JS Code

**Examples**

```
x <- getJSLine()
```

---

|              |   |
|--------------|---|
| getKEGGModal | <i>getKEGGModal prepares a modal for KEGG plots</i> |
|--------------|---|

---

**Description**

getKEGGModal prepares a modal for KEGG plots

getKEGGModal prepares a helpbutton for to go to a specific site in the documentation

**Usage**

```
getKEGGModal()
```

```
getKEGGModal()
```

**Value**

the info button

the info button

**Examples**

```
x<- getKEGGModal()
```

```
x<- getKEGGModal()
```

---

|             |                    |
|-------------|--------------------|
| getLeftMenu | <i>getLeftMenu</i> |
|-------------|--------------------|

---

**Description**

Generates the left menu for for plots within the DEBrowser.

**Usage**

```
getLeftMenu(input = NULL)
```

**Arguments**

input,           input values

**Value**

returns the left menu according to the selected tab;



**Note**

`getLeftMenu`

**Examples**

```
x <- getLeftMenu()
```

---

|                              |                        |
|------------------------------|------------------------|
| <code>getLegendColors</code> | <i>getLegendColors</i> |
|------------------------------|------------------------|

---

**Description**

Generates colors according to the data

**Usage**

```
getLegendColors(Legend = c("up", "down", "NS"))
```

**Arguments**

Legend,            unique Legends

**Value**

`mainPlotControls`

**Note**

`getLegendColors`

**Examples**

```
x <- getLegendColors(c("up", "down", "GS", "NS"))
```

---

|                             |                       |
|-----------------------------|-----------------------|
| <code>getLegendRadio</code> | <i>getLegendRadio</i> |
|-----------------------------|-----------------------|

---

**Description**

Radio buttons for the types in the legend

**Usage**

```
getLegendRadio(id)
```

**Arguments**

`id`, `namespace id`

**Value**

radio control

**Note**

```
getLegendRadio
```

**Examples**

```
x <- getLegendRadio("deprog")
```

---

|                              |                        |
|------------------------------|------------------------|
| <code>getLegendSelect</code> | <i>getLegendSelect</i> |
|------------------------------|------------------------|

---

**Description**

select legend

**Usage**

```
getLegendSelect(id = "pca")
```

**Arguments**

`id`, `namespace id`

**Note**

```
getLegendSelect
```

**Examples**

```
x <- getLegendSelect("pca")
```

---

*getLevelOrder*                      *getLevelOrder*

---

**Description**

Generates the order of the overlapping points

**Usage**

```
getLevelOrder(Level = c("up", "down", "NS"))
```

**Arguments**

Level,                      factor levels shown in the legend

**Value**

order

**Note**

*getLevelOrder*

**Examples**

```
x <- getLevelOrder(c("up", "down", "GS", "NS"))
```

---

*getLoadingMsg*                      *getLoadingMsg*

---

**Description**

Creates and displays the loading message/gif to be displayed within the DEBrowser.

**Usage**

```
getLoadingMsg(output = NULL)
```

**Arguments**

output,                      output message

**Value**

loading msg

**Note**

getLoadingMsg

**Examples**

```
x <- getLoadingMsg()
```

---

getLogo

*getLogo*

---

**Description**

Generates and displays the logo to be shown within DEBbrowser.

**Usage**

```
getLogo()
```

**Value**

return logo

**Note**

getLogo

**Examples**

```
x <- getLogo()
```

---

|                           |                                  |
|---------------------------|----------------------------------|
| <code>getMainPanel</code> | <i><code>getMainPanel</code></i> |
|---------------------------|----------------------------------|

---

**Description**

main panel for volcano, scatter and maplot. Barplot and box plots are in this page as well.

**Usage**

```
getMainPanel()
```

**Value**

the panel for main plots;

**Note**

```
getMainPanel
```

**Examples**

```
x <- getMainPanel()
```

---

|                                   |  |
|-----------------------------------|--|
| <code>getMainPlotsLeftMenu</code> | <i><code>getMainPlotsLeftMenu</code></i> |
|-----------------------------------|--|

---

**Description**

Generates the Main Plots Left menu to be displayed within the DEBrowser.

**Usage**

```
getMainPlotsLeftMenu()
```

**Value**

returns the left menu according to the selected tab;

**Note**

```
getMainPlotsLeftMenu
```

**Examples**

```
x <- getMainPlotsLeftMenu()
```

---

|               |                      |
|---------------|----------------------|
| getMainPlotUI | <i>getMainPlotUI</i> |
|---------------|----------------------|

---

**Description**

main plot for volcano, scatter and maplot.

**Usage**

```
getMainPlotUI(id)
```

**Arguments**

id, namespace id

**Value**

the panel for main plots;

**Note**

```
getMainPlotUI
```

**Examples**

```
x <- getMainPlotUI("main")
```

---

|         |                |
|---------|----------------|
| getMean | <i>getMean</i> |
|---------|----------------|

---

**Description**

Gathers the mean for selected condition.

**Usage**

```
getMean(data = NULL, selcols = NULL)
```

**Arguments**

data, dataset  
selcols, input cols

**Value**

data

**Examples**

```
x <- getMean()
```

---

`getMergedComparison`     *getMergedComparison*

---

**Description**

Gathers the merged comparison data to be used within the DEBrowser.

**Usage**

```
getMergedComparison(dc = NULL, nc = NULL, input = NULL)
```

**Arguments**

|        |                           |
|--------|---------------------------|
| dc,    | data container            |
| nc,    | the number of comparisons |
| input, | input params              |

**Value**

data

**Examples**

```
x <- getMergedComparison()
```

---

`getMetaSelector`     *getMetaSelector*

---

**Description**

Return the sample selection box using meta data table

**Usage**

```
getMetaSelector(metadata = NULL, input = NULL, n = 0)
```

**Arguments**

|           |                 |
|-----------|-----------------|
| metadata, | meta data table |
| input,    | input params    |
| n,        | the box number  |

**Value**

meta select box

**Examples**

```
x<-getMetaSelector()
```

---

|                  |  |
|------------------|--|
| getMethodDetails | <i>get the detail boxes after DE method selected</i> |
|------------------|--|

---

**Description**

get the detail boxes after DE method selected

**Usage**

```
getMethodDetails(num = 0, input = NULL)
```

**Arguments**

|        |                                 |
|--------|---------------------------------|
| num,   | panel that is going to be shown |
| input, | user input                      |

**Examples**

```
x <- getMethodDetails()
```

---

|                   |                          |
|-------------------|--------------------------|
| getMostVariedList | <i>getMostVariedList</i> |
|-------------------|--------------------------|

---

**Description**

Calculates the most varied genes to be used for specific plots within the DEBrowser.

**Usage**

```
getMostVariedList(datavar = NULL, cols = NULL, input = NULL)
```

**Arguments**

|          |                  |
|----------|------------------|
| datavar, | loaded dataset   |
| cols,    | selected columns |
| input,   | input            |



**Value**

data

**Examples**

```
x <- getMostVariedList()
```

---

`getNormalizedMatrix`    *getNormalizedMatrix*

---

**Description**

Normalizes the matrix passed to be used within various methods within DEBrowser. Requires edgeR package

**Usage**

```
getNormalizedMatrix(M = NULL, method = "TMM")
```

**Arguments**

M,                    numeric matrix  
method,               normalization method for edgeR. default is TMM

**Value**

normalized matrix

**Note**

`getNormalizedMatrix`

**Examples**

```
x <- getNormalizedMatrix(mtcars)
```

---

|                          |                    |
|--------------------------|--------------------|
| <code>getOrganism</code> | <i>getOrganism</i> |
|--------------------------|--------------------|

---

**Description**

`getOrganism`

**Usage**

```
getOrganism(org)
```

**Arguments**

`org`, `organism`

**Value**

organism name for keg

**Note**

`getOrganism`

**Examples**

```
x <- getOrganism()
```

---

|                             |                       |
|-----------------------------|-----------------------|
| <code>getOrganismBox</code> | <i>getOrganismBox</i> |
|-----------------------------|-----------------------|

---

**Description**

Get the organism Box.

**Usage**

```
getOrganismBox()
```

**Value**

`selectInput`

**Note**

`getOrganismBox`  
`getOrganismBox` makes the organism box

**Examples**

```
x <- getOrganismBox()
```

---

getOrganismPathway     *getOrganismPathway*

---

**Description**

getOrganismPathway

**Usage**

```
getOrganismPathway(org)
```

**Arguments**

org,                    organism

**Value**

organism name for pathway

**Note**

getOrganismPathway

**Examples**

```
x <- getOrganismPathway()
```

---

getPCAcontolUpdatesJS     *getPCAcontolUpdatesJS in the prep menu we have two PCA plots to show how batch effect correction worked. One set of PCA input controls updates two PCA plots with this JS.*

---

**Description**

getPCAcontolUpdatesJS in the prep menu we have two PCA plots to show how batch effect correction worked. One set of PCA input controls updates two PCA plots with this JS.

**Usage**

```
getPCAcontolUpdatesJS()
```

**Value**

the JS for tab updates

**Examples**

```
x<- getTabUpdateJS()
```

---

|                 |                        |
|-----------------|------------------------|
| getPCAexplained | <i>getPCAexplained</i> |
|-----------------|------------------------|

---

**Description**

Creates a more detailed plot using the PCA results from the selected dataset.

**Usage**

```
getPCAexplained(datasetInput = NULL, pca_data = NULL, input = NULL)
```

**Arguments**

|               |               |
|---------------|---------------|
| datasetInput, | selected data |
| pca_data,     | from user     |
| input,        | input params  |

**Value**

explained plot

**Examples**

```
load(system.file("extdata", "demo", "demodata.Rda", package="debrowser"))
input<-c()
input$qcplot<-"pca"
input$col_list<-colnames(demodata[,1:6])
dat <- getNormalizedMatrix(demodata[,1:6])
pca_data <- run_pca(dat)
x <- getPCAexplained(dat, pca_data, input)
```

---

|              |                     |
|--------------|---------------------|
| getPCAPlotUI | <i>getPCAPlotUI</i> |
|--------------|---------------------|

---

**Description**

PCA plots UI.

**Usage**

```
getPCAPlotUI(id)
```

**Arguments**

id, namespace id

**Value**

the panel for PCA plots;

**Note**

getPCAPlotUI

**Examples**

```
x <- getPCAPlotUI("pca")
```

---

|                |                       |
|----------------|-----------------------|
| getPCselection | <i>getPCselection</i> |
|----------------|-----------------------|

---

**Description**

Generates the PC selection number to be used within DEBrowser.

**Usage**

```
getPCselection(id, num = 1, xy = "x")
```

**Arguments**

id, namespace id  
num, PC selection number  
xy, x or y coordinate

**Value**

PC selection for PCA analysis

**Note**

`getPCselection`

**Examples**

```
x <- getPCselection("pca")
```

---

`getPlotArea`

*getPlotArea*

---

**Description**

returns plot area either for `heatmaply` or `heatmap.2`

**Usage**

```
getPlotArea(input = NULL, session = NULL)
```

**Arguments**

`input`,           input variables  
`session`,         session

**Value**

`heatmaply/heatmap.2` plot area

**Examples**

```
x <- getPlotArea()
```

---

`getProgramTitle`      *getProgramTitle*

---

**Description**

Generates the title of the program to be displayed within DEBbrowser. If it is called in a program, the program title will be hidden

**Usage**

```
getProgramTitle(session = NULL)
```

**Arguments**

`session`,      session var

**Value**

program title

**Note**

```
getProgramTitle
```

**Examples**

```
title<-getProgramTitle()
```

---

`getQAText`      *getQAText Some questions and answers*

---

**Description**

`getQAText` Some questions and answers

**Usage**

```
getQAText()
```

**Value**

help text for QA

**Examples**

```
x<- getQAText()
```

getQCLeftMenu

*getQCLeftMenu*

---

**Description**

Generates the left menu to be used for QC plots within the DEBrowser.

**Usage**

```
getQCLeftMenu(input = NULL)
```

**Arguments**

input,           input values

**Value**

QC left menu

**Note**

getQCLeftMenu

**Examples**

```
x <- getQCLeftMenu()
```

---

getQCPanel

*getQCPanel*

---

**Description**

Gathers the conditional panel for QC plots

**Usage**

```
getQCPanel(input = NULL)
```

**Arguments**

input,           user input

**Value**

the panel for QC plots



**Note**

getQCSection

**Examples**

```
x <- getQCPanel()
```

---

getSampleDetails      *getSampleDetails*

---

**Description**

get sample details

**Usage**

```
getSampleDetails(output = NULL, summary = NULL, details = NULL, data = NULL)
```

**Arguments**

|          |                     |
|----------|---------------------|
| output,  | output              |
| summary, | summary output name |
| details, | details ouput name  |
| data,    | data                |

**Value**

panel

**Examples**

```
x <- getSampleDetails()
```

getSampleNames      *getSampleNames*

---

**Description**

Prepares initial samples to fill condition boxes. it reads the sample names from the data and splits into two.

**Usage**

```
getSampleNames(cnames = NULL, part = 1)
```

**Arguments**

cnames,              sample names in the header of a dataset  
part,                c(1,2). 1=first half and 2= second half

**Value**

sample names.

**Examples**

```
x<-getSampleNames()
```

---

getSamples            *getSamples*

---

**Description**

Gathers the sample names to be used within DEBrowser.

**Usage**

```
getSamples(cnames = NULL, index = 1)
```

**Arguments**

cnames,              names of the samples  
index,                starting column in a tab separated file

**Value**

choices

**Examples**

```
x <- getSamples()
```

---

*getSearchData*                      *getSearchData*

---

**Description**

search the geneset in the tables and return it

**Usage**

```
getSearchData(dat = NULL, input = NULL)
```

**Arguments**

dat,                      table data  
input,                    input params

**Value**

data

**Examples**

```
x <- getSearchData()
```

---

*getSelectedCols*                      *getSelectedCols*

---

**Description**

gets selected columns

**Usage**

```
getSelectedCols(data = NULL, datasetInput = NULL, input = NULL)
```

**Arguments**

data,                      all loaded data  
datasetInput,            selected dataset  
input,                    user input params

**Examples**

```
getSelectedCols()
```

---

```
getSelectedDatasetInput
```

```
getSelectedDatasetInput
```

---

**Description**

Gathers the user selected dataset output to be displayed.

**Usage**

```
getSelectedDatasetInput(  
  rdata = NULL,  
  getSelected = NULL,  
  getMostVaried = NULL,  
  mergedComparison = NULL,  
  input = NULL  
)
```

**Arguments**

|                                |                        |
|--------------------------------|------------------------|
| <code>rdata,</code>            | filtered dataset       |
| <code>getSelected,</code>      | selected data          |
| <code>getMostVaried,</code>    | most varied data       |
| <code>mergedComparison,</code> | merged comparison data |
| <code>input,</code>            | input parameters       |

**Value**

data

**Examples**

```
x <- getSelectedDatasetInput()
```

---

```
getSelectInputBox      getSelectInputBox
```

---

**Description**

Selects user input conditions to run in DESeq.

**Usage**

```
getSelectInputBox(
  id = NULL,
  name = NULL,
  num = 0,
  choices = NULL,
  selected = NULL,
  cw = 2
)
```

**Arguments**

|           |                                 |
|-----------|---------------------------------|
| id,       | input id                        |
| name,     | label of the box                |
| num,      | panel that is going to be shown |
| choices,  | sample list                     |
| selected, | selected smaple list            |
| cw,       | column width                    |

**Examples**

```
x <- getSelectInputBox()
```

---

```
getSelHeat      getSelHeat
```

---

**Description**

heatmap selection functionality

**Usage**

```
getSelHeat(expdata = NULL, input = NULL)
```

**Arguments**

expdata,        selected genes  
input,           input params

**Value**

plot

**Examples**

```
x <- getSelHeat()
```

---

getShapeColor        *getShapeColor*

---

**Description**

Generates the fill and shape selection boxes for PCA plots. metadata file has to be loaded in this case

**Usage**

```
getShapeColor(input = NULL)
```

**Arguments**

input,           input values

**Value**

Color and shape from selection boxes or defaults

**Examples**

```
x <- getShapeColor()
```

---

|                               |                         |
|-------------------------------|-------------------------|
| <code>getStartPlotsMsg</code> | <i>getStartPlotsMsg</i> |
|-------------------------------|-------------------------|

---

**Description**

Generates and displays the starting message to be shown once the user has first seen the main plots page within DEBrowser.

**Usage**

```
getStartPlotsMsg()
```

**Value**

return start plot msg

**Note**

```
getStartPlotsMsg
```

**Examples**

```
x <- getStartPlotsMsg()
```

---

|                            |                      |
|----------------------------|----------------------|
| <code>getStartupMsg</code> | <i>getStartupMsg</i> |
|----------------------------|----------------------|

---

**Description**

Generates and displays the starting message within DEBrowser.

**Usage**

```
getStartupMsg()
```

**Value**

return startup msg

**Note**

```
getStartupMsg
```

**Examples**

```
x <- getStartupMsg()
```

---

|                 |                        |
|-----------------|------------------------|
| getTableDetails | <i>getTableDetails</i> |
|-----------------|------------------------|

---

**Description**

get table details To be able to put a table into two lines are necessary; into the server part; getTableDetails(output, session, "dataname", data, modal=TRUE) into the ui part; uiOutput(ns("dataname"))

**Usage**

```
getTableDetails(  
  output = NULL,  
  session = NULL,  
  tablename = NULL,  
  data = NULL,  
  modal = NULL  
)
```

**Arguments**

|            |   |
|------------|---|
| output,    | output  |
| session,   | session   |
| tablename, | table name  |
| data,      | matrix data   |
| modal,     | if it is true, the matrix is going to be in a modal |

**Value**

panel

**Examples**

```
x <- getTableDetails()
```

---

|               |  |
|---------------|--|
| getTableModal | <i>getTableModal prepares table modal for KEGG</i> |
|---------------|--|

---

**Description**

getTableModal prepares table modal for KEGG

**Usage**

```
getTableModal()
```



**Value**

the info button

**Examples**

```
x<- getTableModal()
```

---

`getTableStyle`

*getTableStyle*

---

**Description**

User defined selection that selects the style of table to display within the DEBrowser.

**Usage**

```
getTableStyle(  
  dat = NULL,  
  input = NULL,  
  padj = c("padj"),  
  foldChange = c("foldChange"),  
  DEsection = TRUE  
)
```

**Arguments**

|                           |  |
|---------------------------|--|
| <code>dat</code> ,        | dataset  |
| <code>input</code> ,      | input params                                     |
| <code>padj</code> ,       | the name of the padj value column in the dataset |
| <code>foldChange</code> , | the name of the foldChange column in the dataset |
| <code>DEsection</code> ,  | if it is in DESection or not                     |

**Note**

`getTableStyle`

**Examples**

```
x <- getTableStyle()
```

---

|                |   |
|----------------|---|
| getTabUpdateJS | <i>getTabUpdateJS</i> prepmenu tab and discovery menu tab updates |
|----------------|---|

---

**Description**

getTabUpdateJS prepmenu tab and discovery menu tab updates

**Usage**

```
getTabUpdateJS()
```

**Value**

the JS for tab updates

**Examples**

```
x<- getTabUpdateJS()
```

---

|              |                     |
|--------------|---------------------|
| getTextOnOff | <i>getTextOnOff</i> |
|--------------|---------------------|

---

**Description**

text on PCA plot on and off

**Usage**

```
getTextOnOff(id = "pca")
```

**Arguments**

id, namespace id

**Note**

getTextOnOff

**Examples**

```
x <- getTextOnOff("pca")
```

---

|       |                                    |
|-------|------------------------------------|
| getUp | <i>getUp get up regulated data</i> |
|-------|------------------------------------|

---

**Description**

getUp get up regulated data

**Usage**

```
getUp(filt_data = NULL)
```

**Arguments**

filt\_data,      filt\_data

**Value**

data

**Examples**

```
x <- getUp()
```

---

|           |   |
|-----------|---|
| getUpDown | <i>getUpDown get up+down regulated data</i> |
|-----------|---|

---

**Description**

getUpDown get up+down regulated data

**Usage**

```
getUpDown(filt_data = NULL)
```

**Arguments**

filt\_data,      filt\_data

**Value**

data

**Examples**

```
x <- getUpDown()
```

---

```
getVariationData      getVariationData
```

---

**Description**

Adds an id to the data frame being used.

**Usage**

```
getVariationData(inputdata = NULL, cols = NULL, conds = NULL, key = NULL)
```

**Arguments**

|            |                     |
|------------|---------------------|
| inputdata, | dataset             |
| cols,      | columns             |
| conds,     | conditions          |
| key,       | gene or region name |

**Value**

plotdata

**Examples**

```
x <- getVariationData()
```

---

```
get_conditions_given_selection
      get_conditions_given_selection
```

---

**Description**

Return the two set of conditions given the selection of meta select box

**Usage**

```
get_conditions_given_selection(metadata = NULL, selection = NULL)
```

**Arguments**

|            |                 |
|------------|-----------------|
| metadata,  | meta data table |
| selection, | selection       |

**Value**

meta select box

**Examples**

```
x<-get_conditions_given_selection()
```

---

heatmapControlsUI      *heatmapControlsUI*

---

**Description**

Generates the left menu to be used for heatmap plots

**Usage**

```
heatmapControlsUI(id)
```

**Arguments**

id,                    module ID

**Value**

HeatmapControls

**Note**

heatmapControlsUI

**Examples**

```
x <- heatmapControlsUI("heatmap")
```

---

|               |                      |
|---------------|----------------------|
| heatmapJScore | <i>heatmapJScore</i> |
|---------------|----------------------|

---

**Description**

heatmap JS code for selection functionality

**Usage**

```
heatmapJScore()
```

**Value**

JS Code

**Examples**

```
x <- heatmapJScore()
```

---

|               |                      |
|---------------|----------------------|
| heatmapServer | <i>heatmapServer</i> |
|---------------|----------------------|

---

**Description**

Sets up shinyServer to be able to run heatmapServer interactively.

**Usage**

```
heatmapServer(input, output, session)
```

**Arguments**

|          |                      |
|----------|----------------------|
| input,   | input params from UI |
| output,  | output params to UI  |
| session, | session variable     |

**Value**

the panel for main plots;

**Note**

heatmapServer

**Examples**

```
heatmapServer
```

---

|           |                  |
|-----------|------------------|
| heatmapUI | <i>heatmapUI</i> |
|-----------|------------------|

---

**Description**

Creates a shinyUI to be able to run DEBrowser interactively.

**Usage**

```
heatmapUI(input, output, session)
```

**Arguments**

|          |                 |
|----------|-----------------|
| input,   | input variables |
| output,  | output objects  |
| session, | session         |

**Value**

the panel for heatmapUI;

**Note**

heatmapUI

**Examples**

```
x<-heatmapUI()
```

hideObj                    *hideObj*

---

**Description**

Hides a shiny object.

**Usage**

```
hideObj(btns = NULL)
```

**Arguments**

btns,                    hide group of objects with shinyjs

**Examples**

```
x <- hideObj()
```

---

histogramControlsUI    *histogramControlsUI*

---

**Description**

Generates the controls in the left menu for a histogram

**Usage**

```
histogramControlsUI(id)
```

**Arguments**

id,                    namespace id

**Value**

returns the left menu

**Note**

histogramControlsUI

**Examples**

```
x <- histogramControlsUI("histogram")
```



---

|             |                    |
|-------------|--------------------|
| installpack | <i>installpack</i> |
|-------------|--------------------|

---

**Description**

install packages if they don't exist display.

**Usage**

```
installpack(package_name = NULL)
```

**Arguments**

package\_name, package name to be installed

**Note**

installpack

**Examples**

```
x <- installpack()
```

---

|                   |                          |
|-------------------|--------------------------|
| IQRPlotControlsUI | <i>IQRPlotControlsUI</i> |
|-------------------|--------------------------|

---

**Description**

Generates the controls in the left menu for an IQR plot#'

**Usage**

```
IQRPlotControlsUI(id)
```

**Arguments**

id, namespace id

**Value**

returns the left menu

**Note**

IQRPlotControlsUI

**Examples**

```
x <- IQRPlotControlsUI("IQR")
```

---

|                  |                         |
|------------------|-------------------------|
| kmeansControlsUI | <i>kmeansControlsUI</i> |
|------------------|-------------------------|

---

**Description**

get kmeans controls

**Usage**

```
kmeansControlsUI(id)
```

**Arguments**

id,                    module ID

**Value**

controls

**Note**

kmeansControlsUI

**Examples**

```
x <- kmeansControlsUI("heatmap")
```

---

|             |                    |
|-------------|--------------------|
| lcfMetRadio | <i>lcfMetRadio</i> |
|-------------|--------------------|

---

**Description**

Radio buttons for low count removal methods

**Usage**

```
lcfMetRadio(id)
```

**Arguments**

id,                    namespace id

**Value**

radio control

**Note**

lcfMetRadio

**Examples**

```
x <- lcfMetRadio("lcf")
```

---

loadpack

*loadpack*

---

**Description**

load packages

**Usage**

```
loadpack(package_name = NULL)
```

**Arguments**

package\_name, package name to be loaded

**Note**

loadpack

**Examples**

```
x <- loadpack()
```

---

|                    |                           |
|--------------------|---------------------------|
| mainPlotControlsUI | <i>mainPlotControlsUI</i> |
|--------------------|---------------------------|

---

**Description**

Generates the left menu to be used for main plots

**Usage**

```
mainPlotControlsUI(id)
```

**Arguments**

|     |           |
|-----|-----------|
| id, | module ID |
|-----|-----------|

**Value**

mainPlotControls

**Note**

mainPlotControlsUI

**Examples**

```
x <- mainPlotControlsUI("main")
```

---

|                |                       |
|----------------|-----------------------|
| mainScatterNew | <i>mainScatterNew</i> |
|----------------|-----------------------|

---

**Description**

Creates the main scatter, volcano or MA plot to be displayed within the main panel.

**Usage**

```
mainScatterNew(input = NULL, data = NULL, source = NULL)
```

**Arguments**

|         |  |
|---------|--|
| input,  | input params   |
| data,   | dataframe that has log2FoldChange and log10padj values |
| source, | for event triggering to select genes                   |

**Value**

scatter, volcano or MA plot

**Examples**

```
x <- mainScatterNew()
```

---

niceKmeans

*niceKmeans*

---

**Description**

Generates hierarchially clustered K-means clusters

**Usage**

```
niceKmeans(df = NULL, input = NULL, iter.max = 1000, nstart = 100)
```

**Arguments**

|           |                                     |
|-----------|-------------------------------------|
| df,       | data                                |
| input,    | user inputs                         |
| iter.max, | max iteration for kmeans clustering |
| nstart,   | n for kmeans clustering             |

**Value**

heatmap plot area

**Note**

niceKmeans

**Examples**

```
x <- niceKmeans()
```

normalizationMethods *normalizationMethods*

---

**Description**

Select box to select normalization method prior to batch effect correction

**Usage**

```
normalizationMethods(id)
```

**Arguments**

id, namespace id

**Value**

radio control

**Note**

normalizationMethods

**Examples**

```
x <- normalizationMethods("batch")
```

---

palUI

*palUI*

---

**Description**

get pallete

**Usage**

```
palUI(id)
```

**Arguments**

id, namespace ID

**Value**

pals

**Note**

palUI

**Examples**

```
x <- palUI("heatmap")
```

---

`panel.cor`

*panel.cor*

---

**Description**

Prepares the correlations for the all2all plot.

**Usage**

```
panel.cor(x, y, prefix = "rho=", cex.cor = 2, ...)
```

**Arguments**

|                       |                       |
|-----------------------|-----------------------|
| <code>x,</code>       | numeric vector x      |
| <code>y,</code>       | numeric vector y      |
| <code>prefix,</code>  | prefix for the text   |
| <code>cex.cor,</code> | correlation font size |
| <code>...</code> ,    | additional parameters |

**Value**

all2all correlation plots

**Examples**

```
panel.cor(c(1,2,3), c(4,5,6))
```

panel.hist                    *panel.hist*

---

**Description**

Prepares the histogram for the all2all plot.

**Usage**

```
panel.hist(x, ...)
```

**Arguments**

x,                    a vector of values for which the histogram is desired  
...,                   any additional params

**Value**

all2all histogram plots

**Examples**

```
panel.hist(1)
```

---

pcaPlotControlsUI            *pcaPlotControlsUI*

---

**Description**

Generates the PCA Plots Left menu to be displayed within the DEBrowser.

**Usage**

```
pcaPlotControlsUI(id = "pca")
```

**Arguments**

id,                    namespace id

**Value**

returns the left menu according to the selected tab;

**Note**

pcaPlotControlsUI



**Examples**

```
x <- pcaPlotControlsUI("pca")
```

---

|                 |                 |
|-----------------|-----------------|
| <i>plotData</i> | <i>plotData</i> |
|-----------------|-----------------|

---

**Description**

prepare plot data for mainplots

**Usage**

```
plotData(pdata = NULL, input = NULL)
```

**Arguments**

|                |              |
|----------------|--------------|
| <i>pdata</i> , | <i>data</i>  |
| <i>input</i> , | <i>input</i> |

**Value**

*prepdata*

**Note**

*plotData*

**Examples**

```
x <- plotData()
```

---

|                      |                      |
|----------------------|----------------------|
| <i>plotMarginsUI</i> | <i>plotMarginsUI</i> |
|----------------------|----------------------|

---

**Description**

Margins module for plotly plots

**Usage**

```
plotMarginsUI(id, t = 20, b = 100, l = 100, r = 20)
```

**Arguments**

|                  |                 |
|------------------|-----------------|
| <code>id,</code> | <code>id</code> |
| <code>t,</code>  | top margin      |
| <code>b,</code>  | bottom margin   |
| <code>l,</code>  | left margin     |
| <code>r,</code>  | right margin    |

**Value**

size and margins controls

**Note**

`plotMarginsUI`

**Examples**

```
x <- plotMarginsUI("heatmap")
```

---

`plotSizeMarginsUI`      *plotSizeMarginsUI*

---

**Description**

Size and margins module for plotly plots

**Usage**

```
plotSizeMarginsUI(id, w = 800, h = 640, t = 20, b = 100, l = 100, r = 20)
```

**Arguments**

|                  |                 |
|------------------|-----------------|
| <code>id,</code> | <code>id</code> |
| <code>w,</code>  | width           |
| <code>h,</code>  | height          |
| <code>t,</code>  | top margin      |
| <code>b,</code>  | bottom margin   |
| <code>l,</code>  | left margin     |
| <code>r,</code>  | right margin    |

**Value**

size and margins controls

**Note**

`plotSizeMarginsUI`

**Examples**

```
x <- plotSizeMarginsUI("heatmap")
```

---

`plotSizeUI`

*plotSizeUI*

---

**Description**

Size module for plotly plots

**Usage**

```
plotSizeUI(id, w = 800, h = 600)
```

**Arguments**

|                  |                     |
|------------------|---------------------|
| <code>id,</code> | <code>id</code>     |
| <code>w,</code>  | <code>width</code>  |
| <code>h,</code>  | <code>height</code> |

**Value**

size and margins controls

**Note**

`plotSizeUI`

**Examples**

```
x <- plotSizeUI("heatmap")
```

---

|            |                   |
|------------|-------------------|
| plotTypeUI | <i>plotTypeUI</i> |
|------------|-------------------|

---

**Description**

Plot download type

**Usage**

```
plotTypeUI(id)
```

**Arguments**

id, id

**Value**

size and margins controls

**Note**

plotTypeUI

**Examples**

```
x <- plotTypeUI("heatmap")
```

---

|          |                 |
|----------|-----------------|
| plot_pca | <i>plot_pca</i> |
|----------|-----------------|

---

**Description**

Plots the PCA results for the selected dataset.

**Usage**

```
plot_pca(  
  dat = NULL,  
  pcx = 1,  
  pcy = 2,  
  metadata = NULL,  
  color = NULL,  
  shape = NULL,  
  size = NULL,  
  textonoff = "Off",  
  legendSelect = "samples",  
  input = NULL  
)
```

**Arguments**

|               |                  |
|---------------|------------------|
| dat,          | data             |
| pcx,          | x axis label     |
| pcy,          | y axis label     |
| metadata,     | additional data  |
| color,        | color for plot   |
| shape,        | shape for plot   |
| size,         | size of the plot |
| textonoff,    | text on off      |
| legendSelect, | select legend    |
| input,        | input param      |

**Value**

pca list

**Examples**

```
load(system.file("extdata", "demo", "demodata.Rda",
  package="debrowser"))
metadata<-cbind(colnames(demodata[,1:6]),
  colnames(demodata[,1:6]),
  c(rep("Cond1",3), rep("Cond2",3)))
colnames(metadata)<-c("samples", "color", "shape")

a <- plot_pca(getNormalizedMatrix(
  demodata[rowSums(demodata[,1:6])>10,1:6]),
  metadata = metadata, color = "samples",
  size = 5, shape = "shape")
```

---

prepDataContainer      *prepDataContainer*

---

**Description**

Prepares the data container that stores values used within DESeq.

**Usage**

```
prepDataContainer(data = NULL, counter = NULL, input = NULL)
```

**Arguments**

|          |                           |
|----------|---------------------------|
| data,    | loaded dataset            |
| counter, | the number of comparisons |
| input,   | input parameters          |

**Value**

data

**Examples**

```
x <- prepDataContainer()
```

---

prepDEOutput

*prepDEOutput*

---

**Description**

Prepares the output data from DE analysis to be used within DEBrowser

**Usage**

```
prepDEOutput(  
  data = NULL,  
  cols = NULL,  
  conds = NULL,  
  inputconds = NULL,  
  i = NULL,  
  input = NULL  
)
```

**Arguments**

|             |                            |
|-------------|----------------------------|
| data,       | loaded dataset             |
| cols,       | columns                    |
| conds,      | conds                      |
| inputconds, | inputconds                 |
| i,          | selected comparison number |
| input,      | input                      |

**Value**

data

**Examples**

```
x <- prepDEOutput()
```

---

prepGroup

*prepGroup*

---

**Description**

prepare group table

**Usage**

```
prepGroup(conds = NULL, cols = NULL)
```

**Arguments**

conds,           inputconds  
cols,            columns

**Value**

data

**Examples**

```
x <- prepGroup()
```

---

prepHeatData

*prepHeatData*

---

**Description**

scales the data

**Usage**

```
prepHeatData(expdata = NULL, input = NULL)
```

**Arguments**

expdata,           a matrixthat includes expression values  
input,            input variables

**Value**

heatdata

**Examples**

```
x <- prepHeatData()
```

---

```
prepPCADat
```

```
prepPCADat
```

---

**Description**

prepares pca data with metadata. If metadata doesn't exist it puts all the samples into a single group; "Conds".

**Usage**

```
prepPCADat(pca_data = NULL, metadata = NULL, input = NULL, pcx = 1, pcy = 2)
```

**Arguments**

|           |                      |
|-----------|----------------------|
| pca_data, | pca run results      |
| metadata, | additional meta data |
| input,    | input                |
| pcx,      | x axis label         |
| pcy,      | y axis label         |

**Value**

Color and shape from selection boxes or defaults

**Examples**

```
x <- prepPCADat()
```

---

```
push
```

```
push
```

---

**Description**

Push an object to the list.

**Usage**

```
push(1, ...)
```



**Arguments**

1,                   that are going to push to the list  
...,                 list object

**Value**

combined list

**Examples**

```
mylist <- list()  
newlist <- push ( 1, mylist )
```

---

*removeCols*                   *removeCols*

---

**Description**

remove unnecessary columns

**Usage**

```
removeCols(cols = NULL, dat = NULL)
```

**Arguments**

cols,                columns that are going to be removed from data frame  
dat,                 data

**Value**

data

**Examples**

```
x <- removeCols()
```

---

|                 |                        |
|-----------------|------------------------|
| removeExtraCols | <i>removeExtraCols</i> |
|-----------------|------------------------|

---

**Description**

remove extra columns for QC plots

**Usage**

```
removeExtraCols(dat = NULL)
```

**Arguments**

dat,                    selected data

**Examples**

```
removeExtraCols()
```

---

|            |                   |
|------------|-------------------|
| round_vals | <i>round_vals</i> |
|------------|-------------------|

---

**Description**

Plot PCA results.

**Usage**

```
round_vals(1)
```

**Arguments**

1,                    the value

**Value**

round value

**Examples**

```
x<-round_vals(5.1323223)
```

---

`runDE`*runDE*

---

**Description**

Run DE algorithms on the selected parameters. Output is to be used for the interactive display.

**Usage**

```
runDE(data = NULL, columns = NULL, conds = NULL, params = NULL)
```

**Arguments**

|                        |  |
|------------------------|--|
| <code>data</code> ,    | A matrix that includes all the expression raw counts, rownames has to be the gene, isoform or region names/IDs       |
| <code>columns</code> , | is a vector that includes the columns that are going to be analyzed. These columns has to match with the given data. |
| <code>conds</code> ,   | experimental conditions. The order has to match with the column order  |
| <code>params</code> ,  | all params for the DE methods  |

**Value**

de results

**Examples**

```
x <- runDE()
```

---

`runDESeq2`*runDESeq2*

---

**Description**

Run DESeq2 algorithm on the selected conditions. Output is to be used for the interactive display.

**Usage**

```
runDESeq2(data = NULL, columns = NULL, conds = NULL, params = NULL)
```

**Arguments**

|          |   |
|----------|---|
| data,    | A matrix that includes all the expression raw counts, rownames has to be the gene, isoform or region names/IDs  |
| columns, | is a vector that includes the columns that are going to be analyzed. These columns has to match with the given data.  |
| conds,   | experimental conditions. The order has to match with the column order   |
| params,  | fitType: either "parametric", "local", or "mean" for the type of fitting of dispersions to the mean intensity. See estimateDispersions for description. betaPrior: whether or not to put a zero-mean normal prior on the non-intercept coefficients. See nbinomWaldTest for description of the calculation of the beta prior. By default, the beta prior is used only for the Wald test, but can also be specified for the likelihood ratio test. testType: either "Wald" or "LRT", which will then use either Wald significance tests (defined by nbinomWaldTest), or the likelihood ratio test on the difference in deviance between a full and reduced model formula (defined by nbinomLRT) shrinkage: Adds shrunken log2 fold changes (LFC) and SE to a results table from DESeq run without LFC shrinkage. For consistency with results, the column name lfcSE is used here although what is returned is a posterior SD. Three shrinkage estimators for LFC are available via type (see the vignette for more details on the estimators). The apeglm publication demonstrates that 'apeglm' and 'ashr' outperform the original 'normal' shrinkage estimator. |

**Value**

deseq2 results

**Examples**

```
x <- runDESeq2()
```

---

runEdgeR

*runEdgeR*

---

**Description**

Run EdgeR algorithm on the selected conditions. Output is to be used for the interactive display.

**Usage**

```
runEdgeR(data = NULL, columns = NULL, conds = NULL, params = NULL)
```

**Arguments**

|          |  |
|----------|--|
| data,    | A matrix that includes all the expression raw counts, rownames has to be the gene, isoform or region names/IDs   |
| columns, | is a vector that includes the columns that are going to be analyzed. These columns has to match with the given data.   |
| conds,   | experimental conditions. The order has to match with the column order  |
| params,  | normfact: Calculate normalization factors to scale the raw library sizes. Values can be "TMM", "RLE", "upperquartile", "none". dispersion: either a numeric vector of dispersions or a character string indicating that dispersions should be taken from the data object. If a numeric vector, then can be either of length one or of length equal to the number of genes. Allowable character values are "common", "trended", "tagwise" or "auto". Default behavior ("auto" is to use most complex dispersions found in data object. testType: exactTest or glmLRT. exactTest: Computes p-values for differential abundance for each gene between two digital libraries, conditioning on the total count for each gene. The counts in each group as a proportion of the whole are assumed to follow a binomial distribution. glmLRT: Fit a negative binomial generalized log-linear model to the read counts for each gene. Conduct genewise statistical tests for a given coefficient or coefficient contrast. |

**Value**

edgeR results

**Examples**

```
x <- runEdgeR()
```

---

runHeatmap

*runHeatmap*

---

**Description**

Creates a heatmap based on the user selected parameters within shiny

**Usage**

```
runHeatmap(input = NULL, session = NULL, expdata = NULL)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| session, | session                                  |
| expdata, | a matrix that includes expression values |

**Value**

heatmapply plot

**Examples**

```
x <- runHeatmap()
```

---

runHeatmap2

*runHeatmap2*

---

**Description**

Creates a heatmap based on the user selected parameters within shiny

**Usage**

```
runHeatmap2(input = NULL, session = NULL, expdata = NULL)
```

**Arguments**

|          |  |
|----------|--|
| input,   | input variables                          |
| session, | session                                  |
| expdata, | a matrix that includes expression values |

**Value**

heatmap.2

**Examples**

```
x <- runHeatmap2()
```

---

runLimma

*runLimma*


---

**Description**

Run Limma algorithm on the selected conditions. Output is to be used for the interactive display.

**Usage**

```
runLimma(data = NULL, columns = NULL, conds = NULL, params = NULL)
```

**Arguments**

|          |  |
|----------|--|
| data,    | A matrix that includes all the expression raw counts, rownames has to be the gene, isoform or region names/IDs   |
| columns, | is a vector that includes the columns that are going to be analyzed. These columns has to match with the given data.   |
| conds,   | experimental conditions. The order has to match with the column order  |
| params,  | normfact: Calculate normalization factors to scale the raw library sizes. Values can be "TMM", "RLE", "upperquartile", "none". fitType, fitting method; "ls" for least squares or "robust" for robust regression normBet: Normalizes expression intensities so that the intensities or log-ratios have similar distributions across a set of arrays. |

**Value**

Limma results

**Examples**

```
x <- runLimma()
```

---

run\_pca

*run\_pca*


---

**Description**

Runs PCA on the selected dataset.

**Usage**

```
run_pca(x = NULL, retx = TRUE, center = TRUE, scale = TRUE)
```

**Arguments**

x,                    dataframe with experiment data  
 retx,                specifies if the data should be returned  
 center,              center the PCA (Boolean)  
 scale,                scale the PCA (Boolean)

**Value**

pca list

**Examples**

```

load(system.file("extdata", "demo", "demodata.Rda",
  package="debrowser"))
pca_data<-run_pca(getNormalizedMatrix(
  demodata[rowSums(demodata[,1:6])>10,1:6]))

```

---

selectConditions            *selectConditions*

---

**Description**

Selects user input conditions, multiple if present, to be used in DESeq.

**Usage**

```

selectConditions(
  Dataset = NULL,
  metadata = NULL,
  choicecounter = NULL,
  session = NULL,
  input = NULL
)

```

**Arguments**

Dataset,            used dataset  
 metadata,          metadatatable to select from metadata  
 choicecounter,     choicecounter to add multiple comparisons  
 session,            session  
 input,              input params

**Value**

the panel for go plots;



**Note**

selectConditions

**Examples**

```
x<- selectConditions()
```

---

|               |                      |
|---------------|----------------------|
| selectedInput | <i>selectedInput</i> |
|---------------|----------------------|

---

**Description**

Selects user input conditions to run in DESeq.

**Usage**

```
selectedInput(id = NULL, num = 0, default = NULL, input = NULL)
```

**Arguments**

|          |                                 |
|----------|---------------------------------|
| id,      | input id                        |
| num,     | panel that is going to be shown |
| default, | default text                    |
| input,   | input params                    |

**Examples**

```
x <- selectedInput()
```

---

|                 |                        |
|-----------------|------------------------|
| selectGroupInfo | <i>selectGroupInfo</i> |
|-----------------|------------------------|

---

**Description**

Group info column selection. This can be used in batch effect or coloring the groups in the plots.

**Usage**

```
selectGroupInfo(  
  metadata = NULL,  
  input = NULL,  
  selectname = "groupselect",  
  label = "Group info"  
)
```

**Arguments**

|             |                         |
|-------------|-------------------------|
| metadata,   | metadata                |
| input,      | input values            |
| selectname, | name of the select box  |
| label,      | label of the select box |

**Note**

selectGroupInfo

**Examples**

```
x <- selectGroupInfo()
```

---

sepRadio

*sepRadio*

---

**Description**

Radio button for separators

**Usage**

```
sepRadio(id, name)
```

**Arguments**

|       |           |
|-------|-----------|
| id,   | module id |
| name, | name      |

**Value**

radio control

**Note**

sepRadio

**Examples**

```
x <- sepRadio("meta", "metadata")
```

---

|          |  |
|----------|--|
| setBatch | <i>setBatch to skip batch effect correction batch variable set with the filter results</i> |
|----------|--|

---

**Description**

setBatch to skip batch effect correction batch variable set with the filter results

**Usage**

```
setBatch(fd = NULL)
```

**Arguments**

fd,                    filtered data

**Value**

fd data

**Examples**

```
x <- setBatch()
```

---

|         |                |
|---------|----------------|
| showObj | <i>showObj</i> |
|---------|----------------|

---

**Description**

Displays a shiny object.

**Usage**

```
showObj(btns = NULL)
```

**Arguments**

btns,                    show group of objects with shinyjs

**Examples**

```
x <- showObj()
```

---

|                |                       |
|----------------|-----------------------|
| startDEBrowser | <i>startDEBrowser</i> |
|----------------|-----------------------|

---

**Description**

Starts the DEBrowser to be able to run interactively.

**Usage**

```
startDEBrowser()
```

**Value**

the app

**Note**

```
startDEBrowser
```

**Examples**

```
startDEBrowser()
```

---

|              |                     |
|--------------|---------------------|
| startHeatmap | <i>startHeatmap</i> |
|--------------|---------------------|

---

**Description**

Starts the DEBrowser heatmap

**Usage**

```
startHeatmap()
```

**Value**

the app

**Note**

```
startHeatmap
```

**Examples**

```
startHeatmap()
```

textareaInput                      *textareaInput*

**Description**

Generates a text area input to be used for gene selection within the DEBrowser.

**Usage**

```
textareaInput(id, label, value, rows = 20, cols = 35, class = "form-control")
```

**Arguments**

|        |                      |
|--------|----------------------|
| id,    | id of the control    |
| label, | label of the control |
| value, | initial value        |
| rows,  | the # of rows        |
| cols,  | the # of cols        |
| class, | css class            |

**Examples**

```
x <- textareaInput("genesetarea", "Gene Set",
  "Fgf21", rows = 5, cols = 35)
```

togglePanels                      *togglePanels*

**Description**

User defined toggle to display which panels are to be shown within DEBrowser.

**Usage**

```
togglePanels(num = NULL, nums = NULL, session = NULL)
```

**Arguments**

|          |                |
|----------|----------------|
| num,     | selected panel |
| nums,    | all panels     |
| session, | session info   |

**Note**

```
togglePanels
```

**Examples**

```
x <- togglePanels()
```

# Index

actionButtonDE, 6  
addDataCols, 7  
addID, 8  
all2all, 8  
all2allControlsUI, 9  
applyFilters, 9  
applyFiltersNew, 10  
applyFiltersToMergedComparison, 10  
  
barMainPlotControlsUI, 11  
batchEffectUI, 12  
batchMethod, 12  
BoxMainPlotControlsUI, 13  
  
changeClusterOrder, 13  
checkCountData, 14  
checkMetaData, 15  
clusterData, 15  
clustFunParamsUI, 16  
compareClust, 16  
condSelectUI, 17  
correctCombat, 18  
correctHarman, 18  
customColorsUI, 19  
cutOffSelectionUI, 19  
  
dataLCFUI, 20  
dataLoadUI, 21  
debrowserall2all, 21  
debrowserbarmainplot, 22  
debrowserbatcheffect, 23  
debrowserboxmainplot, 23  
debrowsercondselect, 24  
debrowserdataload, 25  
debrowserdeanalysis, 26  
debrowserdensityplot, 27  
debrowserheatmap, 27  
debrowserhistogram, 28  
debrowserIQRplot, 29  
debrowserlowcountfilter, 29  
  
debrowsermainplot, 30  
debrowserpcaplot, 31  
dendControlsUI, 31  
densityPlotControlsUI, 32  
deServer, 33  
deUI, 33  
distFunParamsUI, 34  
drawKEGG, 34  
drawPCAExplained, 35  
  
fileTypes, 36  
fileUploadBox, 36  
  
generateTestData, 37  
get\_conditions\_given\_selection, 92  
getAfterLoadMsg, 37  
getAll2AllPlotUI, 38  
getBarMainPlot, 39  
getBarMainPlotUI, 39  
getBoxMainPlot, 40  
getBoxMainPlotUI, 41  
getBSTableUI, 41  
getColors, 42  
getColorShapeSelection, 43  
getCompSelection, 43  
getConditionSelector, 44  
getConditionSelectorFromMeta, 44  
getCondMsg, 45  
getCutOffSelection, 46  
getDataAssesmentText, 46  
getDataForTables, 47  
getDataPreparationText, 48  
getDEAnalysisText, 48  
getDensityPlot, 49  
getDensityPlotUI, 49  
getDEResultsUI, 50  
getDomains, 50  
getDown, 51  
getDownloadSection, 51  
getEnrichDO, 52

getEnrichGO, 53  
getEnrichKEGG, 54  
getEntrezIds, 54  
getEntrezTable, 55  
getGeneList, 56  
getGeneSetData, 57  
getGOLeftMenu, 57  
getGoPanel, 58  
getGOPlots, 58  
getGSEA, 59  
getHeatmapUI, 60  
getHelpButton, 60  
getHideLegendOnOff, 61  
getHistogramUI, 61  
getIntroText, 62  
getIQRPlot, 62  
getIQRPlotUI, 63  
getJSLine, 63  
getKEGGModal, 64  
getLeftMenu, 64  
getLegendColors, 65  
getLegendRadio, 66  
getLegendSelect, 66  
getLevelOrder, 67  
getLoadingMsg, 67  
getLogo, 68  
getMainPanel, 69  
getMainPlotsLeftMenu, 69  
getMainPlotUI, 70  
getMean, 70  
getMergedComparison, 71  
getMetaSelector, 71  
getMethodDetails, 72  
getMostVariedList, 72  
getNormalizedMatrix, 73  
getOrganism, 74  
getOrganismBox, 74  
getOrganismPathway, 75  
getPCAcontolUpdatesJS, 75  
getPCAexplained, 76  
getPCAPlotUI, 77  
getPCselection, 77  
getPlotArea, 78  
getProgramTitle, 79  
getQAText, 79  
getQCLeftMenu, 80  
getQCPanel, 80  
getSampleDetails, 81  
getSampleNames, 82  
getSamples, 82  
getSearchData, 83  
getSelectedCols, 83  
getSelectedDatasetInput, 84  
getSelectInputBox, 85  
getSelHeat, 85  
getShapeColor, 86  
getStartPlotsMsg, 87  
getStartupMsg, 87  
getTableDetails, 88  
getTableModal, 88  
getTableStyle, 89  
getTabUpdateJS, 90  
getTextOnOff, 90  
getUp, 91  
getUpDown, 91  
getVariationData, 92  
heatmapControlsUI, 93  
heatmapJScore, 94  
heatmapServer, 94  
heatmapUI, 95  
hideObj, 96  
histogramControlsUI, 96  
installpack, 97  
IQRPlotControlsUI, 97  
kmeansControlsUI, 98  
lcfMetRadio, 98  
loadpack, 99  
mainPlotControlsUI, 100  
mainScatterNew, 100  
niceKmeans, 101  
normalizationMethods, 102  
palUI, 102  
panel.cor, 103  
panel.hist, 104  
pcaPlotControlsUI, 104  
plot\_pca, 108  
plotData, 105  
plotMarginsUI, 105  
plotSizeMarginsUI, 106  
plotSizeUI, 107  
plotTypeUI, 108



prepDataContainer, 109  
prepDEOutput, 110  
prepGroup, 111  
prepHeatData, 111  
prepPCADat, 112  
push, 112

removeCols, 113  
removeExtraCols, 114  
round\_vals, 114  
run\_pca, 119  
runDE, 115  
runDESeq2, 115  
runEdgeR, 116  
runHeatmap, 117  
runHeatmap2, 118  
runLimma, 119

selectConditions, 120  
selectedInput, 121  
selectGroupInfo, 121  
sepRadio, 122  
setBatch, 123  
showObj, 123  
startDEBrowser, 124  
startHeatmap, 124

textareaInput, 125  
togglePanels, 125