

Package ‘pkgDepTools’

April 12, 2018

Type Package

Title Package Dependency Tools

Version 1.44.0

Author Seth Falcon

Maintainer Seth Falcon <seth@userprimary.net>

Description This package provides tools for computing and analyzing dependency relationships among R packages. It provides tools for building a graph-based representation of the dependencies among all packages in a list of CRAN-style package repositories. There are also utilities for computing installation order of a given package. If the RCurl package is available, an estimate of the download size required to install a given package and its dependencies can be obtained.

License GPL-2

Depends methods, graph, RBGL

Imports graph, RBGL

Suggests Biobase, Rgraphviz, RCurl, BiocInstaller

LazyLoad Yes

biocViews Infrastructure, GraphAndNetwork

NeedsCompilation no

R topics documented:

pkgDepTools-package	2
basicInstallOrder	2
cleanPkgField	3
getDownloadSize	3
getInstallOrder	4
makeDepGraph	4
makePkgUrl	5
parseContentLength	6

Index	7
--------------	----------

pkgDepTools-package *Package Dependency Tools*

Description

This package provides tools for computing and analyzing dependency relationships among R packages. It provides tools for building a graph-based representation of the dependencies among all packages in a list of CRAN-style package repositories. There are also utilities for computing installation order of a given package. If the RCurl package is available, an estimate of the download size required to install a given package and its dependencies can be obtained.

Details

Package: pkgDepTools
Type: Package
License: GPL2

Author(s)

Seth Falcon Maintainer: Seth Falcon <sfalcon@fhcrc.org>

basicInstallOrder *Complete Installation Order of a Given Package*

Description

Helper function to return the complete install order of a given package.

Usage

```
basicInstallOrder(pkg, depG)
```

Arguments

pkg character string package name
depG graphNEL instance as returned by makeDepGraph

Details

Internal function.

Value

character vector of package names in a viable installation order.

Author(s)

Seth Falcon

cleanPkgField	<i>Clean Packages Names from a DESCRIPTION File Field</i>
---------------	---

Description

Given the value from a field like 'Depends' in a package's DESCRIPTION file, return a character vector of package names with the version restrictions stripped and R removed.

Usage

```
cleanPkgField(val)
```

Arguments

val	character string parsed from a package's DESCRIPTION file containing package names and possible version specifiers.
-----	---

Details

Internal function

Warning

FIXME: uses a private function from tools

Author(s)

Seth Falcon

getDownloadSize	<i>Get Size in MB of a URL Using RCurl</i>
-----------------	--

Description

Returns the size in MB of the specified URL. Uses RCurl to parse the HTTP headers for Content-Length.

Usage

```
getDownloadSize(url)
```

Arguments

url	character vector giving the URL. This is not vectorized.
-----	--

Note

Internal function.

Author(s)

Seth Falcon

`getInstallOrder` *List package dependencies in install order*

Description

This function uses a dependency graph created with `makeDepGraph` to list all (recursive) dependencies of a given package in an order suitable for installation.

Usage

```
getInstallOrder(pkg, depG, needed.only = TRUE)
```

Arguments

<code>pkg</code>	character string name of package
<code>depG</code>	graphNEL instance as returned from <code>makeDepGraph</code> .
<code>needed.only</code>	logical value. When TRUE, only those dependencies not currently installed are included in the list, this is the default. When FALSE the complete list of dependencies is given regardless of the set of currently installed packages.

Value

a list with components:

<code>packages</code>	character vector of package names in an order suitable for installation. The order is not unique. The names of the character vector are the estimated download sizes of each package.
<code>total.size</code>	When available, the total size in megabytes of all listed dependencies.

Author(s)

Seth Falcon

`makeDepGraph` *Create a graph representing R package dependencies*

Description

Given a list of CRAN-style repository URLs, this function creates a graph instance representing dependencies between packages in the repositories.

Usage

```
makeDepGraph(repList, suggests.only = FALSE, type =
getOption("pkgType"), keep.builtin = FALSE, dosize = TRUE)
```

Arguments

replList	a character vector of URLs pointing to CRAN-style repositories.
suggests.only	logical value indicating whether only the "Suggests" field should be used. The default (FALSE) means that DESCRIPTION fields "Depends" and "Imports" are used. Note that "Suggests" is special in that its use is less regulated and the resulting graph is less likely to be a DAG (packages sometimes suggest each other).
type	a character vector specifying the type of packages to search for in the repositories. Must be one of "source", "win.binary", or "mac.binary".
keep.builtin	logical value indicating whether or not packages that come with a default R installation should be included in the nodes of the dependency graph. The default, FALSE, is to remove these packages from the return result.
dosize	logical value. When TRUE, the function will attempt to estimate the download size of each package (requires the RCurl package). The size of each package is added as a node attribute to the graph.

Value

A graphNEL-class instance. If the dosize argument was set to TRUE, then an estimate of the download size of each package is stored as a node attribute of the graph. A missing value is used when the download size was not able to be determined as well as when the RCurl package is not available.

Author(s)

Seth Falcon

Examples

```
## Not run:
  deps <- makeDepGraph("http://cran.fhcrc.org", type="source")

## End(Not run)
```

makePkgUrl

Create a URL for a Package in a CRAN-Style Repository

Description

Given a CRAN-style package repository meta data matrix as returned by available.packages, return a character vector of complete URLs for each package.

Usage

```
makePkgUrl(pMat, type = getOption("pkgType"))
```

Arguments

pMat	matrix as returned by available.packages
type	character string, used to determine file extension. Should match the argument used to generate pMat.

Details

Internal function.

Author(s)

Seth Falcon

parseContentLength *Parse HTTP Response Header for Content Length*

Description

Given a string containing an HTTP response header, extract the "Content-Length" header and convert it to a numeric value. If no such header is found, return NA.

Usage

```
parseContentLength(h)
```

Arguments

h string containing the HTTP response header

Details

Internal function

Author(s)

Seth Falcon

Index

*Topic **package**

pkgDepTools-package, 2

*Topic **utilities**

basicInstallOrder, 2

cleanPkgField, 3

getDownloadSize, 3

getInstallOrder, 4

makeDepGraph, 4

makePkgUrl, 5

parseContentLength, 6

basicInstallOrder, 2

cleanPkgField, 3

getDownloadSize, 3

getInstallOrder, 4

makeDepGraph, 4

makePkgUrl, 5

parseContentLength, 6

pkgDepTools (pkgDepTools-package), 2

pkgDepTools-package, 2