

# Package ‘UNDO’

October 16, 2019

**Type** Package

**Title** Unsupervised Deconvolution of Tumor-Stromal Mixed Expressions

**Version** 1.26.0

**Date** 2014-07-17

**Author** Niya Wang <wangny@vt.edu>

**Maintainer** Niya Wang <wangny@vt.edu>

**Depends** R (>= 2.15.2), methods, BiocGenerics, Biobase

**Imports** MASS, boot, nnls, stats, utils

**biocViews** Software

**Description** UNDO is an R package for unsupervised deconvolution of tumor and stromal mixed expression data. It detects marker genes and deconvolutes the mixing expression data without any prior knowledge.

**License** GPL-2

**git\_url** <https://git.bioconductor.org/packages/UNDO>

**git\_branch** RELEASE\_3\_9

**git\_last\_commit** bedc721

**git\_last\_commit\_date** 2019-05-02

**Date/Publication** 2019-10-15

## R topics documented:

UNDO-package . . . . .	2
BiologicalMixMCF7HS27 . . . . .	2
calc_E1 . . . . .	3
dimension_reduction . . . . .	4
gene_expression_input . . . . .	4
marker_gene_selection . . . . .	5
mixing_matrix_computation . . . . .	6
NumericalMixingMatrix . . . . .	7
NumericalMixMCF7HS27 . . . . .	7
PureMCF7HS27 . . . . .	8
two_source_deconv . . . . .	9

<b>Index</b>	<b>10</b>
--------------	-----------

---

UNDO-package	<i>Implementation of UNDO (unsupervised deconvolution of tumor-stromal mixed expressions)</i>
--------------	---

---

## Description

This package contains main function "two\_source\_deconv" to implement the deconvolution of mixed tumor-stromal expressions in a completely unsupervised way. The prior knowledge of mixing matrix or pure expression is not needed. The package detects marker genes and calculate the mixing matrix and pure expressions automatically.

## Details

Package: UNDO  
 Type: Package  
 Version: 1.7.3  
 Date: 2014-04-30  
 License: GPL version 2 or later

```
two_source_deconv(ExpressionData,lowper=0.4,highper=0.1,epsilon1=0.01,epsilon2=0.01,A=NULL,S1=NULL,S2=N
```

## Author(s)

Niya Wang <wangny@vt.edu>

## Examples

```
data(NumericalMixMCF7HS27)
X <- NumericalMixMCF7HS27
deconvResult <- two_source_deconv(X, lowper = 0.4, highper = 0.1, epsilon1 = 0.1, epsilon2 = 0.1, A = NULL, S1=N
```

---

BiologicalMixMCF7HS27 *MCF7 and HS27 biologically mixed*

---

## Description

Expression data from MCF7 and HS27 biologically mixing

## Usage

```
data(BiologicalMixMCF7HS27)
```

## Format

The format is: Formal class 'ExpressionSet' [package "Biobase"] with 7 slots ..@ experimentData :Formal class 'MIAME' [package "Biobase"] with 13 slots .. ..@ name : chr "" .. ..@ lab : chr "" .. ..@ contact : chr "" .. ..@ title : chr "" .. ..@ abstract : chr "" .. ..@ url : chr "" .. ..@ pubMedIds : chr "" .. ..@ samples : list() .. ..@ hybridizations : list() .. ..@ normControls

```

: list() .. .. @ preprocessing : list() .. .. @ other : list() .. .. @ __classVersion__:Formal
class 'Versions' [package "Biobase"] with 1 slots .. .. @ .Data:List of 2 .. .. @ int
[1:3] 1 0 0 .. .. @ int [1:3] 1 1 0 .. @ assayData :<environment: 0x0000000008d92618>
.. @ phenoData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots .. .. @
varMetadata :'data.frame': 0 obs. of 1 variable: .. .. @ labelDescription: chr(0) .. .. @ data
:'data.frame': 2 obs. of 0 variables .. .. @ dimLabels : chr [1:2] "sampleNames" "sampleColumns"
.. .. @ __classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots .. .. @
.Data:List of 1 .. .. @ int [1:3] 1 1 0 .. @ featureData :Formal class 'AnnotatedDataFrame'
[package "Biobase"] with 4 slots .. .. @ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..
.. @ labelDescription: chr(0) .. .. @ data :'data.frame': 22215 obs. of 0 variables .. .. @
dimLabels : chr [1:2] "featureNames" "featureColumns" .. .. @ __classVersion__:Formal class
'Versions' [package "Biobase"] with 1 slots .. .. @ .Data:List of 1 .. .. @ int [1:3]
1 1 0 .. @ annotation : chr "HG-U133A" .. @ protocolData :Formal class 'AnnotatedDataFrame'
[package "Biobase"] with 4 slots .. .. @ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..
.. @ labelDescription: chr(0) .. .. @ data :'data.frame': 2 obs. of 0 variables .. .. @ dimLabels
: chr [1:2] "sampleNames" "sampleColumns" .. .. @ __classVersion__:Formal class 'Versions'
[package "Biobase"] with 1 slots .. .. @ .Data:List of 1 .. .. @ int [1:3] 1 1 0 .. @
__classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots .. .. @ .Data:List of 4
.. .. @ int [1:3] 3 1 0 .. .. @ int [1:3] 2 23 6 .. .. @ int [1:3] 1 3 0 .. .. @ int [1:3] 1 0
0

```

## Examples

```

data(BiologicalMixMCF7HS27)
str(BiologicalMixMCF7HS27)

```

---

calc\_E1

*function calculating the E1 measurement*

---

## Description

A function used to calculate the E1 measurement when the real mixing matrix is provided

## Usage

```
calc_E1(A, Aest)
```

## Arguments

A	real mixing matrix
Aest	estimated mixing matrix

## Value

E1 measurement (numeric)

## Author(s)

Niya Wang <wangny@vt.edu>

**Examples**

```
A <- matrix(runif(4),2,2)
Aest <- matrix(runif(4),2,2)
E1 <- calc_E1(A,Aest) # to calculate the similarity of two random 2*2 matrix
```

---

dimension\_reduction    *Dimension reduction function*

---

**Description**

When the number of input samples is larger than 2, this function is called to reduce the dimension to 2 by using PCA.

**Usage**

```
dimension_reduction(X)
```

**Arguments**

X                    gene expression data matrix

**Value**

X  
dimenMatrix        the dimension reduction matrix used to recover the mixing matrix for all the samples

**Author(s)**

Niya Wang (wangny@vt.edu)

**Examples**

```
X <- matrix(runif(5000),1000,5)
dimenResult <- dimension_reduction(X)
```

---

gene\_expression\_input    *Detect whether the input gene expression data are valid*

---

**Description**

Check the input gene expression data to see whether they are nonempty, nonnegative, etc.

**Usage**

```
gene_expression_input(X)
```

**Arguments**

X                      gene expression data matrix with row representing genes/probe sets, and column representing samples.

**Value**

If the input is valid, the output will be the same as the input; otherwise, if the input contains NA, the corresponding rows will be deleted. if the input contains negative value, the algorithm will stop and give error information.

**Author(s)**

Niya Wang (wangny@vt.edu)

**Examples**

```
gene_expression <- matrix(runif(2000),1000,2)
valid_gene_expression <- gene_expression_input(gene_expression)
```

---

marker\_gene\_selection    *Select marker genes in two sources*

---

**Description**

Select the marker genes in tumor and stroma in an unsupervised way

**Usage**

```
marker_gene_selection(X, lower, higher, epsilon1, epsilon2)
```

**Arguments**

X                      gene expression data

lower                  The percentage of genes the user wants to remove with lowest norm. The range should be between 0 and 1.

higher                 The percentage of genes the user wants to remove with highest norm. The range should be between 0 and 1.

epsilon1                Influence the number of marker genes. With increasing of epsilon1, the number marker genes in source 1 will increase. The value should be positive.

epsilon2                Influence the number of marker genes. With increasing of epsilon1, the number marker genes in source 2 will increase. The value should be positive.

**Value**

a1                      The slope of marker genes in source 1

a2                      The slope of marker genes in source 2

MG1                    The gene list of marker genes in source 1

MG2                    The gene list of marker genes in source 2

dimenMatrix            dimension reduction matrix

**Author(s)**

Niya Wang (wangny@vt.edu)

**Examples**

```
X <- matrix(runif(20000),10000,2)
MG_set <- marker_gene_selection(X, 0.4, 0.1, 0.1, 0.1)
```

---

mixing\_matrix\_computation

*Calculate and scale the mixing matrix*

---

**Description**

Calculate the mixing matrix based on the output from `marker_gene_selection()`, and scale the mixing matrix to make the sum of proportions from tumor and stroma equal to 1. The pure expression levels of tumor and stroma are also computed.

**Usage**

```
mixing_matrix_computation(X, a1, a2, dimenMatrix)
```

**Arguments**

<code>X</code>	Gene expression data matrix
<code>a1</code>	The slope of marker genes in source 1
<code>a2</code>	The slope of marker genes in source 2
<code>dimenMatrix</code>	The dimension reduction matrix used to recover mixing matrix for all the samples

**Value**

<code>Aest</code>	estimated mixing matrix
<code>Sest</code>	estimated pure gene expression of two sources

**Author(s)**

Niya Wang (wangny@vt.edu)

**Examples**

```
a1<- matrix(runif(2),2,1)
a2<- matrix(runif(2),2,1)
X <- 1000*matrix(runif(20000),10000,2)
dimenMatrix <- NULL
Deconv <- mixing_matrix_computation(X, a1, a2, dimenMatrix)
```

---

NumericalMixingMatrix *mixing matrix of data NumericalMixMCF7HS27*

---

**Description**

real mixing matrix of data NumericalMixMCF7HS27

**Usage**

```
data(NumericalMixingMatrix)
```

**Format**

The format is: num [1:2, 1:2] 0.775 0.15 0.225 0.85 - attr(\*, "dimnames")=List of 2 ..\$ : NULL ..\$ : chr [1:2] "V1" "V2"

**Examples**

```
data(NumericalMixingMatrix)
str(NumericalMixingMatrix)
```

---

NumericalMixMCF7HS27 *MCF7 and HS27 numerically mixed*

---

**Description**

Expression data from MCF7 and HS27 numerically mixing

**Usage**

```
data(NumericalMixMCF7HS27)
```

**Format**

The format is: Formal class 'ExpressionSet' [package "Biobase"] with 7 slots ..@ experimentData :Formal class 'MIAME' [package "Biobase"] with 13 slots .. ..@ name : chr "" .. ..@ lab : chr "" .. ..@ contact : chr "" .. ..@ title : chr "" .. ..@ abstract : chr "" .. ..@ url : chr "" .. ..@ pubMedIds : chr "" .. ..@ samples : list() .. ..@ hybridizations : list() .. ..@ normControls : list() .. ..@ preprocessing : list() .. ..@ other : list() .. ..@ .\_\_classVersion\_\_:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 2 .. ..@ .Data:List of 1 [1:3] 1 0 0 .. ..@ .Data:List of 1 [1:3] 1 1 0 ..@ assayData :<environment: 0x000000000e86a5d0> ..@ phenoData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots .. ..@ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..@ labelDescription: chr(0) .. ..@ data :'data.frame': 2 obs. of 0 variables .. ..@ dimLabels : chr [1:2] "sampleNames" "sampleColumns" .. ..@ .\_\_classVersion\_\_:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 1 .. ..@ .Data:List of 1 [1:3] 1 1 0 ..@ featureData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots .. ..@ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..@ labelDescription: chr(0) .. ..@ data :'data.frame': 22215 obs. of 0 variables .. ..@ dimLabels : chr [1:2] "featureNames" "featureColumns" .. ..@ .\_\_classVersion\_\_:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 1 .. ..@ .Data:List of 1 [1:3]

```
1 1 0 ..@ annotation : chr "HG-U133A" ..@ protocolData :Formal class 'AnnotatedDataFrame'
[package "Biobase"] with 4 slots .. ..@ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..
..$ labelDescription: chr(0) .. ..@ data :'data.frame': 2 obs. of 0 variables .. ..@ dimLabels
: chr [1:2] "sampleNames" "sampleColumns" .. ..@ .._classVersion__:Formal class 'Versions'
[package "Biobase"] with 1 slots .. ..@ .Data:List of 1 .. ..@ ..$ : int [1:3] 1 1 0 ..@
.._classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 4
.. ..@ ..$ : int [1:3] 3 1 0 .. ..@ ..$ : int [1:3] 2 23 6 .. ..@ ..$ : int [1:3] 1 3 0 .. ..@ ..$ : int [1:3] 1 0
0
```

## Examples

```
data(NumericalMixMCF7HS27)
str(NumericalMixMCF7HS27)
```

---

PureMCF7HS27

*pure MCF7 and HS27*

---

## Description

pure MCF7 and HS27 expression data

## Usage

```
data(PureMCF7HS27)
```

## Format

The format is: Formal class 'ExpressionSet' [package "Biobase"] with 7 slots ..@ experimentData :Formal class 'MIAME' [package "Biobase"] with 13 slots .. ..@ name : chr "" .. ..@ lab : chr "" .. ..@ contact : chr "" .. ..@ title : chr "" .. ..@ abstract : chr "" .. ..@ url : chr "" .. ..@ pubMedIds : chr "" .. ..@ samples : list() .. ..@ hybridizations : list() .. ..@ normControls : list() .. ..@ preprocessing : list() .. ..@ other : list() .. ..@ ..\_classVersion\_\_:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 2 .. ..@ ..\$ : int [1:3] 1 0 0 .. ..@ ..\$ : int [1:3] 1 1 0 ..@ assayData :<environment: 0x00000000e979d20> ..@ phenoData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots .. ..@ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..@ ..\$ labelDescription: chr(0) .. ..@ data :'data.frame': 2 obs. of 0 variables .. ..@ dimLabels : chr [1:2] "sampleNames" "sampleColumns" .. ..@ ..\_classVersion\_\_:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 1 .. ..@ ..\$ : int [1:3] 1 1 0 ..@ featureData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots .. ..@ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..@ ..\$ labelDescription: chr(0) .. ..@ data :'data.frame': 22215 obs. of 0 variables .. ..@ dimLabels : chr [1:2] "featureNames" "featureColumns" .. ..@ ..\_classVersion\_\_:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 1 .. ..@ ..\$ : int [1:3] 1 1 0 ..@ annotation : chr "HG-U133A" ..@ protocolData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots .. ..@ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..@ ..\$ labelDescription: chr(0) .. ..@ data :'data.frame': 2 obs. of 0 variables .. ..@ dimLabels : chr [1:2] "sampleNames" "sampleColumns" .. ..@ ..\_classVersion\_\_:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 1 .. ..@ ..\$ : int [1:3] 1 1 0 ..@ ..\_classVersion\_\_:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 4 .. ..@ ..\$ : int [1:3] 3 1 0 .. ..@ ..\$ : int [1:3] 2 23 6 .. ..@ ..\$ : int [1:3] 1 3 0 .. ..@ ..\$ : int [1:3] 1 0 0



**Examples**

```
data(PureMCF7HS27)
str(PureMCF7HS27)
```

---

two_source_deconv	<i>Main function to call other subfunction to deconvolute the mixed expression data.</i>
-------------------	--

---

**Description**

This is the main function that is to call all the other subfunctions and realize the deconvolution of mixed expression data. When the real mixing matrix exist, it will also compare the estimated mixing matrix and real mixing matrix and give the E1 measurement.

**Usage**

```
two_source_deconv(ExpressionData, lowerper = 0.4, highper = 0.1, epsilon1 = 0.01, epsilon2 = 0.01, A =
```

**Arguments**

ExpressionData	gene expression data matrix/ExpressionSet object
lowerper	The percentage of genes the user wants to remove with lowest norm. The range should be between 0 and 1.
highper	The percentage of genes the user wants to remove with highest norm. The range should be between 0 and 1.
epsilon1	Influence the number of marker genes. With increasing of epsilon1, the number marker genes in source 1 will increase. The value should be positive.
epsilon2	Influence the number of marker genes. With increasing of epsilon1, the number marker genes in source 2 will increase. The value should be positive.
A	real mixing matrix if existing
S1	Pure expression profile of first source if existing
S2	Pure expression profile of second source if existing
return	if it is equal to 0, do not return estimated S; otherwise, return the estimated S.

**Value**

Aest	estimated mixing matrix
E1	E1 measurement between real and estimated mixing matrix

**Author(s)**

Niya Wang (wangny@vt.edu)

**Examples**

```
data(NumericalMixMCF7HS27)
X <- NumericalMixMCF7HS27
deconvResult <- two_source_deconv(X, lowerper = 0.4, highper = 0.1, epsilon1 = 0.1, epsilon2 = 0.1, A = NULL, S1=N
```

# Index

## \*Topic **datasets**

BiologicalMixMCF7HS27, [2](#)

NumericalMixingMatrix, [7](#)

NumericalMixMCF7HS27, [7](#)

PureMCF7HS27, [8](#)

## \*Topic **methods**

UNDO-package, [2](#)

## \*Topic **package**

UNDO-package, [2](#)

BiologicalMixMCF7HS27, [2](#)

calc\_E1, [3](#)

dimension\_reduction, [4](#)

gene\_expression\_input, [4](#)

marker\_gene\_selection, [5](#)

mixing\_matrix\_computation, [6](#)

NumericalMixingMatrix, [7](#)

NumericalMixMCF7HS27, [7](#)

PureMCF7HS27, [8](#)

two\_source\_deconv, [9](#)

UNDO (UNDO-package), [2](#)

UNDO-package, [2](#)