

Package ‘canceR’

April 19, 2023

Type Package

Title A Graphical User Interface for accessing and modeling the Cancer Genomics Data of MSKCC

Version 1.33.0

Date 2022-04-27

Author Karim Mezhoud.
Nuclear Safety & Security Department.
Nuclear Science Center of Tunisia.

Maintainer Karim Mezhoud <kmezhoud@gmail.com>

Description The package is user friendly interface based on the cgdsr and other modeling packages to explore, compare, and analyse all available Cancer Data (Clinical data, Gene Mutation, Gene Methylation, Gene Expression, Protein Phosphorylation, Copy Number Alteration) hosted by the Computational Biology Center at Memorial-Sloan-Kettering Cancer Center (MSKCC).

License GPL-2

LazyLoad yes

Depends R (>= 4.1), tcltk

Imports GSEABase, tkrplot, geNetClassifier, RUnit, Formula, rpart, survival, Biobase, phenoTest, circlize, plyr, graphics, stats, utils, grDevices, R.oo, R.methodsS3, httr

Suggests testthat (>= 3.1), knitr, rmarkdown, BiocStyle

SystemRequirements Tktable, BWidget

VignetteBuilder knitr

BugReports <https://github.com/kmezhoud/canceR/issues>

biocViews GUI, GeneExpression, Clustering, GO, GeneSetEnrichment, KEGG, MultipleComparison

RoxygenNote 7.1.2

Encoding UTF-8

git_url <https://git.bioconductor.org/packages/canceR>

git_branch devel
git_last_commit 60e88c6
git_last_commit_date 2022-11-01
Date/Publication 2023-04-19

R topics documented:

| | |
|-----------------------------|----|
| about | 4 |
| canceR | 4 |
| canceR_Issue | 5 |
| canceR_Vignette | 5 |
| cbind.na | 6 |
| dialogGeneClassifier | 6 |
| dialoggetGeneListMSigDB | 7 |
| dialogMetOption | 8 |
| dialogMut | 9 |
| dialogOptionCircos | 9 |
| dialogOptionGSEAlm | 10 |
| dialogOptionPhenoTest | 11 |
| dialogPlotOption_SkinCor | 11 |
| dialogSamplingGSEA | 12 |
| dialogSelectFiles_GSEA | 13 |
| dialogSpecificMut | 13 |
| dialogSummary_GSEA | 14 |
| displayInTable | 15 |
| getCases | 15 |
| getCasesGenProfs | 16 |
| getCircos | 17 |
| getClinicalDataMatrix | 17 |
| getClinicData_MultipleCases | 18 |
| getCor_ExpCNAMet | 18 |
| geteSet | 19 |
| getGCTCLSExample | 20 |
| getGCT_CLSfiles | 20 |
| getGeneExpMatrix | 21 |
| getGeneList | 21 |
| getGeneListExample | 22 |
| getGeneListFromMSigDB | 22 |
| getGenesClassifier | 23 |
| getGenesTree_MultipleCases | 23 |
| getGenesTree_SingleCase | 24 |
| getGenProfs | 24 |
| getGSEAlm_Diseases | 25 |
| getGSEAlm_Variables | 26 |
| getInTable | 26 |
| getListProfData | 27 |
| getMegaProfData | 27 |

| | |
|--|----|
| getMetDataMultipleGenes | 28 |
| getMSigDB | 29 |
| getMSigDBExample | 29 |
| getMSigDBfile | 30 |
| getMutData | 30 |
| getPhenoTest | 31 |
| getProfilesDataMultipleGenes | 31 |
| getProfilesDataSingleGene | 32 |
| getSpecificMut | 33 |
| getSummaryGSEA | 33 |
| getSurvival | 34 |
| getTextWin | 34 |
| GSEA | 35 |
| GSEA.Analyze.Sets | 35 |
| GSEA.ConsPlot | 36 |
| GSEA.EnrichmentScore | 37 |
| GSEA.EnrichmentScore2 | 38 |
| GSEA.Gct2Frame | 39 |
| GSEA.Gct2Frame2 | 39 |
| GSEA.GeneRanking | 40 |
| GSEA.HeatMapPlot | 41 |
| GSEA.HeatMapPlot2 | 41 |
| GSEA.NormalizeCols | 42 |
| GSEA.NormalizeRows | 42 |
| GSEA.ReadClsFile | 43 |
| GSEA.Res2Frame | 43 |
| GSEA.Threshold | 44 |
| GSEA.VarFilter | 45 |
| GSEA.write.gct | 45 |
| Match_GeneList_MSigDB | 46 |
| modalDialog | 46 |
| myGlobalEnv | 47 |
| OLD.GSEA.EnrichmentScore | 48 |
| plotModel | 48 |
| plot_1Gene_2GenProfs | 49 |
| plot_2Genes_1GenProf | 49 |
| rbind.na | 50 |
| Run.GSEA | 51 |
| setWorkspace | 51 |
| testCheckedCaseGenProf | 52 |

about

about canceR

Description

about canceR

Usage

about()

Value

dialog box with text

Examples

```
## Not run:  
about()  
  
## End(Not run)
```

canceR

main function

Description

main function

Usage

canceR()

Value

open the starting windows with cancer studies

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())  
## Not run:  
canceR()  
  
## End(Not run)
```

| | |
|--------------|----------------------------|
| canceR_Issue | <i>canceR Report Issue</i> |
|--------------|----------------------------|

Description

canceR Report Issue

Usage

```
canceR_Issue()
```

Value

link to github issues

Examples

```
## Not run:  
canceR_Issue()  
  
## End(Not run)
```

| | |
|-----------------|--------------------------|
| canceR_Vignette | <i>open pdf vignette</i> |
|-----------------|--------------------------|

Description

open pdf vignette

Usage

```
canceR_Vignette()
```

Value

open pdf vignette

Examples

```
## Not run:  
canceR_Vignette()  
  
## End(Not run)
```

| | |
|----------|------------------------------|
| cbind.na | <i>bind non equal column</i> |
|----------|------------------------------|

Description

bind non equal column

Usage

```
cbind.na(..., deparse.level = 1)
```

Arguments

... (generalized) vectors or matrices.

deparse.level integer controlling the construction of labels in the case of non-matrix-like arguments (for the default method): deparse.level = 0 constructs no labels; the default, deparse.level = 1 or 2 constructs labels from the argument names.

Value

a data frame with merged columns

Examples

```
## Not run:
col1 <- c("a", "b", "c", "d")
col2 <- c("A", "B", "C")
col3 <- cbind.na(col1, col2)

## End(Not run)
```

| | |
|----------------------|---|
| dialogGeneClassifier | <i>Dialogue Box for gene classifier setting: sample size and postprob threshold</i> |
|----------------------|---|

Description

Dialogue Box for gene classifier setting: sample size and postprob threshold

Usage

```
dialogGeneClassifier(Lchecked_Cases, entryWidth = 10, returnValOnCancel = "ID_CANCEL")
```

Arguments

`Lchecked_Cases` integer with a number of checked cases
`entryWidth` integer default 10
`returnValOnCancel`
"ID_CANCEL"

Value

a dataframe with genes classes

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))  
## Not run:  
getGenesClassifier()  
dialogGeneClassifier(1,10,returnValOnCancel = "ID_CANCEL")  
  
## End(Not run)
```

`dialoggetGeneListMSigDB`

Multi-select choice of gene sets from loaded MSigDB

Description

Multi-select choice of gene sets from loaded MSigDB

Usage

```
dialoggetGeneListMSigDB(MSigDB)
```

Arguments

`MSigDB` object with MSigDB. A list of genesets

Value

a dataframe with genes classes

Examples

```
z <- 7
## Not run:
##MSigDB <- readLines(paste(.libPaths(), "/cancer/extdata/MSigDB/c5.bp.v4.0.symbols.gmt", sep=""))
dialoggetGeneListMSigDB(MSigDB)

## End(Not run)
```

| | |
|-----------------|--|
| dialogMetOption | <i>Dialog Box to set methylation options</i> |
|-----------------|--|

Description

Dialog Box to set methylation options

Usage

```
dialogMetOption(ProfData, k)
```

Arguments

| | |
|----------|----------------------------------|
| ProfData | adataframe with methylation data |
| k | threshold of silencing gene 0:1 |

Value

a dialog box to set methylation option (threshold of silencing gene)

Examples

```
readRDS(paste(path.package("cancerR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getMetDataMultipleGenes()
#dialogMetOption(ProfData, 0.7)

## End(Not run)
```

| | |
|-----------|--|
| dialogMut | <i>Dialog box to set returned Mutation information</i> |
|-----------|--|

Description

Dialog box to set returned Mutation information

Usage

```
dialogMut(title, question, entryInit, entryWidth = 40, returnValOnCancel = "ID_CANCEL")
```

Arguments

| | |
|-------------------|--------------------|
| title | title of the table |
| question | question |
| entryInit | entryInit |
| entryWidth | 40 |
| returnValOnCancel | "ID_CANCEL" |

Value

a check box with mutations variables

Examples

```
readRDS(paste(path.package("cancerR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
## Not run:  
dialogMut("title", "question", "entryInit", entryWidth = 40, returnValOnCancel = "ID_CANCEL")  
  
## End(Not run)
```

| | |
|--------------------|--------------------------------------|
| dialogOptionCircos | <i>Checkbox to select dimensions</i> |
|--------------------|--------------------------------------|

Description

Checkbox to select dimensions

Usage

```
dialogOptionCircos()
```

Value

a checkbox with all dimensions

Examples

```
readRDS(paste(path.package("canceR"),"/extdata/rdata/Circos.rds", sep=""))
## Not run:
dialogOptionCircos()
#getCircos(dimension ="All")

## End(Not run)
```

dialogOptionGSEAlm *Dialogbox to select variables from Clinical data*

Description

Dialogbox to select variables from Clinical data

Usage

```
dialogOptionGSEAlm(k,ClinicalData)
```

Arguments

k integer 1
ClinicalData dataframe with clinical variables

Value

permutaion value, p-value, coVariables

Examples

```
#data(ClinicalData)
## Not run:
getOptionGSEAlm()

## End(Not run)
```

dialogOptionPhenoTest *Checkbox to select variables from clinical data*

Description

Checkbox to select variables from clinical data

Usage

```
dialogOptionPhenoTest(eSet)
```

Arguments

eSet Expression Set

Value

vectors: variables to test Survival status, AGE, p-value

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
dialogOptionPhenoTest(myGlobalEnv$eSet)

## End(Not run)
```

dialogPlotOption_SkinCor
Checkbox to select variables for plotting

Description

Checkbox to select variables for plotting

Usage

```
dialogPlotOption_SkinCor(s)
```

Arguments

s integer number of Studies

Value

Dialog box with setting of correlation method

Examples

```
readRDS(paste(path.package("cancerR"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
## Not run:
dialogPlotOption_SkinCor(1)

## End(Not run)
```

| | |
|--------------------|--|
| dialogSamplingGSEA | <i>Dialog Box for Sampling patients from expression profile data used for GSEA-R (Broad Institute)</i> |
|--------------------|--|

Description

Dialog Box for Sampling patients from expression profile data used for GSEA-R (Broad Institute)

Usage

```
dialogSamplingGSEA( Lchecked_Cases, entryWidth = 10, returnValOnCancel = "ID_CANCEL")
```

Arguments

| | |
|-------------------|-------------------------|
| Lchecked_Cases | Number of checked Cases |
| entryWidth | 10 |
| returnValOnCancel | "ID_CANCEL" |

Value

A vector with sampling size

Examples

```
readRDS(paste(path.package("cancerR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
Run.GSEA()
#dialogSamplingGSEA(1, entryWidth=10, returnValOnCancel = "ID_CANCEL")

## End(Not run)
```

`dialogSelectFiles_GSEA`

Dialog Box to Select GCT, CLS, GMT and output Files for GSEA-R (Broad Institute)

Description

Dialog Box to Select GCT, CLS, GMT and output Files for GSEA-R (Broad Institute)

Usage

```
dialogSelectFiles_GSEA()
```

Value

A vector with files paths

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
dialogSelectFiles_GSEA()

## End(Not run)
```

`dialogSpecificMut`

dialog box to Specify Mutation using Regular Expression. Search specific mutation using regular expression.

Description

dialog box to Specify Mutation using Regular Expression. Search specific mutation using regular expression.

Usage

```
getSpecificMut()
```

Value

a dataframe with specific mutation informations

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getSpecificMut()

## End(Not run)
```

| | |
|--------------------|---|
| dialogSummary_GSEA | <i>Dialog Box to specify phenotype (variable) used in last GSEA-R to get Summary Results. This function ask the user to specify the phenotype (variable).</i> |
|--------------------|---|

Description

Dialog Box to specify phenotype (variable) used in last GSEA-R to get Summary Results. This function ask the user to specify the phenotype (variable).

Usage

```
dialogSummary_GSEA(Variable,returnValOnCancel ="ID_CANCEL")
```

Arguments

| | |
|-------------------|-------------|
| Variable | phenotype |
| returnValOnCancel | "ID_CANCEL" |

Value

variables

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
#Run.GSEA()
#getSummaryGSEA()

## End(Not run)
```

| | |
|----------------|--------------------------------------|
| displayInTable | <i>Display matrix in tcltk table</i> |
|----------------|--------------------------------------|

Description

Display matrix in tcltk table

Usage

```
displayInTable(tclarray, title="", height=-1, width=-1, nrow=-1, ncol=-1)
```

Arguments

| | |
|----------|--------------------|
| tclarray | a dataframe |
| title | title of the table |
| height | -1 |
| width | -1 |
| nrow | -1 |
| ncol | -1 |

Value

display a Table

Examples

```
#data(ClinicalData)
## Not run:
getInTable(Table= ClinicalData, title= "Clinical Data")

## End(Not run)
```

| | |
|----------|--|
| getCases | <i>Get cases for selected Studies. The Cases are the description of the samples from patients. The samples can be subdivided by the type of assays as, sequencing, CNA, Mutation, Methylation.</i> |
|----------|--|

Description

Get cases for selected Studies. The Cases are the description of the samples from patients. The samples can be subdivided by the type of assays as, sequencing, CNA, Mutation, Methylation.

Usage

```
getCases()
```

Value

a dataframe with cases

Examples

```
## Not run:
# Create CGDS object
cgds<-CGDS("http://www.cbioportal.org/")
# Get list of cancer studies at server
Studies <- getCancerStudies(cgds)[,2]
# Get available case lists (collection of samples) for a given cancer study
mycancerstudy <- getCancerStudies(cgds)[2,1]
mycaselist <- getCaseLists(cgds,mycancerstudy)[1,1]

##getCases()

## End(Not run)
```

getCasesGenProfs *get Cases and Genetic Profiles of selected Studies.*

Description

get Cases and Genetic Profiles of selected Studies.

Usage

```
getCasesGenProfs()
```

Value

This function is run by the "Get Cases and Genetic Profiles for selected Studies in starting window. This function needs to select at least one study and display Cases and genetic profiles in the main window.

Examples

```
##Load Session
readRDS(paste(path.package("canceR"),"/extdata/rdata/brca_tcga73genes.rds", sep=""))
## load Cases and Genetic Profiles
## Not run:
getCasesGenProfs()

## End(Not run)
```

| | |
|-----------|---|
| getCircos | <i>get Circos Layout for selected studies and selected dimensions</i> |
|-----------|---|

Description

get Circos Layout for selected studies and selected dimensions

Usage

```
getCircos(dimension)
```

Arguments

dimension string (All,mRNA, CNA, Met,RPPA, miRNA, Mut)

Value

a plot with Circos style

Examples

```
readRDS(paste(path.package("canceR"),"/extdata/rdata/Circos.rds", sep=""))
## Not run:
getCircos(dimension ="All")

## End(Not run)
```

| | |
|-----------------------|---|
| getClinicalDataMatrix | <i>get matrix with clinical from file</i> |
|-----------------------|---|

Description

get matrix with clinical from file

Usage

```
getClinicalDataMatrix()
```

Value

dataframe of clinicaldata

Examples

```
readRDS(paste(path.package("canceR"),"/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
getClinicalDataMatrix()

## End(Not run)
```

```
getClinicData_MultipleCases
```

get Clinical Data for Multiple Cases. User needs to select at least one case to run this function. Get clinical data for more one or multiple cases.

Description

get Clinical Data for Multiple Cases. User needs to select at least one case to run this function. Get clinical data for more one or multiple cases.

Usage

```
getClinicData_MultipleCases(getSummaryGSEAEExists)
```

Arguments

```
getSummaryGSEAEExists
```

if equal to 0, the clinical data is displayed in table. if the argument is equal to 1, the clinical data is used to summarise GSEA analysis results.

Value

dataframe with clinical data

Examples

```
##Load Session
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Select Case
myGlobalEnv <- new.env(parent = emptyenv())
myGlobalEnv$curselectCases <- 2
## get Clinical data
## Not run:
getClinicData_MultipleCases(getSummaryGSEAEExists = 0)

## End(Not run)
```

```
getCor_ExpCNAMet
```

Get gene correlation for multiple dimensions.

Description

Get gene correlation for multiple dimensions.

Usage

```
getCor_ExpCNAMet(ListMatrix, dimension)
```

Arguments

```
ListMatrix    is a List of numeric matrices  
dimension     Exp,CNA, Met , miRNA , RPPA
```

Value

correlation matrix

Examples

```
readRDS(paste(path.package("cancerR"),"/extdata/rdata/Circos.rds", sep=""))  
## Not run:  
getListProfData()  
getCor_ExpCNAMet(myGlobalEnv$ListProfData$Expression, dimension="mRNA")  
head(myGlobalEnv$Cor_Exp)  
  
## End(Not run)
```

geteSet

Built Expression Set (eSet) from profile data.

Description

Built Expression Set (eSet) from profile data.

Usage

```
geteSet()
```

Value

ExpressionSet

Examples

```
f <- 9  
## Not run:  
readRDS(paste(path.package("cancerR"),"/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))  
geteSet()  
  
## End(Not run)
```

| | |
|------------------|---------------------------------------|
| getGCTCLSExample | <i>get GCT and CLS example files.</i> |
|------------------|---------------------------------------|

Description

get GCT and CLS example files.

Usage

```
getGCTCLSExample()
```

Value

GCT and CLS files

Examples

```
## Load workspace
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getGCTCLSExample()

## End(Not run)
```

| | |
|-----------------|---|
| getGCT_CLSfiles | <i>get Profile (GCT file) and Phenotype (CLS file) Data from Disease.</i> |
|-----------------|---|

Description

get Profile (GCT file) and Phenotype (CLS file) Data from Disease.

Usage

```
getGCT_CLSfiles()
```

Value

GCT and CLS files paths

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getGCT_CLSfiles()

## End(Not run)
```

| | |
|------------------|--|
| getGeneExpMatrix | <i>get matrix with gene expression from file</i> |
|------------------|--|

Description

get matrix with gene expression from file

Usage

```
getGeneExpMatrix()
```

Value

dataframe of gene expression

| | |
|-------------|---|
| getGeneList | <i>User needs to specify which gene is interesting to get genomic cancer data. The gene must be with Symbol and one gene by line.</i> |
|-------------|---|

Description

User needs to specify which gene is interesting to get genomic cancer data. The gene must be with Symbol and one gene by line.

Usage

```
getGeneList()
```

Value

Gene list path of file

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())  
## Not run:  
getGeneList()  
  
## End(Not run)
```

| | |
|--------------------|--|
| getGeneListExample | <i>get Gene List from examples. User can select one from available gene list</i> |
|--------------------|--|

Description

get Gene List from examples. User can select one from available gene list

Usage

```
getGeneListExample()
```

Value

Gene list path of file

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())  
## Not run:  
getGeneListExample()  
  
## End(Not run)
```

| | |
|-----------------------|----------------------------------|
| getGeneListFromMSigDB | <i>get gene list from MSigDB</i> |
|-----------------------|----------------------------------|

Description

get gene list from MSigDB

Usage

```
getGeneListFromMSigDB()
```

Value

a vector with gene list

Examples

```
readRDS(paste(path.package("cancerR"), "/extdata/rdata/brca_tcgaGSEA1m1021.rds", sep=""))  
## Not run:  
getGeneListFromMSigDB()  
  
## End(Not run)
```

getGenesClassifier *get Genes Classifier*

Description

get Genes Classifier

Usage

```
getGenesClassifier()
```

Value

a data frma with genes classes

Examples

```
x <- 0
## Not run:
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
getGenesClassifier()

## End(Not run)
```

getGenesTree_MultipleCases
Get successively trees of genes list for multiple cases

Description

Get successively trees of genes list for multiple cases

Usage

```
getGenesTree_MultipleCases(entryWidth = 10)
```

Arguments

entryWidth 10

Value

plot tree

Examples

```

q <- readRDS(paste(path.package("cancerR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
readRDS(paste(.libPaths(), "/cancerR/data/brca_tcga73genes.rds", sep=""))
getGenesTree_MultipleCases(entryWidth = 10)

## End(Not run)

```

```

getGenesTree_SingleCase

```

classify genes in tree for two phenotypes in the same case(disease).

Description

classify genes in tree for two phenotypes in the same case(disease).

Usage

```

getGenesTree_SingleCase()

```

Value

tree plot

Examples

```

readRDS(paste(path.package("cancerR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
getGenesTree_SingleCase()

## End(Not run)

```

```

getGenProfs

```

Get Genetic Profile from selected Studies

Description

Get Genetic Profile from selected Studies

Usage

```

getGenProfs()

```

Value

dataframe with genetic profil

Examples

```
## Not run:
cgds<-CGDS("http://www.cbioportal.org/")
# Get list of cancer studies at server
Studies <- getCancerStudies(cgds)[,2]
# Get available case lists (collection of samples) for a given cancer study
mycancerstudy <- getCancerStudies(cgds)[2,1]
mycaselist <- getCaseLists(cgds,mycancerstudy)[1,1]
# Get available genetic profiles
mygeneticprofile <- getGeneticProfiles(cgds,mycancerstudy)[4,1]

getGenProfs()

## End(Not run)
```

getGSEAlm_Diseases *get GSEA linear modeling by studies (diseases)*

Description

get GSEA linear modeling by studies (diseases)

Usage

```
getGSEAlm_Diseases()
```

Value

a dataframe with annotation (GO, BP)

Examples

```
readRDS(paste(path.package("cancerR"),"/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getGSEAlm_Diseases

## End(Not run)
```

getGSEAlm_Variables *get GSEA linear modeling by variables (phenotype)*

Description

get GSEA linear modeling by variables (phenotype)

Usage

```
getGSEAlm_Variables()
```

Value

a dataframe with annotation (GO, BP)

Examples

```
x <- 3
## Not run:
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
getGSEAlm_Variables()

## End(Not run)
```

getInTable *get dataframe in TK/TCL table*

Description

get dataframe in TK/TCL table

Usage

```
getInTable(table, title)
```

Arguments

| | |
|-------|-----------------------------|
| table | Dataframe |
| title | string a title of the table |

Value

display a Table

Examples

```
#data(ClinicalData)
## Not run:
getInTable(Table= ClinicalData, title= "Clinical Data")

## End(Not run)
```

| | |
|-----------------|--|
| getListProfData | <i>get a list of Profile Data of every available dimensions. This function load matrices of every dimension (Exp, CNA, Met, RPPA,miRNA,Mut) and save them in a list for every disease.</i> |
|-----------------|--|

Description

get a list of Profile Data of every available dimensions. This function load matrices of every dimension (Exp, CNA, Met, RPPA,miRNA,Mut) and save them in a list for every disease.

Usage

```
getListProfData()
```

Value

a list of data frame with Profiles Data

Examples

```
readRDS(paste(path.package("canceR"),"/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
getListProfData()
head(myGlobalEnv$ProfData$Expression)

## End(Not run)
```

| | |
|-----------------|---|
| getMegaProfData | <i>Get profile data for more than 500 genes list.</i> |
|-----------------|---|

Description

Get profile data for more than 500 genes list.

Usage

```
getMegaProfData(MegaGeneList,k)
```

Arguments

MegaGeneList Genelist >500
k integer number of studies

Value

dataframewith profile data

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())  
readRDS(paste(path.package("cancerR"), "/extdata/rdata/brca_tcgaGSEA1m1021.rds", sep=""))  
## Not run:  
getMegaProfData(myGlobalEnv$MegaGeneList, 1)  
  
## End(Not run)
```

getMetDataMultipleGenes

get Methylation data for multiple genes

Description

get Methylation data for multiple genes

Usage

```
getMetDataMultipleGenes()
```

Value

a dataframe with mean and median of methylation rate (threshold of silencing gene)

Examples

```
readRDS(paste(path.package("cancerR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
## Not run:  
getMetDataMultipleGenes()  
  
## End(Not run)
```

getMSigDB *Reduce MSigDB size for only gene list*

Description

Reduce MSigDB size for only gene list

Usage

```
getMSigDB(eSet, k)
```

Arguments

| | |
|------|---------------------------|
| eSet | Expression Set |
| k | integer Number of studies |

Value

MSigDB for user gene List

Examples

```
d <- 7
## Not run:
setWorkspace()
getMSigDB(eSet = myGlobalEnv$eSetClassifier,k = 1)

## End(Not run)
```

getMSigDBExample *get example of .gmt file from MSigDB (Broad Institute)*

Description

get example of .gmt file from MSigDB (Broad Institute)

Usage

```
getMSigDBExample()
```

Value

path of GMT file

Examples

```
readRDS(paste(path.package("cancerR"),"/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
getMSigDBExample()

## End(Not run)
```

`getMSigDBfile`*Dialog Box to Select MSigDB Files from drive*

Description

Dialog Box to Select MSigDB Files from drive

Usage

```
getMSigDBfile()
```

Value

A path of MSigDB file

Examples

```
f <- 5+2
## Not run:
readRDS(paste(path.package("cancerR"),"/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
geteSet()
getMSigDBfile()

## End(Not run)
```

`getMutData`*get Mutation data for multiple genes*

Description

get Mutation data for multiple genes

Usage

```
getMutData()
```

Value

a dataframe with mutation informations

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getMutData()

## End(Not run)
```

| | |
|--------------|---|
| getPhenoTest | <i>Associate phenotype to Studies (cancers)</i> |
|--------------|---|

Description

Associate phenotype to Studies (cancers)

Usage

```
getPhenoTest()
```

Value

a dataframe with disease/ variables association

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
getPhenoTest(myGlobalEnv$set)

## End(Not run)
```

| | |
|------------------------------|--|
| getProfilesDataMultipleGenes | <i>get Profiles Data of multiple genes</i> |
|------------------------------|--|

Description

get Profiles Data of multiple genes

Usage

```
getProfilesDataMultipleGenes(getSummaryGSEAEExists)
```

Arguments

```
getSummaryGSEAEExists
```

if equal to 0, the clinical data is displayed in table. if the argument is equal to 1, the clinical data is used to summarise GSEA analysis results.

Value

a file with a dataframe of profile data

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
getProfilesDataMultipleGenes(getSummaryGSEAEExists = 0)

## End(Not run)
```

getProfilesDataSingleGene

get Profiles Data for a Single Gene.

Description

get Profiles Data for a Single Gene.

Usage

```
getProfilesDataSingleGene()
```

Value

dataframe with profiles data for a single gene

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Select Case from Breast Cancer
myGlobalEnv <- new.env(parent = emptyenv())
myGlobalEnv$curselectCases <- 9
##Select Genetic Profile from Breast Cancer
myGlobalEnv$curselectGenProfs <- 4
## get Specific Mutation data for 73 Genes list
## Not run:
getProfilesDataSingleGene()

## End(Not run)
```

| | |
|----------------|--|
| getSpecificMut | <i>get specific Mutation data for multiple genes</i> |
|----------------|--|

Description

get specific Mutation data for multiple genes

Usage

```
getSpecificMut()
```

Value

a dataframe with specific mutation informations

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getSpecificMut()

## End(Not run)
```

| | |
|----------------|--|
| getSummaryGSEA | <i>get Summary results from GSEA-R (Broad Institute)</i> |
|----------------|--|

Description

get Summary results from GSEA-R (Broad Institute)

Usage

```
getSummaryGSEA()
```

Value

Dataframe with summary results

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
Run.GSEA()
getSummaryGSEA()

## End(Not run)
```

getSurvival *Survival plot*

Description

Survival plot

Usage

```
getSurvival(Coxph)
```

Arguments

Coxph if Coxph = 0 : plot Kaplan-Meier curves else Coxph= 1 : plot Cox Proportional Hazard Model

Value

Survival plot

Examples

```
surv <- 11
## Not run:
readRDS(paste(path.package("canceR"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
getSurvival(Coxph = 1)

## End(Not run)
```

getTextWin *get text in tcltk windows*

Description

get text in tcltk windows

Usage

```
getTextWin(text)
```

Arguments

text string

Value

tcltk windows with text

Examples

```
text <- "mytext"
## Not run:
getTextWin(text)

## End(Not run)
```

GSEA

GSEA-R (Broad Institute)

Description

See http://www.broadinstitute.org/cancer/software/gsea/wiki/index.php/R-GSEA_Readme

Value

GSEA

Author(s)

Subramanian, Tamayo, et al. (2005, PNAS 102, 15545-15550) and Mootha, Lindgren, et al. (2003, Nat Genet 34, 267-273)

Examples

```
## Not run:
library(canceR)
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
##Run.GSEA()

## End(Not run)
```

GSEA.Analyze.Sets

GSEA.Analyze.Sets

Description

http://www.broadinstitute.org/cancer/software/gsea/wiki/index.php/R-GSEA_Readme

Usage

```
GSEA.Analyze.Sets(directory, topgs="", non.interactive.run= FALSE, height=12, width=17)
```

Arguments

```
directory      directory= fname.Output
topgs          topgs = 20
non.interactive.run
               non.interactive.run= FALSE
height        height=16
width         width=16
```

Value

GSEA.Analyze.Sets

Author(s)

Subramanian, Tamayo, et al. (2005, PNAS 102, 15545-15550) and Mootha, Lindgren, et al. (2003, Nat Genet 34, 267-273)

References

http://www.broadinstitute.org/cancer/software/gsea/wiki/index.php/Main_Page.

Examples

```
## Not run:
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
##Run.GSEA()

## End(Not run)
```

GSEA.ConsPlot

GSEA.ConsPlot

Description

GSEA.ConsPlot

Usage

```
GSEA.ConsPlot(V, col.names, main = " ", sub = " ", xlab = " ", ylab = " ")
```

Arguments

| | |
|-----------|----------------------|
| V | V="Itable" |
| col.names | col.names = colnames |
| main | main= " " |
| sub | sub = " " |
| xlab | xlab= " " |
| ylab | ylab = " " |

Value

GSEA.ConsPlot

Examples

```
## Not run:
library(canceR)
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
##Run.GSEA()

## End(Not run)
```

GSEA.EnrichmentScore *GSEA.EnrichmentScore*

Description

GSEA.EnrichmentScore

Usage

```
GSEA.EnrichmentScore(gene.list, gene.set, weighted.score.type = 1, correl.vector = NULL)
```

Arguments

gene.list
gene.set
weighted.score.type

correl.vector

Value

GSEA.EnrichmentScore

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.EnrichmentScore2 *GSEA.EnrichmentScore2*

Description

GSEA.EnrichmentScore2

Usage

```
GSEA.EnrichmentScore2(gene.list, gene.set, weighted.score.type = 1, correl.vector = NULL)
```

Arguments

gene.list
gene.set
weighted.score.type

correl.vector

Value

GSEA.EnrichmentScore2

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

| | |
|----------------|-----------------------|
| GSEA.Gct2Frame | <i>GSEA.Gct2Frame</i> |
|----------------|-----------------------|

Description

GSEA.Gct2Frame

Usage

GSEA.Gct2Frame(filename = "NULL")

Arguments

filename

Value

GSEA.GCT2Frame

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

| | |
|-----------------|------------------------|
| GSEA.Gct2Frame2 | <i>GSEA.Gct2Frame2</i> |
|-----------------|------------------------|

Description

GSEA.Gct2Frame2

Usage

GSEA.Gct2Frame2(filename = "NULL")

Arguments

filename

Value

GSEA.GCT2Frame2

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.GeneRanking

GSEA.GeneRanking

Description

GSEA.GeneRanking

Arguments

A
class.labels
gene.labels
nperm
permutation.type

sigma.correction

fraction
replace
reverse.sign

Value

GSEA.GeneRanking

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

| | |
|------------------|-------------------------|
| GSEA.HeatMapPlot | <i>GSEA.HeatMapPlot</i> |
|------------------|-------------------------|

Description

GSEA.HeatMapPlot

Value

GSEA.HeatMapPlot

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

| | |
|-------------------|--------------------------|
| GSEA.HeatMapPlot2 | <i>GSEA.HeatMapPlot2</i> |
|-------------------|--------------------------|

Description

GSEA.HeatMapPlot2

Value

GSEA.HeatMapPlot2

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.NormalizeCols *GSEA.NormalizeCols*

Description

GSEA.NormalizeCols

Usage

GSEA.NormalizeCols(V)

Arguments

V

Value

GSEA.NormalizeCols

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
## Load workspace
##Run.GSEA()

## End(Not run)
```

GSEA.NormalizeRows *GSEA.NormalizeRows*

Description

GSEA.NormalizeRows

Usage

GSEA.NormalizeRows(V)

Arguments

V

Value

GSEA.NormalizeRows

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

| | |
|------------------|-------------------------|
| GSEA.ReadClsFile | <i>GSEA.ReadClsFile</i> |
|------------------|-------------------------|

Description

GSEA.ReadClsFile

Usage

```
GSEA.ReadClsFile(file = "NULL")
```

Arguments

file

Value

GSEA.ReadClsFile

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
## Not run:  
##Run.GSEA()  
  
## End(Not run)
```

| | |
|----------------|-----------------------|
| GSEA.Res2Frame | <i>GSEA.Res2Frame</i> |
|----------------|-----------------------|

Description

GSEA.Res2Frame

Usage

```
GSEA.Res2Frame(filename = "NULL")
```

Arguments

filename

Value

GSEA.NormalizeCols

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
## Not run:  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.Threshold

GSEA.Threshold

Description

GSEA.Threshold

Usage

GSEA.Threshold(V, thres, ceil)

Arguments

V

thres

ceil

Value

GSEA.Threshold

Examples

```
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
## Not run:  
  
##Run.GSEA()  
  
## End(Not run)
```

| | |
|----------------|-----------------------|
| GSEA.VarFilter | <i>GSEA.VarFilter</i> |
|----------------|-----------------------|

Description

GSEA.VarFilter

Usage

```
GSEA.VarFilter(V, fold, delta, gene.names = "NULL")
```

Arguments

```
V  
fold  
delta  
gene.names
```

Value

GSEA.VarFilter

Examples

```
## Load workspace  
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
## Not run:  
##Run.GSEA()  
  
## End(Not run)
```

| | |
|----------------|-----------------------|
| GSEA.write.gct | <i>GSEA.write.gct</i> |
|----------------|-----------------------|

Description

GSEA.write.gct

Usage

```
GSEA.write.gct(gct, filename)
```

Arguments

```
gct  
filename
```

Value

GSEA.Write.gct

Examples

```
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:

##Run.GSEA()

## End(Not run)
```

Match_GeneList_MSigDB *Search MSigDb that overlap gene list*

Description

Search MSigDb that overlap gene list

Usage

Match_GeneList_MSigDB

Value

GeneList

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
Match_GeneList_MSigDB()

## End(Not run)
```

modalDialog *Dialog box to specify Gene Symbol.*

Description

Dialog box to specify Gene Symbol.

Usage

```
modalDialog(title, question, entryInit, entryWidth = 40, returnValOnCancel = "ID_CANCEL")
```

Arguments

| | |
|-------------------|-------------|
| title | string |
| question | string |
| entryInit | entryInit |
| entryWidth | 40 |
| returnValOnCancel | "ID_CANCEL" |

Value

dialog box

Examples

```
readRDS(paste(path.package("canceR"),"/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Select Case from Breast Cancer
myGlobalEnv <- new.env(parent = emptyenv())
myGlobalEnv$curselectCases <- 9
##Select Genetic Profile from Breast Cancer
myGlobalEnv$curselectGenProfs <- 4
## get Specific Mutation data for 73 Genes list
## Not run:
getProfilesDataSingleGene()

## End(Not run)
```

myGlobalEnv

myGlobalEnv

Description

Global environment to store canceR variables.

Format

The format is: <environment: 0xb3eb240>

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())
```

OLD.GSEA.EnrichmentScore
OLD.GSEA.EnrichmentScore

Description

OLD.GSEA.EnrichmentScore

Arguments

gene.list
 gene.set

Value

OLD.GSEA.EnchmentScore

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
##Run.GSEA()

## End(Not run)
```

plotModel *model plotting with tcltk*

Description

model plotting with tcltk

Usage

```
plotModel(plotCommand, title= "TITLE", hscale=1, vscale=1 )
```

Arguments

| | |
|-------------|------------------|
| plotCommand | plotcommand |
| title | title of plot |
| hscale | horizintal scale |
| vscale | vertical scale |

Value

plot

Examples

```
readRDS(paste(path.package("canceR"),"/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
## Not run:
plot_1Gene_2GenProfs()

## End(Not run)
```

plot_1Gene_2GenProfs *Plotting two genetic profiles for one Gene*

Description

Plotting two genetic profiles for one Gene

Usage

```
plot_1Gene_2GenProfs()
```

Value

plot

Examples

```
readRDS(paste(path.package("canceR"),"/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
## Not run:
plot_1Gene_2GenProfs()

## End(Not run)
```

plot_2Genes_1GenProf *plot correlation of two genes expressions.*

Description

plot correlation of two genes expressions.

Usage

```
plot_2Genes_1GenProf()
```

Value

plot

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
plot_2Genes_1GenProf()

## End(Not run)
```

rbind.na

bind non equal row

Description

bind non equal row

Usage

```
rbind.na(..., deparse.level = 1)
```

Arguments

... (generalized) vectors or matrices.

deparse.level integer controlling the construction of labels in the case of non-matrix-like arguments (for the default method): deparse.level = 0 constructs no labels; the default, deparse.level = 1 or 2 constructs labels from the argument names.

Value

a data frame with merged rows

Examples

```
## Not run:
row1 <- c("a", "b", "c", "d")
row2 <- c("A", "B", "C")
row3 <- rbind.na(row1, row2)

## End(Not run)
```

| | |
|----------|---|
| Run.GSEA | <i>The main function to run GSEA-R from Broad Institute</i> |
|----------|---|

Description

The main function to run GSEA-R from Broad Institute

Usage

```
Run.GSEA()
```

Value

A vector with sampling size

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
## Not run:  
Run.GSEA()  
  
## End(Not run)
```

| | |
|--------------|---|
| setWorkspace | <i>Setting work Directory and output folders.At starting window, user needs to set work directory for output data. The function is foud in File menu.</i> |
|--------------|---|

Description

Setting work Directory and output folders.At starting window, user needs to set work directory for output data. The function is foud in File menu.

Usage

```
setWorkspace()
```

Value

paths of output files

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))  
## Not run:  
setWorkspace()  
  
## End(Not run)
```

testCheckedCaseGenProf

Testing checked appropriate Cases for appropriate Genetic profiles.

Description

Testing checked appropriate Cases for appropriate Genetic profiles.

Usage

```
testCheckedCaseGenProf()
```

Value

dialog box with warning message

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))  
## Not run:  
testCheckedCaseGenProf()  
  
## End(Not run)
```

Index

- * **datasets**
 - myGlobalEnv, [47](#)
- about, [4](#)
- cancer, [4](#)
- cancer_Issue, [5](#)
- cancer_Vignette, [5](#)
- cbind.na, [6](#)
- dialogGeneClassifier, [6](#)
- dialoggetGeneListMSigDB, [7](#)
- dialogMetOption, [8](#)
- dialogMut, [9](#)
- dialogOptionCircos, [9](#)
- dialogOptionGSEAlm, [10](#)
- dialogOptionPhenoTest, [11](#)
- dialogPlotOption_SkinCor, [11](#)
- dialogSamplingGSEA, [12](#)
- dialogSelectFiles_GSEA, [13](#)
- dialogSpecificMut, [13](#)
- dialogSummary_GSEA, [14](#)
- displayInTable, [15](#)
- getCases, [15](#)
- getCasesGenProfs, [16](#)
- getCircos, [17](#)
- getClinicalDataMatrix, [17](#)
- getClinicData_MultipleCases, [18](#)
- getCor_ExpCNAMet, [18](#)
- geteSet, [19](#)
- getGCT_CLSfiles, [20](#)
- getGCTCLSExample, [20](#)
- getGeneExpMatrix, [21](#)
- getGeneList, [21](#)
- getGeneListExample, [22](#)
- getGeneListFromMSigDB, [22](#)
- getGenesClassifier, [23](#)
- getGenesTree_MultipleCases, [23](#)
- getGenesTree_SingleCase, [24](#)
- getGenProfs, [24](#)
- getGSEAlm_Diseases, [25](#)
- getGSEAlm_Variables, [26](#)
- getInTable, [26](#)
- getListProfData, [27](#)
- getMegaProfData, [27](#)
- getMetDataMultipleGenes, [28](#)
- getMSigDB, [29](#)
- getMSigDBExample, [29](#)
- getMSigDBfile, [30](#)
- getMutData, [30](#)
- getPhenoTest, [31](#)
- getProfilesDataMultipleGenes, [31](#)
- getProfilesDataSingleGene, [32](#)
- getSpecificMut, [33](#)
- getSummaryGSEA, [33](#)
- getSurvival, [34](#)
- getTextWin, [34](#)
- GSEA, [35](#)
- GSEA.Analyze.Sets, [35](#)
- GSEA.ConsPlot, [36](#)
- GSEA.EnrichmentScore, [37](#)
- GSEA.EnrichmentScore2, [38](#)
- GSEA.Gct2Frame, [39](#)
- GSEA.Gct2Frame2, [39](#)
- GSEA.GeneRanking, [40](#)
- GSEA.HeatMapPlot, [41](#)
- GSEA.HeatMapPlot2, [41](#)
- GSEA.NormalizeCols, [42](#)
- GSEA.NormalizeRows, [42](#)
- GSEA.ReadClsFile, [43](#)
- GSEA.Res2Frame, [43](#)
- GSEA.Threshold, [44](#)
- GSEA.VarFilter, [45](#)
- GSEA.write.gct, [45](#)
- Match_GeneList_MSigDB, [46](#)
- modalDialog, [46](#)
- myGlobalEnv, [47](#)

OLD.GSEA.EnrichmentScore, [48](#)

plot_1Gene_2GenProfs, [49](#)

plot_2Genes_1GenProf, [49](#)

plotModel, [48](#)

rbind.na, [50](#)

Run.GSEA, [51](#)

setWorkspace, [51](#)

testCheckedCaseGenProf, [52](#)