

Package ‘psygenet2r’

August 7, 2022

Title psygenet2r - An R package for querying PsyGeNET and to perform comorbidity studies in psychiatric disorders

Version 1.29.0

Description Package to retrieve data from PsyGeNET database (www.psygenet.org) and to perform comorbidity studies with PsyGeNET's and user's data.

Depends R (>= 3.4)

License MIT + file LICENSE

LazyData true

Imports stringr, RCurl, igraph, ggplot2, reshape2, grid, parallel, biomaRt, BgeeDB, topGO, Biobase, labeling, GO.db

Suggests testthat, knitr, rmarkdown

NeedsCompilation no

VignetteBuilder knitr

biocViews Software, BiomedicalInformatics, Genetics, Infrastructure, DataImport, DataRepresentation

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/psygenet2r>

git_branch master

git_last_commit 253c4b6

git_last_commit_date 2022-04-26

Date/Publication 2022-08-07

Author Alba Gutierrez-Sacristan [aut, cre],
Carles Hernandez-Ferrer [aut],
Jaun R. Gonzalez [aut],
Laura I. Furlong [aut]

Maintainer Alba Gutierrez-Sacristan <a.gutierrez.sacristan@gmail.com>

R topics documented:

DataGeNET.Psy-class	2
enrichedPD	3
extract	4
extractSentences	5
geneAttrPlot	6
getUMLs	6
jaccardEstimation	7
JaccardIndexPsy-class	8
ndisease	9
ngene	9
pantherGraphic	10
plot,DataGeNET.Psy,ANY-method	11
plot,JaccardIndexPsy,ANY-method	12
psygenet2r	13
psygenetDisease	13
psygenetDiseaseSentences	14
psygenetGene	15
psygenetGeneSentences	16
qr	17
topAnatEnrichment	17
universe	18
Index	20

DataGeNET.Psy-class *Class DataGeNET.Psy*

Description

Class `DataGeNET.Psy` is the basic object use in `psygenet2r` package. It is the main data container to using the different functions to query `PsyGeNET` database and generate their output. The constructors of this class are the functions `psygenetGene` and `psygenetDisease`.

Slots

`type` Character containing 'gene' of 'disease'. It is used to perform the correct query to `PsyGeNET`.

`search` Character containing 'single' of 'list'. It is used to perform the correct query to `PsyGeNET`.

`database` Character containing the name of the database that will be queried. It can take the values 'MODELS' to use Comparative Toxigenomics Database, data from mouse and rat; 'GAD' to use Genetic Association Database; 'CTD' to use Comparative Toxigenomics Database, data from human; 'PsyCUR' to use Psychiatric disorders Gene association manually curated; 'CURATED' to use Human, manually curated databases (PsyCUR and CTD); or 'ALL' to use all these databases.

term Character with the term(s) to search into the database(s).
 result data.frame with the obtained result

See Also

psygenetGene, psygenetDisease, DataGeNET.Psy-methods

enrichedPD *Enrichment of a user's input (genes) in PsyGeNET's diseases.*

Description

Test the enrichment of a given gene list on Psychiatric Disorders from PsyGeNET.

Usage

```
enrichedPD(gene, database = "ALL", verbose = FALSE, warnings = FALSE)
```

Arguments

gene	Name or vector of names (that can be both code or uml) to specific genes from PsyGeNET.
database	Name of the database that will be queried. It can take the values 'psycur15' to use data validated by experts for first release of PsyGeNET; 'psycur16' to use data validated by experts for second release of PsyGeNET; or 'ALL' to use both databases. Default 'ALL'.
verbose	By default FALSE. Change it to TRUE to get a on-time log from the function.
warnings	By default TRUE. Change it to FALSE to not see the warnings.

Value

A data.frame with the enrichment at each Psychiatric Disorder

Examples

```
enrichedPD(c("ADCY2", "AKAP13", "ANK3"), "ALL")
```

extract	<i>Raw data from DataGeNET.Psy and JaccardIndexPsy.</i>
---------	---

Description

Obtain the raw data from a PsyGeNET's query stored in a DataGeNET.Psy object or the raw data with all the Jaccard Index for the disease of interest of an JaccardIndexPsy object.

Usage

```
extract(object, ...)

## S4 method for signature 'DataGeNET.Psy'
extract(object)

## S4 method for signature 'JaccardIndexPsy'
extract(object, order.cl = "pval", ...)
```

Arguments

object	Object of class DataGeNET.Psy or JaccardIndexPsy
...	NO USED
order.cl	Order resulting data.frame by the name of this column.

Value

A data.frame containing the raw result from PsyGeNET or a data.frame with the result Jaccard Index for each disease.

A data.frame containing the raw result from PsyGeNET

A data.frame with the result Jaccard Index for each disease.

Methods (by class)

- DataGeNET.Psy: Extract function for DataGeNET.Psy
- JaccardIndexPsy: Extract function for JaccardIndexPsy

Examples

```
data(qr)
extract(qr)[1:2, ] # get internat data.frame
## Not run:
#Being x an JaccardIndexPsy
extract(x)

## End(Not run)
```

extractSentences	<i>Method to obtain the sentences that support a gene-disease association from a DataGeNET.Psy object.</i>
------------------	--

Description

PsyGeNET contains a list of sentences that support a gene-disease association from public literature. The internal table of a DataGeNET.Psy object contains this information. The method extractSentences allows to extract those sentences that support a gene-disease association given a DataGeNET.Psy object and a disorder of interest.

Usage

```
extractSentences(object, disorder, verbose)

## S4 method for signature 'DataGeNET.Psy'
extractSentences(object, disorder, verbose = FALSE)
```

Arguments

object	Object of class DataGeNET.Psy.
disorder	The disorder of interest. Only those sentences supporting a gene-disease association with this specific disorder will be extracted. Disorder must be provided by using "Disease Id" or "Disease Name". The "Disease Id" can be provided with or without the "uml" tag. Example of a "Disease Name": "schizophrenia"; Example of a "Disease Id": "umls:C0036341", that is equivalent of using "C0036341".
verbose	If set to TRUE informative messages are show.

Value

A data frame showing the sentences.

Methods (by class)

- DataGeNET.Psy: Get sentences or evidences

Examples

```
data(qr)
extractSentences(qr, "Depression")
```

geneAttrPlot *Plotting the relation between genes and disease-categories*

Description

Given a set of genes or a result of psygenetGene creates four types of plots showing the relation of the genes with the disease's category in psyGeNET.

Usage

```
geneAttrPlot(x, type = "pie", ..., verbose = FALSE)
```

Arguments

x	Vector of genes of interest of DataGeNET.Psy resulting of psygenetDisease.
type	Type of the drawn chart. By default it is "pie". It can takes "pie" to plot a pie chart with the number of genes for each psychiatric category, "disease category" for visualizing a barplot with the total and specific number of genes for each psychiatric disorder, "evidence index" for a barplot showing for each psychiatric disorder the number of gene-disease associations according to the Evidence index and "gene" for visualizing a barplot with the total and specific number of diseases associated to each gene.
...	(Check NOTE section) Passed to inner functions for different plots.
verbose	By default FALSE. Change it to TRUE to get a on-time log from the function.

Value

A plot for a DataGeNET.Psy in terms of the panther-class.

Note

The "Evidence Index" is gotten from PsyGeNET. For more information about it and its calculation, please visit psygenet.org. Argument ... can be filled with specific argument depending on the type of plot:

Type	Argument	Color	Description
gene	cuiBarColor	Purple	Determines the color of the bar for diseases
	diseaseCategoryBarColor	Yellow	Determines the color of the bar for psychiatric categories
disease category	uniqueGenesBarColor	Orange	Determines the color of the bar for unique genes for a disease category
	totalGenesBarColor	Blue	Determines the color of the bar for total genes for a disease category

getUMLs *Query PsyGeNET for given gene(s) and generates an DataGeNET.Psy*

Description

Given the name of one or multiple gene and retrieves their information from PsyGeNET and creates an object of type DataGeNET.Psy.

Usage

```
getUMLs(word, database = "ALL")
```

Arguments

word	Disease to convert to UMLS using PsyGeNET database.
database	Name of the database that will be queried. It can take the values 'psycur15' to use data validated by experts for first release of PsyGeNET; 'psycur16' to use data validated by experts for second release of PsyGeNET; or 'ALL' to use both databases. Default 'ALL'.

Value

The corresponding UMLs for the input disease/s

Examples

```
umls <- getUMLs( word = "depressive", database = "ALL" )
```

jaccardEstimation *Calculation of the Jaccard Index between diseases*

Description

This function is able to calculate the Jacard Index between: 1. multiple diseases, 2. a set of genes and multiple diseases, 3. a set of genes and multiple main psychiatric disorders and 4. multiple diseases and multiple main psychiatric disorders.

Usage

```
jaccardEstimation(pDisease, sDisease, database = "ALL", nboot = 100,
  ncores = 1, verbose = FALSE)
```

Arguments

pDisease	vector of diseases, vector of genes, vector of main psychiatric disorder.
sDisease	vector of diseases, vector of genes, vector of main psychiatric disorder. Only necessary when comparing genes vs. diseases, genes vs. main psychiatric disorders or diseases vs. main psychiatric disorders. To compare multiple diseases only use pDisease.

database	Name of the database that will be queried. It can take the values 'psycur15' to use data validated by experts for first release of PsyGeNET; 'psycur16' to use data validated by experts for second release of PsyGeNET; or 'ALL' to use both databases.
nboot	Number of iterations used to compute the pvalue associated to the calculated Jaccard Index (default 100).
ncores	Number of cores used to calculate the pvalue associated to the computed Jaccard Index (default 1).
verbose	By default FALSE. Change it to TRUE to get a on-time log from the function.

Details

Warning: The main psychiatric disorders are understood as a single set of genes composed by the genes of all the diseases that the main psychiatric disorder contains.

Value

An object of class JaccardIndexPsy with the computed calculation of the JaccardIndex.

Examples

```
ji <- jaccardEstimation( c( "COMT", "CLOCK", "DRD3" ), "umls:C0005586", "ALL" )
```

JaccardIndexPsy-class *Class JaccardIndexPsy*

Description

Class JaccardIndexPsy is the result of the process to look for a Jaccard Index between multiple diseases in psygenet2r package.

Slots

nit Number of iterations to calculate the estimated Jaccard index
 type Slot to save type of query (disease-disease, gene-disease)
 table data.frame containing the result table of Jaccard indexes
 i1 [internal use] vector with names of first component
 i2 [internal use] vector with names of second component

See Also

psygenetGene, psygenetDisease, JaccardIndexPsy-methods

Examples

```
ji <- jaccardEstimation( c( "COMT", "CLOCK", "DRD3" ), "umls:C0005586", "ALL" )
```

ndisease	<i>Getter from DataGeNET.Psy.</i>
----------	-----------------------------------

Description

Obtain the number of unique diseases in a DataGeNET.Psy.

Usage

```
ndisease(object)

## S4 method for signature 'DataGeNET.Psy'
ndisease(object)
```

Arguments

object Object of class DataGeNET.Psy.

Value

The number of unique diseases

Methods (by class)

- DataGeNET.Psy: Get number of diseases

Examples

```
data(qr)
ndisease(qr)
```

ngene	<i>Getter from DataGeNET.Psy.</i>
-------	-----------------------------------

Description

Obtain the number of unique genes in a DataGeNET.Psy.

Usage

```
ngene(object)

## S4 method for signature 'DataGeNET.Psy'
ngene(object)
```

Arguments

object Object of class DataGeNET.Psy.

Value

The number of unique genes

The number of unique genes

Methods (by class)

- DataGeNET.Psy: Get number of genes

Examples

```
data(qr)
ngene(qr)
```

pantherGraphic	<i>Query PsyGeNET for given genes and creates a representation in base of their panther-class</i>
----------------	---

Description

Given a vector of genes of interest (or using a DataGeNET.Psy object), this function creates a representation of a the panther-class these genes belongs to.

Usage

```
pantherGraphic(x, database = "ALL", evidenceIndex, verbose = FALSE)
```

Arguments

x Vector of genes of interest of DataGeNET.Psy resulting of psyegnetDisease.

database Name of the database that will be queried. It can take the values 'psycur15' to use data validated by experts for first release of PsyGeNET; 'psycur16' to use data validated by experts for second release of PsyGeNET; or 'ALL' to use both databases. Default 'ALL'.

evidenceIndex threshold to take into account a gene in the analysis

verbose By default FALSE. Change it to TRUE to get a on-time log from the function.

Value

A plot for a DataGeNET.Psy in terms of the panther-class.

Examples

```
d.alch <- pantherGraphic( c( "COMT", "CLOCK", "DRD3" ), "ALL" )
```

```
plot,DataGeNET.Psy,ANY-method
Plots the content of a DataGeNET.Psy object
```

Description

This functions llows to create a variety of plots for DataGeNET.Psy and JaccardIndexPsy objects.

Usage

```
## S4 method for signature 'DataGeNET.Psy,ANY'
plot(x, y,
     layout = igraph::layout.fruchterman.reingold, type = "GDA network",
     verbose = FALSE, ...)
```

Arguments

x	Object of class DataGeNET.Psy
y	NOT USED
layout	Function to design the location of the different nodes. By default layout.fruchterman.reingold from igraph is used.
type	Type of the drawn chart. By default it is "GDA network" but it also can be "GDCA network", "GDCA heatmap", "GDA heatmap" and "publications". The first two are network representations of the second two. While the last one draws a barplot with the number of PMIDs between genes and diseases.
verbose	By default FALSE. If set to TRUE information on the drawing process will be shown.
...	(Check NOTE section) Passed to inner functions for different plots.

Value

A plot for DataGeNET.Psy.

Note

The "Evidence Index" is gotten from PsyGeNET. For more information about it and its calculation, please visit psygenet.org. Argument ... can be filled with specific argument depending on the type of plot:

Type	Argument	Color	Description
GDA network	geneColor	Yellow	Determines the color of the gene nodes
	diseaseColor	Blue	Determines the color of the disease nodes
GDA heatmap	highColor	Blue	Determines the color of the heatmap for the highest value
	lowColor	White	Determines the color of the heatmap for the lowest value
GDCA network	ei0color	Yellow	Determines the color for those associations with evidence index 0
	eiAmbiguitcolor	Grey	Determines the color for those associations with evidence index greater than 0

GDCA heatmap	eilcolor	Blue	Determines the color for those associations with evidence index 1
	AUDcolor	#FF3C32	
	BDcolor	#FFC698	
	DEPcolor	#9BE75E	
	SCHZcolor	#1F6024	
	CUDcolor	#5AB69C	
	SIDEPcolor	#50B8D6	
	CanUDcolor	#5467C3	
	SYPSYcolor	#A654C3	
geneColor	Orange		

Examples

```
data(qr)
plot(qr) # for all-disease plot
plot(qr, type = 'GDCA network') # for MPI plot
```

```
plot, JaccardIndexPsy, ANY-method
```

Plot the content of a JaccardIndexPsy object.

Description

This functions llows to create a variety of plots for DataGeNEt.Psy and JaccardIndexPsy objects.

Usage

```
## S4 method for signature 'JaccardIndexPsy,ANY'
plot(x, y, cutOff, zero.remove = TRUE,
     noTitle = FALSE, lowColor = "white", highColor = "mediumorchid4",
     verbose = FALSE, ...)
```

Arguments

x	Object of class JaccardIndexPsy.
y	NOT USED
cutOff	Number to filter the shown results.
zero.remove	By deffault TRUE. It removes those relations with a Jaccard Index of 0.
noTitle	By default FALSE. If set to true no title will be added to the plot.
lowColor	By default "white". It can be changed to any other color.
highColor	By default "mediumorchid4". It can be changed to any other color.
verbose	By default FALSE. If set to TRUE information on the drawing process will be shown.
...	NOT USED

Value

A plot for JaccardIndexPsy.

Examples

```
## Not run:
#Being x an JaccardIndexPsy
qr <- plot(x)

## End(Not run)
```

psygenet2r	<i>psygenet2r: Package to query PsyGeNET database and to perform comorbidity studies</i>
------------	--

Description

psygenet2r has two categories of functions: querying functions and analysis and plotting functions.

querying functions

The functions to retrieve data from PsyGeNET are [psygenetDisease](#) and [psygenetGene](#). There are some other support functions like [psygenetGeneSentences](#).

analysis and plotting functions

The functions [extract](#) and [extractSentences](#) allows to retrieve the row data obtained from on-line resources. The functions [plot](#) and [pantherGraphic](#) draws a variety of charts to illustrate the obtained results. The function [enrichedPD](#) was built to perform enrichment studies on PsyGeNET data. Finally the function [jaccardEstimation](#) computes a Jaccard Index from a given input on PsyGeNET data.

psygenetDisease	<i>Query PsyGeNET for given disease(s) and generates an DataGeNET.Psy</i>
-----------------	---

Description

Given the name of one or multiple diseases and retrieves their information from PsyGeNET and creates an object of type DataGeNET.Psy.

Usage

```
psygenetDisease(disease, database = "ALL", evidenceIndex = c(">", 0),
  verbose = FALSE, warnings = TRUE)
```

Arguments

disease	Name or vector of names (that can be both code or uml) to specific diseases from PsyGeNET. The diseases non existing in PsyGeNET will be removed from the output.
database	Name of the database that will be queried. It can take the values 'psycur15' to use data validated by experts for first release of PsyGeNET; 'psycur16' to use data validated by experts for second release of PsyGeNET; or 'ALL' to use both databases. Default 'ALL'.
evidenceIndex	A vector with two elements: 1) character with greather '>' or with lower '<' meaing greather or equal and lower or equal; 2) the evidence index cut-off to be compared. By default: c('>', 0).
verbose	By default FALSE. Change it to TRUE to get a on-time log from the function.
warnings	By default TRUE. Change it to FALSE to don't see the warnings.

Value

An object of class `DataGeNET.Psy`

Note

The "Evidence Index" is gotten from PsyGeNET. For more information about it and its calculation, please visit psygenet.org.

Examples

```
d.sch <- psygenetDisease( "schizophrenia", "ALL" )
```

psygenetDiseaseSentences

Query PsyGeNET for given disease(s) and extract the pmids sentences that report a gene-disease association.

Description

Given a disease or a disease list, retrieves the pmids and sentences for each gene-disease association from PsyGeNET and creates an object of type `DataGeNET.Psy`.

Usage

```
psygenetDiseaseSentences(diseaseList, database = "ALL", verbose = FALSE)
```

Arguments

diseaseList	Name or vector of names (that can be both code or uml) to specific diseases from PsyGeNET. The diseases non existing in PsyGeNET will be removed from the output.
database	Name of the database that will be queried. It can take the values 'psycur15' to use data validated by experts for first release of PsyGeNET; 'psycur16' to use data validated by experts for second release of PsyGeNET; or 'ALL' to use both databases. Default 'ALL'.
verbose	By default FALSE. Change it to TRUE to get a on-time log from the function.

Value

An object of class DataGeNET.Psy

Examples

```
diseasesOfInterest <- c( "Bipolar Disorder", "Depressive Disorder, Major" )
psyDisSen <- psygenetDiseaseSentences( diseaseList = diseasesOfInterest,
                                       database = "ALL" )
```

psygenetGene *Query PsyGeNET for given gene(s) and generates an DataGeNET.Psy*

Description

Given the name of one or multiple gene and retrieves their information from PsyGeNET and creates an object of type DataGeNET.Psy.

Usage

```
psygenetGene(gene, database = "ALL", evidenceIndex = c(">", 0),
             verbose = FALSE, warnings = TRUE)
```

Arguments

gene	Name or vector of names (that can be both code or symbol) to specific genes from PsyGeNET. The genes non existing in PsyGeNET will be removed from the output.
database	Name of the database that will be queried. It can take the values 'psycur15' to use data validated by experts for first release of PsyGeNET; 'psycur16' to use data validated by experts for second release of PsyGeNET; or 'ALL' to use both databases. Default 'ALL'.
evidenceIndex	A vector with two elements: 1) character with greather '>' or with lower '<' meaing greather or equal and lower or equal; 2) the evidence index cut-off to be compared. By default: c('>', 0).
verbose	By default FALSE. Change it to TRUE to get a on-time log from the function.
warnings	By default TRUE. Change it to FALSE to not see the warnings.

qr	DataGeNET.Psy obtained from querying PsyGeNET for gene '4852'.
----	--

Description

A dataset obtained from PsyGeNET after being queried with psygenetGene using the term '4852' on "ALL" database.

Usage

```
data("qr")
```

Format

The format is: Formal class 'DataGeNET.Psy' [package "psygenet2r"] with 5 slots .. type : chr "gene" .. search : chr "" .. database: chr "ALL" .. term : chr "4852" .. qresult : 'data.frame'

Value

A DataGeNET.Psy object.

Source

<http://psygenet.org>

Examples

```
ngene(qr)
ndisease(qr)
```

topAnatEnrichment	<i>Enrichment of a user's input (genes) in anatomical terms (TopAnat).</i>
-------------------	--

Description

Test the enrichment of a given gene list on Psychiatric Disorders from PsyGeNET.

Usage

```
topAnatEnrichment(gene, datatype = c("rna_seq", "affymetrix", "est",
  "in_situ"), statistic = "fisher", cutOff = 1, verbose = FALSE,
  warnings = FALSE)
```

Arguments

gene	Name or vector of names (that can be both code or uml) to specific genes from PsyGeNET.
datatype	It can take the values 'rna_seq', 'affymetrix', "est" or "in situ". Default c("rna_seq", "affymetrix", "est", "in_situ").
statistic	By default it is "fisher". But it can be changed to "ks", "t", "globaltest", "sum" or "ks.ties". All from runTest .
cutOff	Default 1.
verbose	By default FALSE. Change it to TRUE to get a on-time log from the function.
warnings	By default TRUE. Change it to FALSE to not see the warnings.

Value

A data.frame with the enrichment results

Examples

```
## Not run:
topAnatEnrichment(gene=c("ADCY2", "AKAP13", "ANK3"))

## End(Not run)
```

universe	<i>Vector with gene universe for Jaccard Index</i>
----------	--

Description

Vector with all the gene names from DisGeNET database (<http://www.disgenet.org>) used as gene universe for Jaccard Index computation.

Usage

```
universe
```

Format

An object of class character of length 8947.

Details

```
data("universe", package = "psygenet2r")
```

Value

A character vector.

universe

19

Source

<http://www.disgenet.org>

Examples

```
length(universe)
universe[1:10]
```

Index

* datasets

qr, [17](#)
universe, [18](#)

DataGeNET.Psy-class, [2](#)
DataGeNET.Psy-plot
(plot,DataGeNET.Psy,ANY-method),
[11](#)

enrichedPD, [3](#), [13](#)
extract, [4](#), [13](#)
extract,DataGeNET.Psy-method (extract),
[4](#)
extract,JaccardIndexPsy-method
(extract), [4](#)
extractSentences, [5](#), [13](#)
extractSentences,DataGeNET.Psy-method
(extractSentences), [5](#)

geneAttrPlot, [6](#)
getUMLs, [6](#)

jaccardEstimation, [7](#), [13](#)
JaccardIndexPsy-class, [8](#)
JaccardIndexPsy-plot
(plot,JaccardIndexPsy,ANY-method),
[12](#)

ndisease, [9](#)
ndisease,DataGeNET.Psy-method
(ndisease), [9](#)
ngene, [9](#)
ngene,DataGeNET.Psy-method (ngene), [9](#)

pantherGraphic, [10](#), [13](#)
plot,DataGeNET.Psy,ANY-method, [11](#)
plot,JaccardIndexPsy,ANY-method, [12](#)
psygenet2r, [13](#)
psygenet2r-package (psygenet2r), [13](#)
psygenetDisease, [13](#), [13](#)
psygenetDiseaseSentences, [14](#)

psygenetGene, [13](#), [15](#)
psygenetGeneSentences, [13](#), [16](#)

qr, [17](#)

runTest, [18](#)

topAnatEnrichment, [17](#)

universe, [18](#)